

CLIFTON ADHESIVE INC -- CS 5338 -- 8030-00-272-8530

=====  
Product Identification  
=====

Product ID:CS 5338  
MSDS Date:01/19/1995  
FSC:8030  
NIIN:00-272-8530  
Status Code:A  
MSDS Number: CHXRM  
=== Responsible Party ===  
Company Name:CLIFTON ADHESIVE INC  
Address:BURGESS PL  
Box:282  
City:WAYNE  
State:NJ  
ZIP:07474-0282  
Country:US  
Info Phone Num:201-694-0845  
Emergency Phone Num:201-694-0845  
CAGE:79833  
=== Cont  
ractor Identification ===  
Company Name:CLIFTON ADHESIVE INC  
Address:BURGESS PL  
Box:City:WAYNE  
State:NJ  
ZIP:07470  
Country:US  
Phone:201-694-0845; 973-694-0845  
CAGE:79833  
Company Name:DUNBAR SALES CORP  
Address:39 AVENUE C  
Box:City:BAYONNE  
State:NJ  
ZIP:07002-3417  
Country:US  
Phone:201-437-6500  
CAGE:2G164

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLATUM  
CAS:8009-03-8  
Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP AND WATER; GET MED AID. EYES: FLUSH WITH MUCH WATER; GET MED AID. INGEST: TREAT SYMPTOMATICALLY; GET MED AID.

===== Fire Fighting Measures =====

Extinguishing Media:FOR DRY FILM: CO2, FOAM, DRY CHEMICAL  
Fire Fighting Procedures:NIOSH/MSHA APPROVED SCUBA; DRY FILM WILL BURN;  
COOL EXPOSED SURFACES WITH WATER SPRAY

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB IN SAND, EARTH, VERMICULITE, OIL-DRI, OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND HOT SURFACES;  
DO NOT STORE BELOW 40F OR ABOVE 90F

===== Exposure Controls/Personal Protection =====

Ventilation:AS SPECIFIED - LOCAL EXHAUST; MECHANICAL EXHAUST (EXPLOSION PROOF EQUIPMENT)  
Protective Gloves:REQUIRED  
Eye Protection:SAFETY GLASSES  
Work Hygienic Practices:KEEP AREA CLEAN; CLEAN UP SPILLS IMMEDIATELY;  
PRACTICE GOOD PERSONAL HYGEINE  
Supplemental Safety and Health  
EXPOSURE LIMITS ARE FOR AIR LEVELS ONLY. WHEN SKIN CONTACT OCCURS, OVEREXPOSURE MAY RESULT THOUGH AIR LEVELS ARE LESS THAN LIMITS LISTED UNDER INGREDIENTS

===== Physical/Chemical Properties =====

Spec Gravity:920

Appearance and Odor:SOLID AT ROOM TEMP; MILD BLAND ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:KEEP FROM OXIDIZING AGENTS

Hazardous Decomposition Products:OXIDES OF CARBON

===== Disposal Considerations =====

Waste Dispo

sal Methods:PER FED, STATE, AND LOCAL CHEMICAL AND SOLVENT  
REGS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.