View NSN Online: https://aerobasegroup.com/nsn/8010-01-302-6838

NILES CHEMICAL PAINT CO. -- N-6238B 2K HAZE GRAY T-IIIF#151 -- 8010-01-302-6838

Product ID:N-6238B 2K HAZE GRAY T-IIIF#151 MSDS Date:12/03/1997 FSC:8010 NIIN:01-302-6838 Kit Part:Y MSDS Number: CHXSR === Responsible Party === Company Name: NILES CHEMICAL PAINT CO. Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Info Phone Num:616-683-3377 Emergency Phone Num:219-236-5856 Preparer's Name: MICHAEL LICHATOWICH CAGE:02388 === Contractor Identification === Company Name: NILES CHEMICAL PAINT Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Phone:616-683-3377/219-236-5856 CAGE:02388

======= Composition/Information on Ingredients ==========

Ingred Name:EPOXY RESIN CAS:25068-38-6 RTECS #:KC2100000 Fraction by Wt: 53% Other REC Limits:NONE RECOMMENDED

Ingred Name:TALC (CONTAINING ASBESTOS) CAS:14807 -96-6 RTECS #:MW2700000 Fraction by Wt: 26% Other REC Limits:NONE RECOMMENDED OSHA PEL:2MG/M3 ACGIH TLV:2MG/M3

Ingred Name:#100 SOLVENT CAS:64742-95-6 Fraction by Wt: 19% Other REC Limits:NONE RECOMMENDED

Ingred Name:RHEOLOGICAL ADDITIVE Fraction by Wt: 1% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and C
hronic:EYES: SEVERE IRRITATION, LACRIMATION,
REDNESS, BLURRED VISION; SKIN: REDNESS/IRRITATION DEFATTING LEADING
TO DERMOTITISO INHALE: NASAL/RESP IRRITATION, CNS DEPRESSION,
NAUSEA, HEADACHE, VERTIGO, UNCON SCIOUSNESS, ASPHYXIATION;
SWALLOWING: GI IRRITATION, ABDOMINAL PAIN, NAUSEA, VOMITING,
DIARRHEA.
Explanation of Carcinogenicity:NO
Effects of Overexposure:LIVER/KIDNEY/CNS/LUNG HAZARD, NUSSANCE DUST,
DRYNESS OF SKIN

======= First Aid Measures ======

First Aid:INHALE: REMOVE TO FRESH AIR IMMED; GIVE CPR; GET MED AID ASAP. SKIN: ** EYE: IMMED FLUSH WITH MUCH WATER AT LEAST 15 MINUTES LIFTING UPPER/LOWER LIDS; GET MED AID IMMED; DO NOT WEAR CONTACT LENSES WHI LE WORKING. INGEST: DRINK 1 OR 2 GLASSES OF WATER; DO NOT INDUCE VOMITING; GET MED AID IMMED; TREAT SYMPTOMATICALLY.

Flash Point Method:TCC Flash Point:107F,38C Lower Limits:1.9 Upper Limits:12.0

Extinguishing Media:DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:WEAR SCUBA WITH FULL FACEPIECE IN POSITIVE

PRESSURE MODE; FULL PROTECTIVE CLOTHING; WATER MAY BE USED TO COOL CONTAINERS TO PREVENT EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED; ISOLATE FROM ALL IGNITABLES; CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT; EXPOSURE TO DECOMP PRODUCTS MAY CAUSE HAZARDS.*

Spill Release Procedures: ELIMINATE ALL IGNITABLES; MINIMIZE ALL CONTACT WITH PRODUCT; DIKE; AVOID RUNOFF INTO SOIL, SEWERS, OR WATERWAYS. ABSORB WITH INERT MATERIAL SUCH AS CLAY, SOIL, OR A COMMERCIALLY AVAILABLE ABSORBENT; SH OVEL INTO SALVAGE DRUMS FOR DISPOSAL.

Handling and Storage Precautions:AVLOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR IGNITABLES; KEEP CONTAINERS CLOSED; AVOID ROUGH HANDLING.

Othe

r Precautions:EMPTY CONTAINERS MAY BE HAZARDOUS; DO NOT WELD/FLAME CUT ON EMPTY DRUMS; SHOCK FROM DROPPING MAY SPLIT CONTAINER.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:WEAR AN APPROPRIATE (TYPE TC-23C-75) PROPERLY FITTED HALF-MASK OR FULL FACEPIECE RESPIRATOR (NIOSH/MSHA).

Ventilation:SUFFICIENT VENTILATION REQUIRED; REMOVE DECOMP PRODUCTS FORMED DURING WELDING/FLAME CUTTING.

Protective Gloves: CHEMICAL RESISTANT NITRILE/VITON

Eye P

rotection:CHEMICAL SAFETY GOGGLES/FACE SHIELD.

Other Protective Equipment: CHEMICAL RESISTANT CLOTHING.

Work Hygienic Practices: WASH IMMED UPON CONTAMINATION; REMOVE ANY WET CLOTHING AND WASH BEFORE REUSE; WASH BEFORE EATING, SMOKING, USING TOILET

Supplemental Safety and Health

VAPORS ARE HVR THAN AIR AND MAY TRAVEL ALONG GROUND TO AN IGNITION SOURCE **SKIN: IMMED FLUSH W/MUCH WTR. IMMED REMOVE CONTAM CLOTHING. FLUSH SKIN W/WTR. GET MED AID WASH CLOTHING AND DECONTAM SHO E

S BEFORE REUSE

Boiling Pt:B.P. Text:318F,100C Vapor Density:>AIR Spec Gravity:1.276 VOC Grams/Liter:2.04 Viscosity:80-88KU Evaporation Rate & amp; Reference: