

EXXON CO USA, A DIV OF EXXON CORP. -- EXXSOL D 60 SOLVENT -- 6850-00-274-5421
===== Product Identification =====

Product ID:EXXSOL D 60 SOLVENT
MSDS Date:08/27/1986
FSC:6850
NIIN:00-274-5421
Status Code:A
MSDS Number: CHYYD
=== Responsible Party ===
Company Name:EXXON CO USA, A DIV OF EXXON CORP.
Address:800 BELL ST
Box:2180
City:HOUSTON
State:TX
ZIP:77252-2180
Country:US
Info Phone Num:713-870-6
000/6884 (HEALTH)
Emergency Phone Num:800-726-2015/800-424-9300(CHEMTREC)
CAGE:29700
=== Contractor Identification ===
Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC
Address:2210 HACKBERRY LN
Box:687
City:CONROE
State:TX
ZIP:77305
Country:US
Phone:409-756-1065
CAGE:4N760
Company Name:EXXON COMPANY U.S.A.
Address:Box:2180
City:HOUSTON
State:TX
ZIP:77252-2180
Country:US
Phone:713-656-5949 / 713-656-3424
CAGE:29700

===== Composition/Information on Ingredients =====

Ingred

Name:PETROLEUM HYDROCARBON/SEVERELY HYDROTREATED LIGHT
DISTILLATE

CAS:64742-47-8

RTECS #:OA5504000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:143F,62C

Lower Limits:1.4

Upper Limits:9.3

Extinguishing Media:WATER FOG OR SPRAY,DRY CHEMICAL,CARBON
DIOXIDE,FOAM.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL

PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER
FOG.

Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

=====
===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:360-419F

Melt/Freeze Pt:M.P/F.P Text:-32F,-36C

Vapor Pres:3

Evaporation Rate & Reference:0.1 (N-BUTYL ACETATE=1)

Solubility in Water: