

OCTAGON PROCESS INC. -- VV-L800C AM.2, OCTOIL 90-2A, 3012301 -- 9150-00-231-9045  
===== Product Identification =====

Product ID:VV-L800C AM.2, OCTOIL 90-2A, 3012301

MSDS Date:06/19/1998

FSC:9150

NIIN:00-231-9045

Status Code:A

MSDS Number: CJFCL

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-313

-1187

Emergency Phone Num:201-945-9400

Resp. Party Other MSDS Num.:CSS-14165

Preparer's Name:J.J. BURGARD

Chemtrec Ind/Phone:(800)424-9300

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

===== Composition/Information on Ingredients =====

Ingred Name:OIL MIST, MINERAL

===== Hazards Identification =====

LD50 LC5

0 Mixture:TLV FOR OIL MIST (MINERAL) IS 5 MG/M3.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE AND CHRONIC- MAY CAUSE MILD EYE IRRITATION AND REDNESS. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD TO MODERATE IRRITATION. NO ADVERSE EFFECTS EXPECTED BY INHALATION. PRACTICALLY NON-TOXIC BY INGESTION. MAY CAUSE SLIGHT IRRITATION TO THE GASTROINTESTINAL TRACT.

Explanation of Car

cinogenicity:NONE SPECIFIED MY MFR MSDS.

Effects of Overexposure:EYE, SKIN AND GASTROINTESTINAL TRACT IRRITATION

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:EYES-FLOOD WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN-WASH WITH SOAP & WATER. INHALATION-NONE NORMALLY REQUIRED. INGESTED-GIVE LIQUIDS AND INDUCE VOMITING UNLESS VICTIM IN UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:=160.C, 320.F

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2 (CARBON DIOXIDE).

Fire Fighting Procedures:KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER FOG. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED.

Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. STOP LEAK. DIKE & CONTAIN SPILLS. USE PUMP TO TRANSFER LARGE SPILLS TO CONTAINER FOR DISPOSAL. REMAINING LIQUID/SMALL SPILLS CAN BE TAKEN UP ON SAND, CLAY, EARTH & SHOVE LED INTO CONTAINERS. PREVENT RUN-OFF TO ENTER WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MFR MSDS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE

IN COOL PLACE AWAY FROM  
INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.  
Other Precautions:CLEAN CONTAMINATED EQUIPMENT BEFORE STARTING ANY  
REPAIR WORK.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF WORKING IN A CONFINED  
AREA OR MISTING IS OCCURING, USE NIOSH-APPROVED RESPIRATORY  
PROTECTION.

Ventilation:USE LOCAL EXHAUST OF MECHANICAL VENTILATION (FAN).

Protective Gloves:RUBBEROR NEOPRENE.

Ey

e Protection:SAFETY GLASSES OR GOGGLES WHEN HANDLING CHEMICALS.

Other Protective Equipment:PROVIDE LOCAL EMERGENCY SHOWERS AND EYE WASH  
STATIONS.

Work Hygienic Practices:ALL USERS SHOULD CONSULT MSDS BEFORE HANDLING  
THIS MATERIAL. WASH HANDS AND FACE AFTER HANDLING MATERIAL.  
LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. DISPOSE OF OIL SOAKED  
FOOTWARE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:=287.8C, 5

50.F

Vapor Pres: