GEO.PFAU'S SONS CO,INC. -- PEACOCK EWS LARD OIL -- 9150-00-265-9406

Product ID:PEACOCK EWS LARD OIL MSDS Date:10/27/1999 FSC:9150 NIIN:00-265-9406 Status Code:A **MSDS Number: CJFNN** === Responsible Party === Company Name: GEO. PFAU'S SONS CO, INC. Address:800 WALL STREET Box:7 City: JEFFERSONVILLE State:IN ZIP:47130-3619 Country:US Info Phone Num:812-283-6697 Emergenc y Phone Num:812-283-6697 CAGE:2W231 === Contractor Identification === Company Name: GEO. PFAU'S SONS CO, INC. Address:800 WALL STREET Box:7 City: JEFFERSONVILLE State:IN ZIP:47130-3619 Country:US Phone:812-283-6697 CAGE:2W231 Company Name: SALATHE OIL CO INC Address:2226 PETERS RD Box:City:HARVEY State:LA ZIP:70058 Country:US Phone:504-366-4542 Contract Num:SP0450-00-M-D118 CAGE:0T5C6 Company Name: SALATHE OIL CO INC Address:2226 PETERS RD Box:City:HARVEY State:LA ZIP:70058 Country:US Phone:504-366-45

42 Contract Num:SP0450-98-M-CQ14 CAGE:0T5C6 Company Name:SDB CONSULTANTS LTD Address:401 WHITNEY AVE SUITE 120 Box:City:GRETNA State:LA ZIP:70056 Country:US Phone:504-366-9105 CAGE:0PGK2 Ingred Name:LARD, OIL (NON-HAZARDOUS) CAS:8016-28-2 = Wt:100. Other REC Limits:NONE RECOMMENDED Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogeni city:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYES AND SKIN. ACUTE -SKIN CONTACT, AMBIENT: SLIGHT IRRITATION MAY OCCUR. ELEVATED TEMPERATURE: OIL-TYPE BURNS MAY OCCUR. EYE CONTACT, AMBIENT: SLIGHT EYE IRRITATION MAY OCCUR. ELEVATE D TEMPERATURE: VAPOR MAY CAUSE IRRITATION. OIL-TYPE BURNS MAY OCCUR. ON DIRECT CONTACT. INHALATION, AMBIENT: NONE ANTICIPATED. ELEVATED TEMPERATURE: MAY PRODUCE VARIOUS CARBON OXIDES WHICH CAUSE IRRIT ATION TO T HE RESPIRATORY TRACT. INGESTION: NOT EXPECTED TO BE ACUTELY TOXIC -MAY HAVE A LAXATIVE EFFECT. CHRONIC - AS RECEIVED, MATERIAL IS NOT KNOWN TO HAVE CHRONIC TOXIC EFFECTS. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, BURNS (IF HOT)

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: MOVE AFFECTED SUBJECT TO FRESH AIR. EYES: FLUSH WITH GENTLE RUNNING WATER AND CONSULT PHYSICI AN. SKIN: WASH AFFECTED SKIN AREAS WITH SOAP AND WATER. IF H OT OIL-TYPE BURNS, TREAT AS SUCH. INGESTION: CONSULT PHYSICIAN.

Flash Point Method:COC

Flash Point:=260.C, 500.F

Extinguishing Media:USE NO WATER. TREAT AS AN OIL FIRE. USE CARBON DIOXIDE, FOAMITE, SAND OR SODIUM BICARBONATE.

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE GEAR TO PREVENT CONTACT W

ITH

SKIN AND EYES.

Unusual Fire/Explosion Hazard:HAZARD: COMBUSTION GENERATES TOXIC FUMES CONTAINING CARBON OXIDES.

Spill Release Procedures:SPILL AREAS MAY BE SLICK OR SLIPPERY. USE CARE TO AVOID FALLS OR OTHER ACCIDENTS. WEAR PROTECTIVE EQUIPMENT. PROVIDE ADEQUATE VENTILATION. CONTAIN SPILLS IMMEDIATELY WITH INERT MATERIAL SUCH AS SAND, CLAY, EARTH, ETC.. RECOVER FREE OIL IF POSSIBLE. MATERIAL CAN BE REMOVED FROM THE GROUND BY PUMP, SHOVEL

AND/OR ABORBTION AND PLACED IN A PROPER CONTAINER FOR DISPOSAL. PREVENT ENTRY TO SEWERS.

Handling and Storage Precautions: MAINTAIN TEMPERATURE AT A MAXIMUM 50 C FOR STORAGE. AVOID STORAGE AND TRANSFER FACILITIES CONSTRUCTED OF COPPER, COPPER ALLOYS AND ELEMENTS 24 THROUGH 30 (CR, MN, FE, CO, NI, CU, ZN).

Other Precautions: AVOID BREATHING VAPORS, IF HOT. DO NOT GET IN EYES,

ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. LAUNDER BEFORE REUSE. K EEP OUT OF REACH OF CHILDREN.

Respiratory Protection:NEEDED ONLY AT ELEVATED TEMPERATURES OR UNDER CONDITIONS OF MISTING. USE AN OSHA OR NIOSH APPROVED RESPIRATOR. Ventilation:WITH USE OF PRODUCT AT AMBIENT TEMPERATURE, NONE REQUIRED OTHER GENERAL PURPO SE VENTILATION. LOCAL EXHAUST RECOMMEND AT ELEVATED TEMP.***(SEE BELOW)

Protective Gloves: GLOVES ARE GENERALLY NOT REQUIRED AT AMBIENT TEMP **(SEE BELOW)

Eye Protection: SAFETY GLASSES OR FACE SHIELD AT AMBIENT. GOGGLES OR FACE MASK REQUIRED.

Other Protective Equipment:BOOTS AND APRON WHEN PRODUCT IS HEATED. NONE AT AMBLENT-NORMAL OIL RESISTANT THEMAL PROTECTION WHEN HEATED. Supplemental Safety and Health

**UNLESS INDIVIDUAL DISPLAYS SIGNS OF IRRITATION FROM EXPOSURE. AT TEMP.

ABOVE AMBIENT, NORMAL OIL-RESISTANT THERMAL PROTECTION IS RECOMMENDED.***OR IN THE PRESENCE OF MIST OR FUMES.

HCC:V6 Melt/Freeze Pt:=7.2C, 45.F M.P/F.P Text:POUR POINT,ASTM D97 Vapor Pres:1 AIR=1 Spec Gravity:.905-.915@25C H20=1 Viscosity:190-210 SUS @100F Evaporation Rate & amp; Reference: