

GC THORSEN ELECTRONICS -- VINYLITE CEMENT

=====  
MSDS Safety Information  
=====

FSC: 8040  
NIIN: 00-264-3838  
MSDS Date: 09/13/1993  
MSDS Num: CJFPP  
Product ID: VINYLITE CEMENT  
MFN: 01  
Responsible Party  
Cage: 72653  
Name: GC THORSEN ELECTRONICS  
Address: 1801 MORGAN STREET  
City: ROCKFORD IL 61105-1209  
Info Phone Number: 815-968-9661  
Emergency Phone Number: (800)424-9300  
Preparer's Name: M WINSEL  
Chemtrec IND/Phone: (800)424-9300  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 72653  
Name: GC THORSEN  
Address: 1801 MORGAN STREET  
City: ROCKFORD IL 61105  
Phone: 815-968-9661

=====  
Item Description Information  
=====

=====  
Item Manager: GSA  
Item Name: ADHESIVE  
Unit of Issue: BT  
Quantitative Expression: 00000000002OZ  
UI Container Qty: 0

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Signs And Symptions Of Overexposure: DIZZINESS, NAUSEA, SKIN AND EYE IRRITATION  
First Aid: EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. REMOVE CONTACT LENSES.

GET MEDICAL ATTENTION. SKIN: FLUSH WITH COPIOUS AMOUNTS OF WATER AND SOAP. IF IRRITATION PERSISTS, SEE DR. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF NEEDED. INGESTION: DO NOT INDUCE VOMITING. CALL DR.

=====  
Handling and Disposal  
=====

Spill Release Procedures: PICK UP WITH INERT ABSORBANT MATERIAL. STORE IN STEEL METAL CONTAINERS.

Waste Disposal Methods: LICENSED INCINERATOR OR PER GOVERNMENT REGULATIONS.

Handling And Storage Precautions: STORE IN COOL, DRY AREA, AWAY FROM IGNITION SOURCE.

Other Precautions: USE WITH ADEQUATE VENTILATION.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: CC

Flash Point: =-20.C, -4.F

Extinguishing Media: CO2, CHEMICAL FOAM

Fire Fighting Procedures: VENTILATE AREA WELL. AVOID BREATHING FUMES. USE SCUBA.

Unusual Fire/Ex

plosion Hazard: TOXIC FUMES RESULT FROM COMBUSTION.

=====  
Control Measures  
=====

Respiratory Protection: LICENSED RESPIRATOR IF TLV IS EXCEEDED.

Ventilation: LOCAL, MECHANICAL, TO MEET TLV.

Protective Gloves: AS NEEDED TO AVOID SKIN CONTACT.

Eye Protection: GOGGLES, SAFETY GLASSES

Other Protective Equipment: AS NECESSARY TO AVOID SKIN CONTACT  
=====

=  
Physical/Chemical Properties  
=====

Boiling Point: =55.6C, 132.F

Vapor Pres: 185 MM HG

Vapor Density: >1

Spec Gravity: .79

VOC Grams/Liter: 458

Evaporation Rate & Reference: 7.7

Solubility in Water: NOT

Appearance and Odor: CLEAR, COLORLESS LIQUID WITH ACETONE ODOR.

Percent Volatiles by Volume: 58  
=====

Reactivity Data  
=====

Stability Ind

icator: YES

Stability Condition To Avoid: HEAT AND IGNITION SOURCES

Materials To Avoid: STRONG OXIDIZERS

Hazardous Decomposition Products: CO, CO2

Hazardous Polymerization Indicator: NO

=====  
Regulatory Information  
=====

Sara Title III Information: VINYL ACETATE RESIN  
=====

HAZCOM Label  
=====

Prod

uct ID: VINYLITE CEMENT

Cage: 72653

Company Name: GC THORSEN

Street: 1801 MORGAN STREET

City: ROCKFORD IL

Zipcode: 61105

Health Emergency Phone: (800)424-9300

Label Required IND: Y

Date Of Label Review: 10/12/1999

Status Code: A

Origination Code: G  
=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verif

y

and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.