

FARWEST PAINT MFG CO -- WHITE STENCIL PAINT COLOR #37875 -- 8010-00-285-4933

=====
Product Identification
=====

Product ID:WHITE STENCIL PAINT COLOR #37875

MSDS Date:03/01/1998

FSC:8010

NIIN:00-285-4933

Status Code:A

MSDS Number: CJGBQ

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-

8844

Emergency Phone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBON (PER MSDS:CAS # 64742-89-8).

Fraction by Wt: 12.12%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM PER MFG

ACGIH TLV:300 PPM PER MFG

Ingred Name:TOLUENE (SAR

A III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 2.89%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA, SOLVENT
CAS:8032-32-4
RTECS #:WJ8925000
Fraction by Wt: 11.62%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2900 MG/M3;500 PPM
ACGIH TLV:525 MG/M3;100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogen

icity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: PROLONGED/REPEATED CONTACT: MAY CAUSE IRRITAITON, SENSITIZATION, OR DEFATTING. INHAL:EXCESSIVE EXPOSURE: MAY LEAD TO HEADACHE, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS. SOME REPORTS HAVE ASSOC IATED REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/ PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYE: MAY BE EYE IRRITANT.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH SAFE HA

NDLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH W/ SOAP & WATER. REMOVE CONTAMINATED CLOTHING IMMEDIATELY. EYES: FLUSH WITH WATER FOR 15 MINUTES, LIFTING LIDS TO RINSE ENTIRE EYE. CALL DR IMMED. INGEST: DO NOT INDUCE VOMITING. K EEP PERSON WARM & QUIET. SEE DR AT ONCE. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: REMOVE TO FRESH AIR. IF RESPIRATOR

Y SYMPTOMS DEVELOP, SEEK DR AT ONCE.

===== Fire Fighting Measures =====

Flash Point:50.0F,10.0C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,CO2,DRY CHEM,WATER FOG. USE THE ABOVE OR ANY CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE AS EXTINGUISHING MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL.

Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPO TO VAP/PROD OF COMBUST SHOULD WEAR SELF-CONTAINED BREATHING APPARATU S.EVACUATE

AREA OF UPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE IN AIR & MAY BE IGNITED BY SPARKS/PILOT LIGHT/ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SORUCES OF IGNITION. VENTILATE AREA. ABSORB AREA W/ ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE, OR SAND AND PLACE MATERIAL INTO A CLOSED CONTAINER. IF

LARGE SPILL, DIKE AREA TO PREVENT MATERIAL FROM ENTERING WATER SYSTEMS OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING VAPOR/SPRAY MIST. KEEP AWAY FROM HEAT & OPEN FLAME. MATERIAL MAY CAUSE SENSITIZATION. AVOID CONTACT W/ SKIN, EYES, & CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DO NO T WELD ON FULL OR EMPTY CO NTNRS.

KEEP CONTNRS CLOSED WHEN NOT IN USE & PROPERLY LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANNISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPORS OR SPRAY MIST WHEN TLV/PEL IS EXCEEDED.

Ventilation:GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE LEVELS BELOW LIMITS LISTED.

Protective Gloves:NITRILE, NEOPRENE, OR RUB

BER.
Eye Protection:FACE SHIELD OR CHEMICAL GOGGLES.
Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYEWASH STATION & SAFETY SHOWER SHOULD BE AVAILABLE.
Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=96.1C, 205.F
B.P. Text:205F - 389 F
Vapor Pres:38 MM HG @ 20 C
Vapor Density:>AIR
VOC Pounds/Gallon:390
Viscosity:75-80 KU
Evaporation Rate
& Reference:SLOWER THAN ETHER
Solubility in Water:NIL
Appearance and Odor:WHITE MEDIUM VISCOUS LIQUID WITH A MILD SWEET AROMATIC ODOR.
Percent Volatiles by Volume:51

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDENTS, ACIDS, BASES, AND EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.
Stability Condition to Avoid:HEAT SPARKS AND OPEN FLAME. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.
Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods:IF DISCARDED, MATERIAL & CONTAINER SHOULD BE TREATED AS HAZ WASTE BASED ON CHARACTERISTICS OF IGNITABILITY PER RCRA (40 CFR 261). DISPOSAL OF MATERIAL/CONTAINERS REQUIRES COMPLIANCE W/ APPLICABLE LABELING, PACKAGING, & RECORD KEEPING STANDARDS

RDS. DIPOSE IN ACCORDANCE W/ LOCAL/STATE/FED AGENCIES. GROUND HANDLING EQUIPMENT TO PREVENT SPARKS.

=====
===== Regulatory Information =====

SARA Title III Information: THIS MATERIAL HAS BEEN CATEGORIZED AS HAVING THE FOLLOWING HAZARDS AS DEFINED BY SARA TITLE III REGULATIONS (40 CFR 370): ACUTE, FIRE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense

e. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.