

DURANT PAINTS INC -- IVORY #23717 1 GAL CAN -- 8010-01-441-5922

=====
Product Identification
=====

Product ID:IVORY #23717 1 GAL CAN

MSDS Date:03/01/1998

FSC:8010

NIIN:01-441-5922

Status Code:A

MSDS Number: CJGCV

=== Responsible Party ===

Company Name:DURANT PAINTS INC

Address:112 RAILROAD ST

City:REVERE

State:MA

ZIP:02151-4007

Country:US

Emergency Phone Num:781-289-8415

CAGE:3F338

=== Contractor

Identification ===

Company Name:DURANT PAINTS INC

Address:112 RAILROAD ST

Box:City:REVERE

State:MA

ZIP:02151-4007

Country:US

Phone:781-289-8415

CAGE:3F338

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE=.50) (LEL=1.0)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 14.40%

ACGIH TLV:100 PPM

ACGIH STEL:100 PPM

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:EYES/SKIN: LIQUID

IS SLIGHTLY

IRRITATING. HIGH VAPOR CONCENTRATION MAY CAUSE IRRITATION. PROLONGED/REPEATED SKIN CONTACT CAN CAUSE DEFATTING/DRYING OF SKIN WHICH MAY RESULT IN SKIN IRRITATION/DERMATITIS. INHAL: VAPORS MAY IRRITATE NOSE/THROAT/RESPIRATORY TRACT. HIGH VAPOR CONCENTRATIONS MAY CAUSE CNS DEPRESSION.

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE, SKIN, AND RESPIRATORY DISORDERS MAY BE AGGRIVATED BY EXPOSURE TO PRODUCT.

=====
===== First Aid Measures =====
=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES, LIFTING LIDS TO RINSE ENTIRE EYE. CALL DR IMMED. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH W/COPIOUS AMOUNTS OF WATER, FOLLOWED BY SOAP & WATER. CALL DR. DO NOT REUSE CLOTHING UNTIL CLEANED. INHALATION: REMOVE TO FRESH AIR. APPLY CPR/OXYGEN IF NECESSARY. GET MED ATTN. INGESTION: DON'T INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW HIP LEVEL TO PREVENT ASPIRATION OF LIQUID INTO LUNGS. CALL DR. *SE

E

NOTES TO PHYSICIAN UNDER "OTHER INFORMATION" SECTION ON THIS MSDS.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TCC

Flash Point:=-51.7C, 125.F

Lower Limits:1.0

Upper Limits:6

Extinguishing Media:CO2

Fire Fighting Procedures:CAUTION: COMBUSTABLE! DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR INCLUDING NIOSH APPROVED SCBA. COOL FIRE EXPOSED CONTAINERS W/H2O.

Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO INTENSE HEAT SHOULD

BE COOLED W/H2O TO PREVENT VAPOR PRESSURE BUILD UP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME SHOULD BE COOLED W/ LG QUANTITIES H2O TO PREVENT WEAKING OF CONTAINER STRUCTURE.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:CAUTION: COMBUSTABLE! LG SPILL: ELIMINATE IGNITION SOURCES. WEAR APPROPRIATE RESPIRATOR/OTHER PROTECTIVE CLOTHING. SHUT OFF LEAK ONLY IF SAFE TO DO. DIKE & CONTAIN. R

EMOVE

W/VACCUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE W/ABSORBENT SUCH AS CLAY, SAND, OR OTHER SUITABLE MATERIAL. PLACE IN NONLEAKING CONTAINERS & TIGHTLY SEAL FOR PROPER DISPOSAL.**CONTINUED "OTHER PRECAUTIONS"

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY AREA AWAY FROM HEAT/SPARKS/ FLAME. CONTAINERS, EVEN EMPTY, CAN CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND, WELD, OR PERFORM SIMILAR OPERATIONS ON/NEAR CONTRS. STATIC ELECTRIC ITY MAY ACCUMULATE & CREATE FIRE HAZARD. GROUND FIXED EQUIP. BOND & GROUND TRANSFER CONTRS/EQUIP.

Other Precautions:**CONTINUED SPILL RELEASE:FLUSH SPILL AREA W/WATER TO REMOVE TRACE RESIDUE. DISPOSE OF FLUSH SOLUTION AS ABOVE. SMALL SPILLS: TAKE UP W/ABSORBENT MATERIAL IN CONTAINERS AS ABOVE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID PROLONGED/REPEATED BREA THING OF VAPORS. IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, USE NIOSH APPORVED RESPIRATOR TO PREVENT OVEREXPOSURE IN ACCORD W/29 CFR 1910.134. USE EITHER ATMOSPHERE SUPPLYING RESPIRATOR OR AIR PURIFYING RESPIRATOR.

Ventilation:PROVIDE SUFFICIENT MECHANICAL VENT. TO MAINTAIN BELOW TLV (8).

Protective Gloves:AVOID CONTACT W/SKIN. CHEMICAL RESISTANT GLOVES

Eye Protection:AVOID CONTACT W/EYES. SAFETY GLASSES/GOGGLES.

Other Protective Equipment:WEAR CHEMICAL PRO TECTIVE CLOTHING.

Work Hygienic Practices:WASH W/ SOAP & WATER BEFORE EATING, DIRINKING, SMOKING, APPLYING COSMETICS, OR USING TOILET FACILITIES. LAUNDER CONTAM CLOTHING BEFORE REUSE. AIR DRY CONTAM CLOTHES IN WELL VENTILTD AREA BEFORE WASHING

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:355 - 395 F

Vapor Density:>AIR

VOC Grams/Liter:1.96

Evaporation Rate & Reference:SLOWER THAN AIR

Appearance and Odor

:LIQUID

Percent Volatiles by Volume:30.9

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HEAT, FLAME, CONTACT W/ STRONG
OXIDIZING AGENTS.

Hazardous Decomposition Products:CO, AND UNIDENTIFIED ORGANIC COMPOUNDS
MAY BE FORMED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:UNDER EPA - RCRA (40CFR261.21).

IF THIS PRODUCT

BECOMES WASTE MATERIAL, IT WOULD BE IGNITIBLE HAZ WASTE (D001).

REFER TO LATEST EPA OR STATE REGULATIONS REGARDING PROPER DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.