

KRYLON HARDWARE -- 1311 MATTE FINISH, K01311 -- 8010-00-280-1257

=====  
Product Identification  
=====

Product ID:1311 MATTE FINISH, K01311

MSDS Date:06/16/1998

FSC:8010

NIIN:00-280-1257

Status Code:A

MSDS Number: CJHTY

=== Responsible Party ===

Company Name:KRYLON HARDWARE

Address:31500 SOLON ROAD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Phone Num:800-832-2541

Emergency Phone Num:216-566-2917

CAGE:09800

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPANE; VP: 760.00

CAS:74-98-6

RTECS #:TX2275000

= Wt:15.

OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:BUTANE; VP: 760.00

CAS:106-97-8

RTECS #:EJ4200000

= Wt:15.

OSHA PEL:800 PPM

ACGIH TLV:19

00 MG/M3;800 PPM

Ingred Name:TOLUENE; VP: 22.00

CAS:108-88-3

RTECS #:XS5250000

= Wt:50.

OSHA PEL:see Table Z-2

ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE; VP: 180.00

CAS:67-64-1

RTECS #:AL3150000

= Wt:13.

OSHA PEL:2400 MG/M3;1000 PPM

ACGIH TLV:1780 MG/M3;750 PPM

ACGIH STEL:2380 MG/M3;1000 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES In  
gestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR  
SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. TO MINIMIZE  
EXPOSURE, FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND  
PERSONAL PROTECTIVE EQUIPMENT. ACUTE: IRRITATION OF EYES, SKIN AND  
RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME  
OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH.  
SIGNS AND SYMP

TOMS OF OVEREXPOSURE: HEADACHE, DIZZINESS, NAUSEA,  
AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO  
VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY  
INDICATE EYE OR EXCESSIVE SKIN EXPOSURE. (EFFECTS OF OVEREXPOSURE)

Effects of Overexposure:HEALTH HAZARD: CHRONIC: TOLUENE APPEARS ON THE  
NAVYLIST OF OCCUPATIONAL CHEMICAL REPRODUCTIVE HAZARDS. SEEK CONSULTATION  
FROM APPROPRIATE HEALTH PROFESSIONALS CONCERNING LATEST HAZARD LIST  
INFO & SAFE HANDLING & EXPOSURE

SURE INFO . PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS IN SECTION 2 MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY, CARDIOVASCULAR AND REPRODUCTIVE SYSTEMS. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE

BREATHING. KEEP WARM AND QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE. EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE CONSCIOUS PA TIENT SEVERAL GLASSES OF WATER. SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

F  
lash Point: