

CLAIR MFG CO -- 015 HEALTH CARE DISINFECTANT 15.5 OZ -- 6840-01-375-3795

=====
Product Identification
=====

Product ID:015 HEALTH CARE DISINFECTANT 15.5 OZ

MSDS Date:03/16/1999

FSC:6840

NIIN:01-375-3795

Status Code:A

MSDS Number: CJJCK

=== Responsible Party ===

Company Name:CLAIR MFG CO

Address:500 VISTA

City:ADDISON

State:IL

ZIP:60101

Country:US

Info Phone Num:630-543-7600

Emergency Phone Num:1-

800-228-5635

Preparer's Name:AMANDA ZPOUT

CAGE:31834

=== Contractor Identification ===

Company Name:CLAIR MFG CO

Address:500 VISTA

Box:City:ADDISON

State:IL

ZIP:60101

Country:US

Phone:630-543-7600

CAGE:31834

Company Name:GABIEL SERVICE & SUPPLY CORP

Contract Num:SP0450-99-M-NA44

CAGE:5X681

=====
Composition/Information on Ingredients
=====

Ingred Name:ORTHO PHENYL PHENOL

CAS:90-43-7

RTECS #:DV5775000

Minimum % Wt:.1

Maximum % Wt:.5

Ingred Name:PARA TERTIARY AMYLPHENOL

CAS:80

-46-6
RTECS #:SM6825000
Minumum % Wt:0.
Maxumum % Wt:.1

Ingred Name:SDA DENATURED ALCOHOL (MIXTURE WATER, ETHYL ALCOHOL CAS#
64-17-5, METHYL ALCOHOL CAS# 67-56-1)
Minumum % Wt:40.
Maxumum % Wt:55.

Ingred Name:SODIUM NITRITE
CAS:7632-00-0
RTECS #:RA1225000
Minumum % Wt:.1
Maxumum % Wt:.5
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:AMMONIUM HYDROXIDE
CAS:1336-21-6
RTECS #:BQ9625000
Minumum % Wt:0.
Maxumum % Wt:.5
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LIQUEFIED PETRO
LEUM GAS
CAS:68476-85-7
RTECS #:SE7545000
Minumum % Wt:25.
Maxumum % Wt:30.
OSHA PEL:1800 MG/M3;1000 PPM
ACGIH TLV:1800 MG/M3;1000 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:RESPIRATORY IRRITATION. HIGH
CONCENTRATIONS MAY LEAD TO DRYING, IRRITATION AND DERMATITIS.
PO

SSIBLE SKIN ABSORPTION. EYE CONTACT MAY CAUSE BURNING AND IRRITATION.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:RESPIRATORY IRRITATION. HIGH CONCENTRATIONS MAY LEAD TO DRYING, IRRITATION AND DERMATITIS. POSSIBLE SKIN ABSORPTION. EYE CONTACT MAY CAUSE BURNING AND IRRITATION.

Medical Cond Aggravated by Exposure:PREEXISTING SKIN OR EYE DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING LIDS OPEN. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN-REMOVE CONTAMINATED CLOTHES. FLUSH WITH WATER FOLLOWED BY WASHING WITH SOAP & WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. DO NOT REUSE CLOTHES UNTIL CLEANED. INHALATION-REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GET MEDICAL ATTENTION. INGESTED-GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Lower Limits:1.8

Upper Limits:9.2

Extinguishing Media:CARBON DIOXIDE, FOAM AND OR DRY CHEMICAL MAY BE USED.

Fire Fighting Procedures:CONTAINERS SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESURE BUILD UP. USE EQUIPMENT OR SHIELDING AS REQUIRED TO PROTECT PERSONNEL FROM BURSTING, RUPTURING OR VENTING CONTAINERS.

Unusual Fire/Explosion Hazard:AT ELEVATED TEMPERATURES (OVER 54C-130F)

CONTAINERS MAY VENT OR BURST.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCE OF IGNITION. VENTILATE AREA. SOAK UP WITH ABSORBENT AND PLACE IN A DESIGNATED DISPOSAL CONTAINER. CONSULT LOCAL REGULATORY AGENCY FOR PROPER DISPOSITION OF MATERIAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID BRETHING VAPOR.

KEEP AWAY FROM

HEAT AND FLAME. USE WITH ADEQUATE VENTILATION. DO NOT PUNCTURE OR INCINERATE CONTAINERS. DO NOT EXPOSE TO DIRECT SUNLIGHT OR STORE AT TEMPERATURES ABOVE 130F (54C) . STORE AS LEVEL 2 AEROSOL (NFPA 306).

Other Precautions:READ AND FOLLOW DIRECTIONS ON THE PRODUCT LABEL.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED . IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS(SEC .11), USE A

NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSUREI

Ventilation:LOCAL EXHUST IS ADAQUATE UNDER NORMAL CONDITIONS, MECHANICAL VENTILATION IS OPTIONAL.

Protective Gloves:OPTIONAL CHEMICAL RESISTENT GLOVES.

Eye Protection:CHEMICAL SAFETY GLASSES ARE RECOMMENDED.

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING TO PREVENT SKIN CONTACT. PROTECTIVE CLOTHING AND EQUIPMENT SHOULD BE IN ACCORDANCE WITH 29 CFR 1910.132 AND CFR 1910.133.

Work Hygienic Practices:ENSURE STRICT S ANITARY CONDITIONS ARE CONFORMED TO WHEN WORKING AROUND CHEMICALS.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

=====
===== Physical/Chemical Properties =====

HCC:V3

Vapor Pres:125@130F

Vapor Density:>1(AIR=1)

Spec Gravity: