View NSN Online: https://aerobasegroup.com/nsn/9150-00-857-9079 FISKE BROS REFINING CO -- LUBRIPLATE NO.130-A, NO. 130-AA \_\_\_\_\_\_ MSDS Safety Information \_\_\_\_\_ FSC: 9150 NIIN: 00-857-9079 MSDS Date: 01/01/1999 MSDS Num: CJJFR Product ID: LUBRIPLATE NO.130-A, NO. 130-AA Responsible Party Cage: 73219 Name: FISKE BROS REFINING CO Address: 129 LOCKWOOD ST City: NEWARK NJ 07105-4720 Info Phone Number: 201-589-9150 Emergency Phone Number: 800-255-3924 \_\_\_\_\_\_ Item Description Information \_\_\_\_\_ Item Manager: S9G Item Name: GREASE, GENERAL PURPOSE Unit of Issue: CN Quantitative Expression: 0000000014OZ UI Container Qty: 1 \_\_\_\_\_ Ingredients \_\_\_\_\_\_ Name: \*\*\* PROPRIETARY \* \_\_\_\_\_\_

Health Hazards Data

\_\_\_\_\_

LD50 LC50 Mixture: TLV FOR OIL MIST IN AIR: 5 MG/M3

Route Of Entry Inds - Inhalation: NO

Skin: NO Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN

IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN

HEALTH RISKS VARY FROM PER

SON TO PERSON. AS A PRECAUTION, EXPOSURE TO

LIQUIDS, VAPORS MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Explanation Of Carcinogenicity: NONE SPECIFIED BY MANUFACTURER

Signs And Symptions Of Overexposure: SKIN-IRRITATION. ASPIRATION-MILD TO SEVER PULMONARY INJURY.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER

First Aid: EYE CONTA

CT: FLUSH WITH WATER FOR 15 MINUTES OR UNTIL IRRITATION

SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN. SKIN CONTACT: REMOVE ANY CONTAMINATED CLOTHING & WASH WITH SOAP & WARM WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF ITS APPEARANCE OR SIZE, COTACT A PHYSICIAN IMMEDIATELY! DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALED: VAPOR PRESSURE IS VERY LOW & DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT

, IMMEDIATELY REMOVE FROM

EXPOSURE & APHYSICIAN. INGESTED: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT IND UCE VOMITING!

\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_

Spill Release Procedures: SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD SOLVENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEW ERS

AND WATER COURSES.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER

Waste Disposal Methods: ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT AN APPROVED WASTE DISPOSAL FACILITY OR SITE.

Handling And Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions: REMOVE OIL-SOAKED CLOTHING AND LAUNDER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====

Fire and Explosion Hazard Information

\_\_\_\_\_\_

Flash Point Method: COC Flash Point: =204.4C, 400.F

Lower Limits: 0.9 Upper Limits: 7.0

Extinguishing Media: FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG). Fire Fighting Procedures: COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED

BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard: DO NOT STORE OR MIX WITH

STRONG OXIDANTS. EMPTY

CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THE MAY EXPLODE.

\_\_\_\_\_\_

**Control Measures** 

\_\_\_\_\_\_

Respiratory Protection: NORMALLY NOT NEEDED.

Ventilation: LOCAL EXHAUST, MECHANICAL(GENERAL) USED TO CAPTURE FUMES AND

VAPORS.

Protective Gloves: USE OIL-RESISTANT, IF NEEDED.

Eye Protection: GOGGLES.

Other Protective Equipment: USE OIL-RESISTANT APRON, IF N

EEDED.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER

Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER

\_\_\_\_\_\_

Physical/Chemical Properties

\_\_\_\_\_\_

HCC: V6

Boiling Point: >287.8C, 550.F M.P/F.P Text: SEMI-SOLID

Vapor Pres: <0.01 Vapor Density: >5 Spec Gravity: 0.94-0.96

Solubility in Water: NEGLIGIBLE

Appearance and Odor: SMOOTH, OFF-WHITE GREASE WITH MINERAL OIL ODOR

\_\_\_\_\_\_

Reactivity Data

\_\_\_\_\_

Stability Indicator: YES

Stability Condition To Avoid: N/A.

Materials To Avoid: AVOID CONTACT WITH STRONG OXIDANTS LIKE LIQUID CHLORINE,

CONCENTRATED OXYGEN.

Hazardous Decomposition Products: MAY FORM SULFUR DIOXIDE (SO2). IF INCOMPLETE

COMBUSTION, CARBON MONOXIDE. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: N/A.

\_\_\_\_\_

Toxicological Information

\_\_\_\_\_

Toxicological Information: NONE SPECIFIED BY MANUFACTURER

\_\_\_\_\_

**Ecological Information** 

\_\_\_\_\_

Ecological: NONE SPECIFIED BY MANUFACTURER

\_\_\_\_\_

MSDS Transport Information

\_\_\_\_\_

Tra

nsport Information: NONE SPECIFIED BY MANUFACTURER \_\_\_\_\_ Regulatory Information \_\_\_\_\_ Sara Title III Information: SARA TITLE III, SECTION 313 STATUS: ZINC COMPOUNDS Federal Regulatory Information: NONE SPECIFIED BY MANUFACTURER State Regulatory Information: NONE SPECIFIED BY MANUFACTURER Other Information \_\_\_\_\_ \_\_\_\_\_ Other Information: NONE SPECIFIED BY MANUFACTURER \_\_\_\_\_ Transportation Information Responsible Party Cage: 73219 Trans ID NO: 146487 Product ID: LUBRIPLATE NO.130-A, NO. 130-AA MSDS Prepared Date: 01/01/1999 Review Date: 07/22/1999 MFN: 1 Net Unit Weight: 0.88 LB Multiple KIT Number: 0 Unit Of Issue: CN Container QTY: 1 \_\_\_\_\_ ========== **Detail DOT Information** \_\_\_\_\_ DOT PSN Code: ZZZ DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_

**Detail IMO Information** 

\_\_\_\_\_

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

\_\_\_\_\_\_

**Detail IATA Information** 

=======

\_\_\_\_\_

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_\_

Detail AFI Information

\_\_\_\_\_

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_\_

**HAZCOM Label** 

\_\_\_\_\_\_

Product ID

: LUBRIPLATE NO.130-A, NO. 130-AA

Cage: 73219

Company Name: FISKE BROS REFINING CO

Street: 129 LOCKWOOD ST

City: NEWARK NJ Zipcode: 07105-4720

Health Emergency Phone: 800-255-3924

Label Required IND: Y

Date Of Label Review: 07/22/1999

Status Code: A
Year Procured: 1999
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION

Respiratory Protection IND: NO

Health Hazard: Slight Contact Hazard: Slight Fire Hazard: Slight Reactivity Hazard: None Hazard And Precautio

ns: TARGET ORGANS: SKIN. PROLONGED OR REPEATED SKIN CONTACT
MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE
IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION,
EXPOSURE TO LIQUIDS, VAPORS MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT
HAS A LOW ORDER OF TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS
DURING INGESTION MAY CAUSE MILD TO SEVERE PULMON ARY INJURY.

\_\_\_\_\_\_

Disclaimer (prov

ided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability fo

r such use. Any person

utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.