

READ RIGHT DIVISION OF ACCTECH LLC -- PC DUSTER 2(3507/8/9/10/22/3607/8/9) --
6830-01-434-1191

===== Product Identification =====

Product ID:PC DUSTER 2(3507/8/9/10/22/3607/8/9)
MSDS Date:03/01/1998
FSC:6830
NIIN:01-434-1191
Status Code:A
MSDS Number: CJJRP
=== Responsible Party ===
Company Name:READ RIGHT DIVISION OF ACCTECH LLC
Address:33 MURRY HILL DRIVE
City:NANUET
State:NY
ZIP:10954
Countr
y:US
Info Phone Num:800-327-1237
Emergency Phone Num:800-327-1237
Chemtrec Ind/Phone:(800)424-9300
CAGE:09ZF6

=== Contractor Identification ===

Company Name:ACCTECH LLC
Address:33 MURRY HILL DRIVE
Box:City:NANUET
State:NY
ZIP:10954
Country:US
Phone:800-284-5577
CAGE:09ZF6
Company Name:DEFENSE SUPPLY CENTER RICHMOND, ATTN: DSCR-VBA
Address:8000 JEFFERSON DAVIS HIGHWAY
Box:City:RICHMOND
State:VA
ZIP:23297-5607
Country:US
Phone:804-279-4371, DSN 695-4371
CAGE:SO004

===== Composition/Info

Information on Ingredients =====

Ingredient Name:1,1,1,2-TETRAFLUOROETHANE

CAS:811-97-2

= Wt:100.

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: EXCESSIVE INHALATION OF VAPORS MAY BE FATAL. VAPORS REDUCE AVAILABLE OXYGEN IN AIR. REDUCED OXYGEN LEVELS TO 12-14% PRODUCE SYMPTOMS OF ASPHYXIATION. MATERIAL CAN INDUCE CARDIAC SENSITIZATION TO EPINEPHRINE AND CARDIAC

ARRHYTHMIA. SKIN: DIRECT EXPOSURE OF SKIN TO LIQUID MAY CAUSE FROSTBITE. EYES: IRRITANT.

Explanation of Carcinogenicity:NOT LISTED.

Effects of Overexposure:INHALATION: REDUCED OXYGEN LEVELS TO 12-14% PRODUCE DROWSINESS, LOSS OF COORDINATION, INCREASED PULSE RATE, NARCOSIS, CARDIAC SENSITIZATION AND DEEPER RESPIRATION.

Medical Conditions Aggravated by Exposure:ANEMIA, ASTHMA, DERMAL SENSITIVITY AND LOW BLOOD PRESSURE.

===== First Aid Measures =====

=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MIN., INCLUDING UNDER EYELIDS. GET MEDICAL ATTENTION. SKIN: FLUSH WITH WATER. TREAT FOR FROSTBITE IF NECESSARY BY BATHING AREA WITH LUKEWARM WATER. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. KEEP AT REST. RESTORE AND/OR SUPPORT BREATHING AS NEEDED. GET PROMPT MEDICAL ATTENTION. INGESTION: NOT A POTENTIAL ROUTE OF EXPOSURE.

===== Fire Fighting Measures =====

Flash Point Method:

TCC

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM. WATER MAY BE USED TO COOL CONTAINERS EXPOSED TO THE FIRE TO REDUCE PRESSURE BUILDUP.

Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS EXPOSED TO THE FIRE TO REDUCE PRESSURE BUILDUP.

Unusual Fire/Explosion Hazard:CYLINDERS ARE UNDER PRESSURE AND MAY RUPTURE UNDER FIRE CONDITIONS. DECOMPOSITION MAY PRODUCE HYDROCHLORIC AND HYDROFLUORIC ACID. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURNS

TING.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA, ESPECIALLY LOW PLACES WHERE HEAVY VAPORS MAY COLLECT. REMOVE OPEN FLAMES. ISOLATE HAZARD UNTIL ALL GAS HAS DISPERSED. WATER SPRAY MAY BE USED TO REDUCE VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN, COOL, VENTILATED AREA AWAY FROM SOURCES OF IGNITION & OXIDIZING AGENTS. MAINTAIN TEMP AT LESS THAN 120F. STORE AS A LEVEL 1 AEROSOL (NFPA 30B). OVER HEATING, PRESSURIZING, OR RUSTING CAN CAUSE CAN TO BURST RESULTING IN SERIOUS PERSONAL INJURY. EMPTY CONTAINERS RETAIN RESIDUE.
Other Precautions:FOLLOW ALL LABEL WARNINGS. DISPOSE OF EMPTY CONTAINER ACCORDING TO REGULATIONS. DO NOT REUSE THE CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNDER NORMAL USE, NO RESPIRATORY PROTECTION IS REQUIRED. SELF-CONTAINED BREATHING APPARATUS IS REQUIRED IF A LARGE RELEASE OCCURS.
Ventilation:NORMAL VENTILATION FOR STANDARD PROCEDURES IS GENERALLY ADEQUATE. LOCAL EXHAUST SHOULD BE USED WHEN LARGE AMOUNTS ARE RELEASED. SEE OTHER
Protective Gloves:LINED NITRILE OR NATURAL RUBBER GLOVES
Eye Protection:CHEMICAL SPLASH GOGGLES
Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID INHALATION OF VAPORS AND REPEATED OR PROLONGED CONTACT OF LIQUID WITH SKIN OR CLOTHING
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:G3
Boiling Pt:=-26.C, -14.8F
Vapor Pres:70 PSIG @ 70F
Vapor Density:4.34
Spec Gravity:1.21
Evaporation Rate & Reference:LIQUIFIED GAS
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR, LIQUIFIED GAS; ETHEREAL ODOR
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, CHLORINE,AND CHEMICALLY ACTIVE MET

ALS;I.E.

ALKALI OR ALKALINE EARTH METALS-POWDERED AL,ZN,ETC

Stability Condition to Avoid:OPEN FLAMES OR HIGH TEMPERATURES.

Hazardous Decomposition Products:CAN BE DECOMPOSED BY HIGH TEMPERATURES(OPEN FLAME,GLOWING METAL SURFACE,ETC)FORMING HYDROFLUORIC ACID,AND POSSIBLY CARBONYL HALIDES.

===== Toxicological Information =====

Toxicological Information:NOT AVAILABLE.

===== Ecological Information =====

Ecological:NOT AVAILABLE.

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW FEDERAL, STATE, AND LOCAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:DOT: CONSUMER COMMODITY. IATA/ICAP: CONSUMER COMMODITY. IMDG: 1,1,1,2-TETRAFLUOROETHANE, UN3159, CLASS 2.2, NONFLAMMABLE GAS.

===== Regulatory Information =====

SARA Title III Information:TOXIC CHEMICAL (SECTION 313)
: NOT LISTED.

EXTREMELY HAZARDOUS SUBSTANCE (SECTION 302, 304, 311, 312): NOT LISTED.

Federal Regulatory Information:TSCA INVENTORY STATUS: LISTED IN THE TSCA INVENTORY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.