

HACH CO -- SILICA 1 REAGENT -- 6810-01-461-3318

=====
Product Identification
=====

Product ID:SILICA 1 REAGENT
MSDS Date:04/29/1996
FSC:6810
NIIN:01-461-3318
Status Code:A
MSDS Number: CJKXN
==== Responsible Party ====
Company Name:HACH CO
Box:389
City:LOVELAND
State:CO
ZIP:80539-0389
Country:US
Info Phone Num:970-669-3050
Emergency Phone Num:303-623-5716
CAGE:91224

==== Contractor Identification ==
=

Company Name:HACH CO
Address:5600 LINDBERGH DR
Box:389
City:LOVELAND
State:CO
ZIP:80539
Country:US
Phone:970-669-3050/ 303-623-5716
Contract Num:SP0450-99-M-NA98
CAGE:91224

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLYBDIC ACID
CAS:7782-91-4
Minumum % Wt:5.
Maxumum % Wt:10.
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:SODIUM BISULFATE
CAS:7681-38-1
RTECS #:VZ1860000
Minumum % Wt:5.
Maxumum % Wt:10.

Ingred Name:SULFURIC ACID
CAS:7664-93-9
RTECS #:

WS5600000
Minumum % Wt:5.
Maxumum % Wt:10.
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3
ACGIH STEL:3 MG/M3
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:DEMINERALIZED WATER
CAS:7732-18-5
Code:F
RTECS #:ZC0110000

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EYES: CAUSES EYE BURNS. SKIN: CAUSES
BURNS. SKIN ABSORPTION: NONE REPORTED.
INGESTION: CAUSES: BURNS.
MAY CAUSE: NAUEA, VOMITING, DIARRHEA, RAPID PULSE & RESPIRATIONS,
LOSS OF APPETITE, CIRCULATORY D ISTURBANCES, ANEMIA, LIVER DAMAGE.
INGESTION OF MOLYBDENUM MAY CAUSE LOSS OF COORDINATION, ENZYME
ACTIVITY EFFECTS, COPPER DEFICIENCY, GOUT. INHALATION: CAN CAUSE
BURNS. MAY CAUSE LIVER DAMAGE, DIFFIC ULT BREATHING, TOOTH EROSION,
MOUTH SORENESS.

Explanation of Carcinogenicity:AN INGREDIENT OF THIS MIXTURE IS IARC
GROUP 1: RECOGNIZED CARCINOGEN.
SULFURIC ACID-IARC EVALUATION WAS
BASED ON EXPOSURE TO THE MIST OR VAPOR OF CONCENTRATED SULFURIC
ACID GENERATED DURING CHEMICAL P ROCESSSES. THE PRODUCT DOES NOT
CONTAIN ANY NTP LISTED CHEMICALS. ADDITIONAL
CANCER/REPRODUCTIVE/TOXICITY DATA: NONE REPORTED.

Effects of Overexposure:EYES: CAUSES EYE BURNS. SKIN: CAUSES BURNS.
INGESTION: CAUSES: BURNS. MAY CAUSE: NAUEA, VOMITING, DIARRHEA,
RAPID PULSE & RESPIRATIONS, LOSS OF APPETITE, CIRCULATORY
DISTURBANCES, ANEMIA,
LIVER DAMA GE. INGESTION OF MOLYBDENUM MAY
CAUSE LOSS OF COORDINATION, ENZYME ACTIVITY EFFECTS, COPPER
DEFICIENCY, GOUT. INHALATION: CAN CAUSE BURNS. MAY CAUSE LIVER
DAMAGE, DIFFICULT BREATHING, TOOTH EROSION, M OUTH SORENESS.

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE CONDITIONS, SKIN
CONDITIONS, RESPIRATORY CONDITIONS, GOUT.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH EYES WITH WATER FOR 15
MINUTE

S. CALL PHYSICIAN. SKIN CONTACT: WASH SKIN WITH PLENTY OF WATER FOR 15 MINUTES. CALL PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE 1-2 GLASSES OF WATER. CALL PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:WILL NOT BURN.

Extinguishing Media:USE MEDIA APPROPRIATE TO SURROUNDING FIRE CONDITIONS.

Fire Fi

ghting Procedures:AS IN ANY FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS PRESSURE-DEMAND AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:NONE REPORTED. FLAMMABLE PROPERTIES: MATERIAL WILL NOT BURN. DURING A FIRE, CORROSIVE & TOXIC GASSES MAY BE GENERATED BY THERMAL DECOMPOSITION.

===== Accidental Release Measures =====

Spill Release Procedures:ONLY PERSONS QUALIFIED TO RESPOND TO AN EMERGENCY INVOLVING HAZARDOUS SUBSTANCES MAY RESPOND TO A SPILL IAW

29 CFR 1010.1200(A)(V). ABSORB SPILLED LIQUID WITH NON-REACTIVE SORBENT MATERIAL. STOP SPILLED MATERIAL FROM BEING RELEASED TO THE ENVIRONMENT. COVER WITH ALKALI. SCOOP INTO A BEAKER & DISSOLVE IN WATER. ADJUST PH TO 6-9 WITH ALKALI. FLUSH REACTED MATERIAL TO DRAIN IN EXCESS WATER.

Neutralizing Agent:SODA ASH, SODIUM BICARBONATE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BETWEEN 10C & 25C. KEEP AWAY

FROM OXIDIZERS, REDUCERS. AVOID CONTACT WITH EYES, SKIN CLOTHING. DO NOT BREATHE MIST OR VAPORS. WASH THOROUGHLY AFTER HANDLING. USE WITH ADEQUATE VENTILATION. MAINTAIN IN GENERAL INDUSTRIAL PRACTICES WHEN USING THIS PRODUCT. FLAMMABILITY CLASS: NOT APPLICABLE.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ADEQUATE VENTILATION.

Ventilation:USE GENERAL VENTILATION TO MINIMIZE EXPOSURE TO M

IST.,
VAPOR OR DUST.

Protective Gloves:DISPOSABLE LATEX GLOVES, LAB COAT.

Eye Protection:SAFETY GLASSES WITH TOP AND SID SHIELDS

Other Protective Equipment:HAVE A SAFETY SHOWER NEARBY. HAVE AN EYE
WASH STATION NEARBY.

Work Hygienic Practices:MAINTAIN GENERAL INDUSTRIAL HYGIENE PRACTICES
WHEN USING THIS PRODUCT.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:NOT DETERMINE

D

Melt/Freeze Pt:=100.C, 212.F

Vapor Pres:NOT DETERMINED

Spec Gravity:1.14-1.21

pH: