View NSN Online: https://aerobasegroup.com/nsn/6850-00-405-9312

BLUE MAGIC, INC -- PRO-TEK INVISIBLE GLOVE, PART NOS 5213, 5214, 5215, 5216 6850-00-405-9312

============ Product Identification =========================

Product ID:PRO-TEK INVISIBLE GLOVE, PART NOS 5213, 5214, 5215, 5216

MSDS Date:11/01/1998

FSC:6850

NIIN:00-405-9312 Status Code:A

MSDS Number: CJNSM === Responsible Party ===

Company Name: BLUE MAGIC, INC

Address:23070 MILES ROAD

City:CLEVELAND

State:OH ZIP:44128 Countr

v:US

Info Phone Num:216-518-8222/800-729-1816

Emergency Phone Num:800.729.1816

**CAGE:057V8** 

=== Contractor Identification ===

Company Name: AMERICO INDUSTRIAL SUPPLY INC

Address:1070 E DOMINGUEZ ST UNIT B

Box:City:CARSON

State:CA

ZIP:90746-3619 Country:US

Phone:310-763-5500 FAX:310-763-5858

Contract Num:SP0450-99-M-C902

CAGE:0XDR8

Company Name: BLUE MAGIC, INC

Address:23070 MILES ROAD

Box:City:CLEVELAND

State:OH ZIP:44128 Country:US

Phone:216-518-8222/800-729-1816

**CAGE:057V8** 

====== Composit

| Ingred Name:ALKALINE SILICATES   |
|--|
| ======================================   |
| Health Hazards Acute and Chronic:**TARGET-ORGANS:NONE** THIS MATERIAL IS NOT A HEALTH HAZARD. PROLONGED CONTINUOUS USE BY PERSONS WITH SENSITIVE SKIN COULD CAUSE IRRITAION. CONTAINS ALKALINE SILICATE. DISCONTINUE USE IF IRRITATION D EVELOPES. MAY CAUSE IRRITATION TO EYES. AVOID PROLONGED, REPEATED CONTACT W/SKIN OR EYES. WASH TH |
| OROUGHLY WITH SOAP AND WATER AFTER USING. Effects of Overexposure:SLIGHT IRRITATION.   |
| Medical Cond Aggravated by Exposure:INDIVIDUAL WITH SENSITIVE SKIN.  |
| ======================================   |
| First Aid:INGESTION:IF CONSCIOUS, INDUCE VOMITING AFTER DRINKING TWO GLASSES OF WATER. GET MEDICAL HELP. SKIN: IF IRRITATION DEVELOPES, WASH THOROUGHLY WITH SOAP AND WATER AND DISCONTINUE USE. EYES: FUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP IF SYMPTOMS PE RSIST.  |
| ======================================   |
| Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM OR CO2. Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL. WILL NOT BURN UNLESS WATER HAS EVAPORATED.  |
| ========= Accidental Release Measures ==========   |
| Spill Release Procedures:PICK UP EXCESS WITH A RAG AND WASH RESIDUE WITH WATER.  |
| ======================================   |
| Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP CONTAINERS CLOSED. Other Precautions:KEEP AWAY FROM CHILDREN.  |
| ====== Exposure Controls/Personal Protection ========  |
| Respiratory Protection:NONE REQUIRED. Eye Protection:SAFETY GLASSES. Other Protective Equipment:SAFETY SHOES, HARD HATS AND SUITABLE CLOTHING IS STANDARD PRACTICE IN MANY INDUSTRIAL OPERATIONS. Work Hygienic Practices:WASH HANDS WITH SOAP AND WATER AFTER USING. Supplemental Safety and Health NO SPECIAL PRO                        |

ion/Information on Ingredients ========

| TECTION NECESSARY.   |
|--|
| ======================================   |
| HCC:N1 Spec Gravity:0.7 Solubility in Water:DISPERSES Appearance and Odor:WHITE PASTE, SLIGHT LEMON ODOR. Percent Volatiles by Volume:61   |
| ======== Stability and Reactivity Data =========   |
| Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:NORMALLY STABLE AS DEFINED IN NFPA 704-12 (4-3,1).   |
| ======= Disposal Considerations ==========   |
| Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.  |
| ======= MSDS Transport Information =========   |
| Transport Information:NOT REGULATED.   |
| Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and |

assume responsibility for the suitability of this information to their particular situation.