

DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV. -- HYSOL PC20M -- 5970-00-442-0272
===== Product Identification =====

Product ID:HYSOL PC20M
MSDS Date:09/03/1998
FSC:5970
NIIN:00-442-0272
Status Code:A
MSDS Number: CJQCC
=== Responsible Party ===
Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV.
Address:211 FRANKLIN ST.
City:OLEAN
State:NY
ZIP:14760-1297
Country:US
Info Phone Num:716-372-6300
Emergency Phone Num:716-372-6300
Resp. Party Other MSDS Num.:PRODUCT: P00012
Chemtrec Ind/Phone:(800)424-9300
CAGE:04347
=== Contractor Identification ===
Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV
Address:211 FRANKLIN ST.
Box:City:OLEAN
State:NY
ZIP:14760-1297
Country:US
Phone:716-372-6300/6309
CAGE:04347
Company Name:MCKEOWN ROBERT CO. INC.
Address:111 CHAMBERS BROOK RD.
Box:City:SOMERVILLE
State:NJ
ZIP:08876
Country:US
Phone:908-218-9000
Contract Num:SP0430-99-M-TB62

CAGE:7B953

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

= Wt:40.13

OSHA PEL:see Table Z-2

ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL METHACRYLATE

CAS:97-88-1

RTECS #:OZ3675000

Minumum % Wt:1.

Maxumum % Wt:5.

Ingred Name:2-BUTANONE

CAS:78-93-3

RTECS #:EL6475000

Minumum % Wt:10.

Maxumum % Wt:30.

OSHA PEL:590 MG/M3;200 PPM

ACGIH TLV:590 MG/M3;200 PPM

ACGIH STEL:885 MG/M3;300 PP

M

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS: EYES, SKIN, RESPIRATORY

TRACT. EYE CONTACT: MAY CAUSE SEVERE EYE IRRITATION. SKIN CONTACT:

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION, DEFATTING

AND DRYING OF THE SKIN. I NHALATION: HARMFUL IF INHALED,

MAY CAUSE

ALLERGIC RESPIRATORY REACTION SUCH AS ASTHMA. INGESTION: MODERATELY

TOXIC, MAY CAUSE VOMITING.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:EYES-IRRITATION. SKIN-IRRITATION, DEFATTING,

DRYING. INHALED-HARMFUL; MAY CAUSE ALLERGIC RESPIRATORY REACTION

SUCH AS ASTHMA. INGESTED-MODERATELY, MAY CAUSE VOMITING.

Medical Cond Aggravated by Exposure:PREEXISTING SKIN AND EYE DISORDERS

MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PR

E-EXISTING SKIN OR

LUNG ALLERGIES MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGIC SYMPTOMS TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYE CONTACT: IMMEDIATELY WASH/FLUSH EYES WITH WATER FOR MINIMUM 10 MINUTES. SEEK MEDICAL ATTENTION. SKIN CONTACT: WASH OFF IN FLOWING WATER OR SHOWER. REMOVE CONTAMINATED CLOTHING AND SHOES. SEEK MEDICAL ATTENTION, IF IRRITATION DEVELOPS. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SEEK MEDICAL ATTENTION. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK PROMPT MEDICAL ATTENTION. NOTE TO PHYSICIAN: TREATMENT SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS. THERE ARE NO SPECIFIC ANTIDOTES.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:11.1C, 52.F

Extinguishing Media:WATER FOG, CO

RBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:RECOMMEND USE OF SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NO UNUSUAL FIRE OR EXPLOSION HAZARDS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN-UP: CONTAIN SPILL IN NATURAL FORM OR WITH SAND OR DIRT. ELIMINATE ALL IGNITION SOURCES. PREVENT RUNOFF TO STORM SEWERS, DITCHES AND WATERWAYS. SHOVEL OR SCRAPE (NON-METALLIC) ABSORBED WASTE MATERIAL INTO DISPOSAL CONTAINER.

SEAL LID TIGHTLY WITH TAPE AND LABEL PROPERLY. CLEAN UP SPILL IMMEDIATELY. OBSERVE PRECAUTIONS INCLUDING VENTILATION AND/ OR PERSONAL PROTECTIVE EQUIPMENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT LESS THAN TWENTY FIVE DEGREE CENTIGRADE (