

PRAXAIR SURFACE TECHNOLOGIES INC -- NI-114, WELDING POWDER -- 3439-01-426-3164

===== Product Identification =====

Product ID:NI-114, WELDING POWDER

MSDS Date:06/22/1994

FSC:3439

NIIN:01-426-3164

Status Code:A

MSDS Number: CJQGW

=== Responsible Party ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Info Phone Num:317-24

0-2650

Emergency Phone Num:317-240-2209

Resp. Party Other MSDS Num.:PRODUCT CODE:036014-04

Preparer's Name:MICHELLE ALEXANDER

Chemtrec Ind/Phone:(800)424-9300

CAGE:0FGH2

=== Contractor Identification ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

Box:City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:0FGH2

Company Name:STARGHILL TECHNOLOGIES CORP

Address:3850 OAKMAN BLVD

Box:City:DETROIT

State:MI

ZIP:48204-1119

Country:US

Phone:313-933-4141

C

=====
Composition/Information on Ingredients
=====

Ingred Name:NICKEL
CAS:7440-02-0
RTECS #:QR5950000
Minimum % Wt:50.
Maximum % Wt:75.
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3

Ingred Name:CARBON
CAS:7440-44-0
RTECS #:FF5250000
Minimum % Wt:20.
Maximum % Wt:50.
OSHA PEL:10 MG/M3
ACGIH TLV:2.5 MG/M3

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: EYES: MAY CAUSE IRRITATION.

SKIN CONTACT:MAY CAUSE ALLERGIC DERMATITIS, PAPULAR FORMATION, ULCERS, DRY AND SCALY SKIN, FEVER. SKIN ABSORPTION: NO EVIDENCE OF ADVERSE EFFECTS. INHALATION: MAY CAUSE RESPIRATORY TRACT IRRITATION, WITH CHEST PAIN, VOMITING, DIARRHEA, BURNING SENSATION, AND CENTRAL NERVOUS SYSTEM DEPRESSION. MAY ALSO CAUSE INTERSTITIAL PNEUMONITIS AND SENSITIZATION OF THE RESPIRATORY TRACT.

INGESTION:

MAY CAUSE NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, CENTRAL NERVOUS SYSTEM DEPRESSION, AND BURNING SENSATION. CHRONIC: EYES: DAMAGE. SKIN: AFFECT WHOLE BODY WITH LESIONS, SORENESS, ITCHING. INHALATION: EMPHYSEMA.

Explanation of Carcinogenicity:NICKEL HAS BEEN DETERMINED TO CAUSE CANCER IN EXPERIMENTAL ANIMALS (IARC, NTP). NICKEL IS LISTED AS A PROBABLE HUMAN CARCINOGEN.

Effects of Overexposure:EYES: IRRITATION, REDNESS, EXCESS REDNESS OF CONJUGA

NCTIVA, CORNEAL DAMAGE. SKIN: DERMATITIS, REDNESS, PAPULAR FORMATION, ULCERS, DRY AND SCALY SKIN, FEVER. INHALATION: RESPIRATORY TRACT IRRITATION, CHE ST PAIN, DIARRHEA, BURNING SENSATION, CNS DEPRESSION, INTERSTITIAL PNEUMONITIS, EMPHYSEMA, SENSITIZATION OF RESPIRATORY TRACT. INGESTION: NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, CENTRAL NERVOUS SY STEM DEPRESSION, BURNING SENSATION.CHRONIC ECZEMA/NEURODERMATIS FROM NICKEL DOES REQUIRE CONTINUOUS METAL CONTACT.

Medic
al Cond Aggravated by Exposure: BREATHING OF DUST MAY AGGRAVATE ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE. MAY ALSO AGGRAVATE AN EXISTING DERMATITIS.

===== First Aid Measures =====

First Aid: EYES: FLUSH WITH PENTY OF WATER. IF DISCOMFORT PERSISTS, GET MEDICAL ATTENTION, PREFERABLY AN OPTALMOLOGIST. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. OXYGE
N MAY BE GIVEN
IF NECESSARY. CALL A PHYSICIAN. INGESTION: GIVE AT LEAST 2 GLASSES OF MILK OR WATER. INDUCE VOMITING, UNLESS PATIENT IS UNCONSCIOUS. CALL A PHYSICIA N. NOTES TO PHYSICIAN: THE HAZARDS OF THIS MATERIAL ARE MAINLY DUE TO ITS SENSITIZING AND MILD IRRITATING PROPERTIES. THERE IS NO SPECIFIC ANTIDOTE.

===== Fire Fighting Measures =====

Flash Point: NONE
Upper Limits: 0.00%
Extinguishing Media: USE DRY POWDER METAL EXTINGUISHING MATER
IAL TO
EXTINGUISH METAL FIRES. USE APPROPRIATE EXTINGUISHER TO EXTINGUISH MATERIALS THAT MAY BE IGNITED BY THE THERMAL SPRAY FLAME.
Fire Fighting Procedures: COMPLY WITH ANSI Z49.1 SAFETY IN WELDING AND CUTTING, NFPA51B STANDARD FOR FIRE PREVENTION IN USE OF CUTTING AND WELDING PROCESSES. NFPA51 OXYGEN-FUEL GAS SYSTEMS FOR WELDING AND CUTTING, AND NFPA58 S TANDARD FOR THE STORAGE AND HANDLING OF LIQUIDIFIED PETROLEUM GASES.
Unusual Fire/Explosion Hazard: AIRBORNE DUST PARTI

CLES, ESPECIALLY METAL

DUST, AND ACCUMULATION OF SUCH SHOULD BE TREATED AS EXPLOSIVES. TO MINIMIZE DANGER FROM DUST EXPLOSIONS, ADEQUATE VENTILATION SHOULD BE PROVIDED TO SPARY BOOT H IN ACCORDANCE WITH AMERICAN WELDING SOCIETY PUBLICATION AWSC2.1-73, AND ACGIH PUBLICATION "INDUSTRIAL VENTILATION".

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST HAZARDS AND DISPOSE OF PER WASTE DISPOSAL METHOD.

===== Handling and Storage =====

Handling and Storage Precautions:CAUTION: WHEN THERMAL SPRAYING; ELECTRICITY CAN CAUSE FATAL SHOCK. ARC RAYS CAN BURN EYES AND SKIN. WEAR RECOMMENDED EYE AND BODY PROTECTION. FUMES, GAS, AND DUST CAN HARM YOUR HEALTH. PROVIDE ENOUGH VENTILATION AND WEAR RESPIRATOR. Other Precautions:ALWAYS SPRAY WITH ENOUGH VENTILATION. SPARKS DURING SPRAYING CAN BE A SOURCE OF IGNITION OF COMBUSTIBLE MATERIALS. PREVENT FIRES. REFER TO NFPA 51B "CUTTING AND WELDING PROCESSES".

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DEPENDS UPON SPECIFIC USE, CONDITION, AND LOCATION. IF THERE IS DUSTINESS, WEAR RESPIRATOR SELECTED PER OSHA 1910.134, AND OSHA 29 CFR 1910.252 AND ANSI Z49.1.

Ventilation:LOCAL DUST PICK UP AND VENTILATION RECOMMENDED.

Protective Gloves:NOT REQUIRED.

Eye Protection:WHEN DUSTY USE GOGGLES PER OSHA 1910.13.

Other Protective Equi

ment:SEE ANSI Z49.1, ANSI Z87.1, ANSI Z88.2 FOR HELMETS, FACE SHIELDS AND GOGGLES.

Work Hygienic Practices:NONE PROVIDED BY MFR.

Supplemental Safety and Health

NONE PROVIDED BY MFR.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NONE

Spec Gravity:1.4 (WATER = 1)

Evaporation Rate & Reference:NON VOLATILE

Appearance and Odor:DUSTY YELLOW GRAY POWDER.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES
NONE KNOWN.

Stability Condition to Avoid: NONE KNOWN.

Hazardous Decomposition Products: WHEN THERMAL SPRAYING, DECOMPOSITION PRODUCTS VARY WITH CONDITIONS. DECOMPOSITION PRODUCTS OF NORMAL OPERATION FROM THIS SPRAY POWDER INCLUDE OXIDES, SUB-OXIDES, COMPLEX OXIDES OF THE POWDERED METALS.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: D
ISOPE OF WASTE PER LOCAL, STATE, AND FEDERAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information: NOT REGULATED. PER MSDS: SHIPPING NAME: METAL ALLOY POWDER NOI ITEM 136500 SUB 1. NO UN NUMBER.

===== Regulatory Information =====

SARA Title III Information: SECTION 313: THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND OF CFR 372: CAS # 7440-02-0 , NICKEL,