View NSN Online: https://aerobasegroup.com/nsn/3439-00-913-4750

SUPERIOR FLUX AND MFG CO -- SUPERIOR NO.625 -- 3439-00-913-4750

Product ID:SUPERIOR NO.625 MSDS Date:05/07/1999 FSC:3439 NIIN:00-913-4750 Status Code:A MSDS Number: CJVBG === Responsible Party === Company Name: SUPERIOR FLUX AND MFG CO Address:6615 PARKLAND BLVD City:CLEVELAND State:OH ZIP:44193 Country:US Info Phone Num:440-349-3000 Emergency Phone Num: (800) 424-9300 Chemtrec Ind/Phone:(800)424-9300 CAGE:87618 === Contractor Identification === Company Name: AUFHAUSER CORP Address:39 WEST MALL Box:City:PLAINVIEW State:NY ZIP:11803-4209 Country:US Phone:212-757-6824/FAX: 516-694-8690 CAGE:59401 Company Name: SUPERIOR FLUX AND MFG CO Address:6615 PARKLAND BLVD City:SOLON (FORMALLY CLEVELAND) State:OH ZIP:44139 Country:US Phone:440-349-3000 CAGE:87618

Ingred Name: POTASSIUM FLUOROHYDROBORAT

E CAS:12228-71-6 Code:F Minumum % Wt:5. Maxumum % Wt:20.

Ingred Name:POTASSIUM TETRABORATE CAS:1332-77-0 Minumum % Wt:15. Maxumum % Wt:25.

Ingred Name:BORIC ACID CAS:10043-35-3 RTECS #:ED4550000 Minumum % Wt:15. Maxumum % Wt:30.

Ingred Name:POTASSIUM FLUOROBORATE CAS:14075-53-7 RTECS #:ED2800000 Minumum % Wt:7. Maxumum % Wt:15.

Ingred Name:SODIUM ALUMINUM FLUORIDE CAS:15096-52-3 RTECS #:WA9625000 Minumum % Wt:1. Maxumum % Wt:5.

Ingred Name:LITHIUM CHLORIDE CAS:7447-41-8 RTECS #:OJ5950000 Mi numum % Wt:2. Maxumum % Wt:5.

Ingred Name:ZINC CHLORIDE CAS:7646-85-7 RTECS #:ZH1400000 Minumum % Wt:.2 Maxumum % Wt:1. OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3 ACGIH STEL:2 MG/M3 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EVOLVES FLUORIDES WHEN HEATED, MAY CAUSE BURNING OF EYES AND THROAT FOR 10 MINUTES. CALL PHYSICIAN. SKIN: WASH THOROUGHLY WITH WATER.

INGESTION: IF PATIENT IS FULLY CONSCIOUS, GIVE TWO GLASSES OF WATER AND I NDUCE VOMITING. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

Flash Point:NONE Autoignition Temp:Autoignition Temp Text:NONE Lower Limits:NA Upper Limits:NA Extinguishing Media:NOT NEEDED Fire Fighting Procedures:NORMAL CAUTION WHEN USING CHEMICALS. Unusual Fire/Explosion Hazard:FLUORIDES.

=====

Spill Release Procedures: CLEAN UP PASTE AND FLUSH REMAINING MATERIAL WITH LOTS OF WATER.

Handling and Storage Precautions:STORE IN PLASTIC CONTAINERS IN COOL AREA. DO NOT STORE IN GLASS OR PORCELAIN CONTAINER. WASH THOROUGHLY AFTER USE.

Other Precautions: KEEP CONTAINER AWAY FROM EXCESSIVE HEAT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH APPROVED RESPIRA

TOR.

Ventilation:LOCAL EXHAUST. Protective Gloves:RECOMMEND, NIOSH APPROVED Eye Protection:SAFETY GOGGLES Other Protective Equipment:RUBBER APRON. Work Hygienic Practices:AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH THROUGHLY AFTER USE. Supplemental Safety and Health

HCC:N1 Boiling Pt:B.P. Text:NA Melt/Freeze Pt:=500.C, 932.F Vapor Pres:NA Vapor Density:NA Spec Gravity:1.6 Evaporation Rate & amp; Reference:0.3 (BUTYL A CETATE=1) Solubility in Water:MODERATE Appearance and Odor:WHITE ORDORLESS PASTE Percent Volatiles by Volume:30

Stability Indicator/Materials to Avoid:YES GLASS OR PORCELAIN. Stability Condition to Avoid:EXCESS HEAT. Hazardous Decomposition Products:FLUORIDES WITH HIGH HEAT. Conditions to Avoid Polymerization:WILL NOT OCCUR. NA

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH EPA REGULATIONS.

Transport Information:NOT REGULATED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document s hould seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.