

SANDSTROM PRODUCTS COMPANY -- DRY FILM LUBRICANT,27A (MIL-L-46147B TYPE 1) --
9150-01-360-1909

===== Product Identification =====

Product ID:DRY FILM LUBRICANT,27A (MIL-L-46147B TYPE 1)

MSDS Date:04/30/1998

FSC:9150

NIIN:01-360-1909

Status Code:A

MSDS Number: CJWDJ

=== Responsible Party ===

Company Name:SANDSTROM PRODUCTS COMPANY

Address:224 SOUTH MAIN STREET

City:PORT BYRON

State:IL

ZIP:61275

Co

untry:US

Info Phone Num:309-523-2121

Emergency Phone Num:309-523-2121

Preparer's Name:NONE

Chemtrec Ind/Phone:(800)424-9300

CAGE:34227

=== Contractor Identification ===

Company Name:SANDSTROM PRODUCTS COMPANY

Address:224 SOUTH MAIN STREET

Box:City:PORT BYRON

State:IL

ZIP:61275

Country:US

Phone:309-523-2121

CAGE:34227

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE

CAS:108-65-6

RTECS #:A18295000

Other REC Limits:NONE RECO

MMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 25 PPM
ACGIH TLV:S, 25 PPM; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Minumum % Wt:45.
Maxumum % Wt:50.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000
LBS

Ingred Name:BASIC LEAD PHOSPHITE/DIBASIC LEAD PHOSPHITE
CAS:12141-20-7
Minumum % Wt:1.
Maxumum % Wt:5.
Other REC Limits:NONE RECOMMENDED

Ingred Name:ANTIMONY TRIOXIDE (SARA III)
CAS:1309-64-4
RTECS #:CC5650000
Minumum % Wt:1.
Maxumum % Wt:5.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG (SB)/M3
ACGIH TLV:0.5 MG (SB)/M3; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MOLYBDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
Other REC Limits:NONE RECOMMENDED

Ingred Name:BISPHEN

OL A EPOXY RESIN

CAS:25036-25-3

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE- EYE CONTACT MAY CAUSE IRRITATION & CORNEAL INJURY. ABSORPTION THROUGH SKIN CAN OCCUR. MAY DRY SKIN. INHALATION MAY CAUSE IRRITATION & CNS DEPRESSION. INGESTION MAY CAUSE CNS DEPRESSION, LIVER & KIDNEY DAMAGE.

CHRONIC- SKIN DEFATTING & DERMATITIS. TARGET ORGANS:CNS, EYES, SKIN, LUNGS, LIVER, KIDNEYS, GI TRACT.

Explanation of Carcinogenicity:CONTAINS LEAD. NONE OR THE COMPONENTS OF THIS PRODUCT ARE RECOGNIZED AS CARCINOGENIC.

Effects of Overexposure:EYES, SKIN, RESPIRATORY AND GASTRO-INTESTINAL TRACTS IRRITATION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, BRAIN, LIVER & KIDNEY DAMAGE

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS

OR IMPAIRED CNS OR RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:WASH WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL:IF UNCONSCIOUS, DRINK TWO GLASSES OF WATER & INDUCE VOMITING. IF VOMITING, KEEP VICTIM'S HEAD BELOW HIS HIP

S. GET IMMEDIATE MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:=-6.7C, 44.F

44 +/-2 F

Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

Fire Fighting Procedures:WARNING! FLAMMABLE. CLEAR AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT HELMET, FACE SHIELD, BUNKER COAT,GLOVES, RUBBER BOOTS, AND A POSITIVE PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS

PPRATUS.

Unusual Fire/Explosion Hazard:CONTAINER EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRES-SURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME SHOULD BE COOLED WITH LARGE QUANTITIES OF WASTER AS NEEDED TO PREVENT WEAKING OF CONTINER STRUCTURE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. REMOVE SOURCES OF IGNITION.

VENTILATE AREA. ABSORB LIQUID WITH NON-FLAMMABLE ABSORBENT MATERIALS SUCH AS CLAY, SAND AND PLACE IN CONTAINER FOR DISPOSAL. PREVENT SPILLS FROM ENTERING SEWERS OR WATERWAYS.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS IN COOL, WELL VENTILATED AREAS AWAY FROM SOURCES OF IGNITION SUCH AS SPARKS, FLAMES, WELDING ARCS & INCOMPATIBLE MATERIALS.

Other Precautions:"EMPTY" CONTA

INERS RETAIN RESIDUE AND CAN BE

DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS. THEY MAY EXPLODE AND CAUSE INJURY. AVOID RE PEATED OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID PROLONGED OR REPEATED BREATHING OF VAPORS/DUST. IF EXPOSURE EXCEEDS TLV USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

Ventilation:MECHANICAL (GENERA

L AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)

VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:PLASTIC, RUBBER

Eye Protection:CHEMICAL SAFETY GOGGLES(PREVENT CONTACT)

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWERS SHOULD BE AVAILABLE IN THE IMMEDIATE VICINITY OF ANY POTENTIAL EXPOSURE.

Work Hygienic Practices:USE ONLY AS DIRECTED ON LABEL. READ LABEL BEFORE USING PRODUCT. DO NOT BREATHE VAPORS. WASH HANDS BEFORE EATING.

Supplemental Safety and Health

FLAM

MABLE. DO NOT USE IN CONFINED AREA OR AREA WITH LITTLE AIR
MOVEMENT. EMPLOY MEANS TO PREVENT VAPOR BUILDUP. KEEP OUT OF REACH
OF CHILDREN.

===== Physical/Chemical Properties =====

HCC:F2
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:B.P. Text:NOT KNOWN
Vapor Density:>1
Spec Gravity:1.09
pH:3.00
VOC Grams/Liter:5.85
Evaporation Rate & Reference:0.00 (BUTYL ACETATE=1)
Appearance and Odor:LUBRICANT, COLOR, BLACK.
Percent Volatiles by Volume:83.4

=====

=== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES
Hazardous Decomposition Products:LEAD OXIDE FUMES, CARBON MONOXIDE,
CARBON DIOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED
DURING COMBUSTION.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE O
F IN ACCORDANCE WITH ALL LOCAL, STATE
AND FEDERAL REGULATIONS.

===== Regulatory Information =====

SARA Title III Information:LISTED BY SARA: METHYL ETHYL KETONE, DIBASIC
LEAD PHOSPHITE, ANTIMONY TRIOXIDE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this inf

ormation to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.