View NSN Online: https://aerobasegroup.com/nsn/8010-00-111-6384

SERMATECH INTERNATIONAL INC SUB OF TELEFEX INC -- SERMETEL 249 -- 8010-00-111-6384

Product ID:SERMETEL 249 MSDS Date:08/01/1997

FSC:8010

NIIN:00-111-6384 Status Code:A

MSDS Number: CJWRV === Responsible Party ===

Company Name: SERMATECH INTERNATIONAL INC SUB OF TELEFEX INC

Address:155 S LIMERICK RD

City:LIMERICK

State:PA

ZIP:19468-1603 Country:US

Info Phone Num:6

10-948-5100

Emergency Phone Num:215 948-5100

CAGE:58913

=== Contractor Identification ===

Company Name: SERMATECH INTERNATIONAL INC SUB OF TELEFEX INC

Address:155 S LIMERICK RD

Box:City:LIMERICK

State:PA

ZIP:19468-1603 Country:US

Phone:610-948-5100

CAGE:58913

======= Composition/Information on Ingredients ========

Ingred Name: ALUMINUM METAL POWDER

CAS:7429-90-5

RTECS #:BD0330000 Minumum % Wt:20. Maxumum % Wt:40. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:ZINC DUST

CAS:7440-6

6-6 RTECS #:ZG8600000 Minumum % Wt:20. Maxumum % Wt:40. EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:AQUEOUS ALKALI SILICATE CAS:1312-76-1 Minumum % Wt:20. Maxumum % Wt:40.
======================================
Health Hazards Acute and Chronic:SKIN/EYES: MAY CAUSE IRRITATION. INHALATION: IRRITATION TO LUNGS & MUCOUS MEMBRANES W/CHRONIC INHALATION OF THE ATOMIZED MIST. Effects of Overexposure:IRRITATION, TIGHTNESS OF CHEST, METALLIC TASTE, CO
UGH, DIZZINESS, FEVER, CHILLS, HEADACHE, NAUSEA, DRY THROAT, METAL FUME FEVER/ZINC SHAKES.
======================================
First Aid:EYES: IRRIGATE W/RUNNING WATER FOR 15 MINS. SKIN: RINSE W/WATER. INGESTION: RINSE MOUTH THOROUGHLY W/WATER. DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASE S.
======================================
Flash Point:NONE Extinguishing Media: CO2, SAND, DRY CHEMICAL Fire Fighting Procedures:COATING CONTAINS FINELY DIVIDED ALUMINUM & ZINC. DON'T USE WATER BASED EXTINGUISHING AGENTS. Unusual Fire/Explosion Hazard:DIRECT CONTACT W/ACIDS MAY PRODUCE HYDROGEN GAS.
========= Accidental Release Measures ==========
Spill Release Procedures: ABSORB ONTO INERT INORGANIC ABSORBENT & FLUSH AREA W/EXCESS WATER.
=========== Handling and Storage =============

Handling and Storage Precautions:SH

ORIGINAL CONTAINERS. STORAGE TEMP: 40-90F. DON'T FREEZE. STORE INSIDE IN ORIGINAL CONTAINERS. SHAKE BOTTLE & RELEASE CAP ONCE EVERY TWO WEEKS TO HELP MAINTAIN PIGME NT SUSPENSION & TO RELIEVE ANY PRESSURE. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: SUPPLIED AIR RESPIRATORS ARE RECOMMENDED FOR SPRAY APPLICATION. Ventilation: SPRAY BOOTH SHOULD HAVE MINIMUM AIR FLOW OF 150 FT. Protective Gloves:R **EQUIRED** Eye Protection: REQUIRED Other Protective Equipment: APPLY COATING IN A CLEAN WELL VENTILATED AREA. Work Hygienic Practices: SERMETEL 249 IS A SLURRY OF INORGANIC METAL PIGMENTS DISPERSED IN AN AQUEOUS ALKALI SILICATE SOLUTION. ALWAYS USE GOOD INDUSTRIAL HYGIENE PRACTICES WHEN HANDLING THIS PRODUCT. Supplemental Safety and Health SOLUBILITY: BINDER IS MISCIBLE; PIGMENT IS INSOLUBLE. ========= Physical/Chemical Properties =========== Vapor Pres:23.7 Vapor Dens ity:0.7 Spec Gravity:1.72-1.8 pH:10-12 Evaporation Rate & Evaporation R Solubility in Water:(SEE SUPP) Appearance and Odor: GRAY PIGMENT SUSPENDED IN CLEAR BINDER: NO ODOR Percent Volatiles by Volume:73 ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES ACIDS, ALKALIS, STRONG OXIDIZING/REDUCING AGENTS Stability Condition to Avoid:FREEZING Hazardous Decomposition Products: HYDROGEN GAS

ELF LIFE: 6 MONTHS WHEN STORED IN

====== Disposal Conside

rations					
rations	 	 	 	 	_

Waste Disposal Methods:PIGMENT MAY BE FILTERED TO DISPOSE OF SEPARATELY. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

============ Other Information ==============================

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informat ion to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.