

PRAXAIR SURFACE TECHNOLOGIES INC -- NI-567 PRODUCT CODE: ZNI567-0005 --
3439-01-426-5424

===== Product Identification =====

Product ID:NI-567 PRODUCT CODE: ZNI567-0005

MSDS Date:02/06/1996

FSC:3439

NIIN:01-426-5424

Status Code:A

MSDS Number: CJWTX

=== Responsible Party ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

|

Info Phone Num:317-240-2650

Emergency Phone Num:(800)424-9300

Preparer's Name:J. HUDDLESTON

Chemtec Ind/Phone:(800)424-9300

CAGE:0FGH2

=== Contractor Identification ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

Box:City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:0FGH2

Company Name:STARGHILL TECHNOLOGIES CORP

Address:3850 OAKMAN BLVD

Box:City:DETROIT

State:MI

ZIP:48204-1119

Country:US

Phone:313-933-4141

Contract Num:SP0450-95-D-4037

CAGE:0

VYG8

=====
Composition/Information on Ingredients
=====

Ingred Name:CHROMIUM
CAS:7440-47-3
RTECS #:GB4200000
Minumum % Wt:1.
Maxumum % Wt:5.
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:NICKEL
CAS:7440-02-0
RTECS #:QR5950000
> Wt:75.
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Minumum % Wt:1.
Maxumum % Wt:5.
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:BORON
CAS:7440-42-8
RTECS #:ED7350
000
Minumum % Wt:1.
Maxumum % Wt:5.

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Minumum % Wt:1.
Maxumum % Wt:5.

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:SKIN:MAY CAUSE ALLERGIC DERMATITIS,
WITH REDNESS & PAPULAR FORMATION IN SUSCEPTABLE INDIVIDUALS. MAY
CAUS

E ULCERS PROGRESSING TO DRY & SCALY SKIN, FEVER. EYE:MAY CAUSE IRRITATION, EXPERIENCED AS REDNESS & EXCESS REDNESS OF THE CONJUNCTIVA. SWALLOWING: MAY CAUSE NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, CENTRAL NERVOUS SYSTEM DEPRESSION, & BURNING SENSATION. INHALATION:MAY CAUSE RESPIRATORY TRACT IRRITATION, WITH CHEST PAIN, VOMITING, DIARRHEA, BURNING SENSATION, & CENTRAL NERVOUS SYSTEM DEPRESSION. MAY ALSO CAUSE INTERSTITIAL PNEUMONITIS & SENSITIZATION OF THE RESPI

RATORY TRACT IN SUSCEPTIBLE PERSONS.

Explanation of Carcinogenicity:NICKEL AND CHROMIUM HAVE BEEN DETERMINED TO CAUSE CANCER IN EXPERIMENTAL ANIMALS (IARC, NTP). NICKEL IS LISTED AS A PROBABLE HUMAN CARCINOGEN. CHROMIUM IS LISTED AS A HUMAN CARCINOGEN. CHRONIC ECZEMA/NEURODERMATITIS FROM NICKEL DOES NOT REQUIRE CONTINUOUS METAL CONTACT.

Effects of Overexposure:MAY CAUSE SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS. CHRONIC EXPOSURE TO THE EYE CAN CAUSE CORNEAL DAMAGE, POLYCY

THEMIA, HYPERPLASIA OF THE THYROID GLAND AND DAMAGE TO THE ALPHA CELLS OF THE PANCREAS. REPEATED INHALATION MAY CAUSE EMPHYSEMA OR PULMONARY FIBROTIC DISEASE. CHRONIC SKIN CONTACT MAY SPREAD TO THE WHOLE BODY WITH LESIONS, ITCHING, SORENESS, BURNING SENSATION AND REDNESS.

Medical Conditions Aggravated by Exposure:BREATHING OF DUST MAY AGGRAVATE ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE. MAY ALSO AGGRAVATE AN EXISTING DERMATITIS.

=====
First Aid

Measures =====

First Aid:SWALLOWING:GIVE AT LEAST 2 GLASSES OF MILK OR WATER. INDUCE VOMITING, UNLESS PATIENT IS UNCONSCIOUS. CALL A PHYSICIAN. SKIN:WASH THOROUGHLY WITH SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. OXYGEN MAY BE GIVEN IF NECESSARY. CALL A PHYSICIAN. EYES: FLUSH THOROUGHLY WITH PLENTY OF WATER. IF DISCOMFORT PERSISTS, SEEK MEDICAL ATTENTION. PREFERABLY AN OPHTHALMOLOGIST. NOTES TO PHYSICIAN

:THE HAZARDS OF

THIS MATERIAL ARE MAINLY DUE TO ITS SENSITIZING AND MILD IRRITATING PROPERTIES. THERE IS NO SPECIFIC ANTIDOTE.

=====
Fire Fighting Measures =====

Flash Point:NONE

Upper Limits:0.00%

Extinguishing Media:USE SPECIAL DRY POWDER METAL EXTINGUISHING MATERIAL TO EXTINGUISH METAL FIRES. USE APPROPRIATE EXTINGUISHER FOR COMBUSTIBLE MATERIALS THAT MAY BE IGNITED BY THE THERMAL SPRAY FLAME.

Fire Fighting Procedures:NONE SPECIFIED BY M

ANUFACTURER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST HAZARDS AND DISPOSE OF PER WASTE DISPOSAL METHOD.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:CAUTION: WHEN THERMAL SPRAYING - ELECTRICITY CAN

CAUSE FATAL SHOCK! DO NOT TOUCH LIVE ELECTRICAL PARTS! ARC RAYS CAN BURN EYES AND SKIN! WEAR RECOMMENDED EYE AND BODY PROTECTION. FUMES, GAS, AND DUST CAN HARM YOUR HEALTH. PROVIDE ENOUGH VENTILATION AND WEAR RESPIRATOR IF REQUIRED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DEPENDS UPON SPECIFIC USE, CONDITION, AND LOCATION. IF THERE IS DUSTINESS, WEAR RESPIRATOR SELECTED PER OSHA 1910.134, AND OS

HA 29 CFR 1910.252 AND ANSI Z49.1.

Ventilation:LOCAL DUST PICK UP AND VENTILATION RECOMMENDED.

Protective Gloves:NOT REQUIRED.

Eye Protection:WHEN DUSTY USE GOGGLES PER OSHA 1910.13

Other Protective Equipment:SEE ANSI Z49.1, ANSI Z87.1, ANSI Z88.2 FOR HELMETS, FACE SHIELDS AND GOGGLES.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B

.P. Text:NONE

Vapor Density:N/VOLATILE

Evaporation Rate & Reference:UNAVAILABLE

Appearance and Odor:DUSTY DARK GRAY POWDER

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN.

Stability Condition to Avoid:NONE KNOWN.

Hazardous Decomposition Products:WHEN THERMAL SPRAYING, WILL VARY WITH OPERATING CONDITIONS. REASONABLY EXPECTED DECOMPOSITION PRODUCTS OF NORMAL OPERATION FROM THIS THE

RMAL SPRAY POWDER INCLUDE OXIDES OF
THE LISTED INGREDIENTS.

===== Toxicological Information =====

Toxicological Information:NONE SPECIFIED BY MANUFACTURER.

===== Ecological Information =====

Ecological:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE PER LOCAL, STATE, AND FEDERAL
REGULATIONS.

===== MSDS Transport I
nformation =====

Transport Information:NONE SPECIFIED BY MANUFACTURER.

===== Regulatory Information =====

SARA Title III Information:PRODUCT CONTAINS THE FOLLOWING TOXIC
CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF
THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND
OF 40 CFR 372: CHROMIUM, CAS# 7440-47-3, 75%.

Federal Regulatory Information:ALL COMPONENTS OF THIS PRODUCTS ARE
LISTED IN TSCA

State Regulatory Information:CALIFORNIA PROPOSITION 65 (CARCINOGEN):
CHROMIUM, CAS# 7440-47-3; NICKEL, CAS# 7440-02-0. CALIFORNIA
PROPOSITION 65 (TERATOGENIC): NONE. CALIFORNIA PROPOSITION 65 (BOTH
TERATOGENIC AND CARCINOGEN): NO NE.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of Ameri

ca in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.