View NSN Online: https://aerobasegroup.com/nsn/9150-01-413-6897

GARD CORPORATION -- GARD HIGH PERFORMANCE 10W-30 -- 9150-01-413-6897

Product ID:GARD HIGH PERFORMANCE 10W-30

MSDS Date:01/01/1987

FSC:9150

NIIN:01-413-6897

Status Code:A

MSDS Number: CJYBJ === Responsible Party ===

Company Name: GARD CORPORATION

Address:2727 ROE LANE

City: KANSAS CITY

State:KS ZIP:66103 Country:US

Info Phone Num:913-236-5000 Emergency Phone Num:91

3-236-5000

Preparer's Name: ROBER BENTZ

CAGE:3K676

=== Contractor Identification ===

Company Name: UNIMARK OIL COMPANY (FORMERLY GARD OIL)

Address:2727 ROE LANE

City:KANSAS CITY

State:KS

ZIP:66103-1543 Country:US

Phone:913-236-5000; FX 913-236-4419

CAGE:3K676

====== Composition/Information on Ingredients ========

Ingred Name:RE-REFINED HYDROTREATED PETROLEUM LUBRICATING OIL

CAS:64742-62-7

Fraction by Wt: 50-60%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SOLVENT DEWAXED RESIDUAL

OIL (PETROLEUM) CAS:64742-62-7

Fraction by Wt: 20-25%

Other REC Limits: NONE RECOMMENDED

Ingred Name:PROPRIETARY ADDITIVES IN CARRIER OIL

Fraction by Wt: 20-25%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ZINC C1-C14 ALKYLDITHIOPHOSHPATE

CAS:68649-42-3 Fraction by Wt: 0-1.2%

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification =============

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports

of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN:MATL AFT PROL/REP CONTACT MAY CAUSE IRRIT DUE TO SENSITIZATION,RASH,ERMATITUS.EYE:MATL WILL CAUSE IRRIT.INHAL:EXCESSIVE HOT VAP/OIL MIST INHAL CAN CASUE NASAL/RESP IRRIT.INGEST:SYMPTOMS SIMILAR TO INHAL W/ADDN HEALTH CONCERNS SUCH AS CHEM PNEUMONITIS(ASPIRATION OF CHEM INTO LUNGS).HAS LAXATIVE PROPERTIES (SUPPLEM)

Explanation of Carcinogenicity:PER MSDS:USED MOTOR OIL HAS BEEN SHOWN TO CAU

SE SKIN CANC IN CERTAIN LAB ANIMALS CONT EXPO TO USED MOTOR OIL BY REP APPL

Effects of Overexposure: SKIN IRRIT DUE TO SENSITIZATION, RASH, ERMATITUS. EYE IRRIT. NASAL/RESPIRATORY IRRIT. CHEMICAL PNEUMONITIS, LAXATIVE PROPERTIES, NAUSEA, ABDOMINAL CRAMPS, DIARRHEA.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE/SKIN:IMMED FLUSH EYE W/LG AMT OF WATER FOR @LEAST 15MINS.WASH SKIN AREA

S WELL W/SOAP/WATER.REMOVE EXPO CLOTH.IRRIT
PERSIST CONSULT PHYSICIAN.INHAL:REMOVE TO FRESH AIR.NOT BREATH GIVE
ART RESP.DIFF BREATH ADMINISTER OXY.GET PROMPT MED ATTN.INGEST:DO
NOT INDUCE VOMIT.KEEP WARM/QUIET.NEVER GIVE ANYTHING BY MOUTH TO
DROWSY/UNCONSC PERSON.GET IMMED MED ATTN.

============ Fire Fighting Measures =========================

Flash Point Method:COC Flash Point:392F,200C Autoignition Temp:Autoignition Temp Text:NP Lower Limits:N/DETERMINED Upper Limits

:N/DETERMINED

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, POLYMER FOAM, WATER FOG.

Fire Fighting Procedures:ADDN OF WATER TO BURNING MATL WILL REDUCE INTENSITY OF FLAME BUT SPREAD FIRE.FIREFIGHTERS SHOULD BE EQUIPPED W/APPROPRIATE PROT GEAR,USE MSHA/NIOSH APPROVE(SUP)

Unusual Fire/Explosion Hazard: CNTNR DEVELOP PRESSURE WHEN HEATED; MAY RUPTURE DURING FIRE CAUSING POT EXPLO SITUATION. KEEP SEAL CNTNR COLL W/WATERSPRAY. CNTNR SUED FOR STORAGE MAY RETAIN (SUPP)

=========

==== Accidental Release Measures =========

Spill Release Procedures:USE PPE.IMMED TURN OFF/ISOLATE IGN SOURCES.EVACUATE AREA/VENTI.PERSONNEL W/PROPER PPE SHOULD CONTAIN SPILL IMMED W/INERT MATLS(SAND,EARTH,CHEM SPILL PADS OF COTTON)W/DIKES IN MANNER THAT KEEP SPILL AW AY FROM SEWERS/WATERWAYS.LG:CONTAIN.PICKUP(SUPP)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=========== Handling and Storage ===============

Handling and Storage Precautions

:DON'T TRANSFER TO UNMARKED

CNTNRS.STORE IN CLSD CNTNRS AWAY FROM HEAT/SPARKS/OPEN FLAME/OXIDIZING MATLS.PROD CLASSIFIED AS COMBUST UNDER DOT REGS.

Other Precautions:FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE.SEE NFPA 30 & OSHA 1910.106-FLAMM/COMBUSTIBLE LIQS.AVOID PROL/REP CONTACT TO SKIN.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:NONE REQUIRE IF AIRBORNE CONCEN MAINTAIN BEL THRESHHOLD LIMITS.OTHERWISE RESPIRATORY P

ROTECTION PROGRAM MEETING

OSHA 1910.134/ANSI Z88.2 REMQTS MUST BE FOLLOWED.MISTING-WEAR MSHA/NIOSH APPROV/EQUIVA 1 /2MASK FORM DUST/MIST AIR PURI RESPIRATR Ventilation:USE ADQU VENTI WHEN WORK W/MATL IN ENCLSD AREA.MECH METHODS(FUME HOODS,AREA FANS)USE TO RED LOC VAP/MIST AREA.

Protective Gloves:SOLVT IMPERV-VINYL, PLAST, NITRIL, BUTYL RB

Eye Protection:SAF GLASSES W/SIDESHIELD, VENT GOGG.

Other Protective Equipment:EYEWASH STATIONS,SHOWERS SHOULD BE AVAI IN AREA WHERE MATL USED/STOR

ED.EYE WARE: ANSI Z87.1 OR APPROVE EQUIV.

Work Hygienic Practices: LAUNDER EXPO CLOTH BEF REUSE.

Supplemental Safety and Health

FIREFIGHTER:BREATH MASK(PRESSURE DEMAND/EQUIVAL). FIRE/EXPLO HAZ:COMBUST/FLAMM VAP.AVOID HEAT/WELD/CUT/ETC OF EMPTY DR-AVOIDS POSSIBILITY OF IGN RESIDUE.RETURN DR TO PROPER COLLECTION SITES FOR DISPO/ RECYC. HEALTH:MAY CAUSE NAU,ABD CRAMPS,DIARR. SPILL:W/EXPLO PROOF/NONSPARK VAC PUMPS/SHOVEL/ETC & NOTIFY AUTHORITIES.

======= Physical/Chemical

Properties ========

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C Melt/Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decomp Text:NP

Vapor Pres:1

Spec Gravity: 0.88 @15.6C

pH:NP

Viscosity:NP

Evaporation Rate & DETERMINED.

Solubility in Water: NOT SOLUBLE.

Appearance and Odor:AMBER-BROWN FLUID W/CHARACTERISTIC PETROLEUM ODOR.

Percent Volatiles by Volume: