

SPRAYON PRODUCTS DIV SHERWIN-WILLIAMS CO -- KRYLON 1303/1303A CRYSTAL CLEAR --
8010-01-005-8577

===== Product Identification =====

Product ID:KRYLON 1303/1303A CRYSTAL CLEAR

MSDS Date:08/20/1994

FSC:8010

NIIN:01-005-8577

Status Code:A

MSDS Number: CJYPN

=== Responsible Party ===

Company Name:SPRAYON PRODUCTS DIV SHERWIN-WILLIAMS CO

Address:31500 SOLON ROAD

City:SOLON

State:OH

ZIP:44139-5000

Cou

ntry:US

Info Phone Num:800-777-2966

Emergency Phone Num:216-292-7400

CAGE:09800

=== Contractor Identification ===

Company Name:NASCO INTL INC., NASCO DIV

Address:901 JANESVILL AVE

Box:City:FORT ATKINSON

State:WI

ZIP:53538-0901

Country:US

Phone:920-563-2446

CAGE:33089

Company Name:SAX ARTS & CRAFTS SUB OF BEATRICE COMPANIES INC

Address:2405 S CALHOUN RD

Box:City:NEW BERLIN

State:WI

ZIP:53151

Country:US

Phone:262-784-6880

CAGE:26290

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26

300 FARGO AVENUE
Box:City:BEDFORD HEIGHTS
State:OH
ZIP:44146
Country:US
Phone:216-292-7400 OR 216-595-8634
CAGE:09800

=====
===== Composition/Information on Ingredients =====

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9495

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:V M & P NAPHTHA
CAS:64742-89-8
Fraction by
Wt: 22%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PETROLEUM HYDROCARBON,
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 13%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313)
CAS:100-41-4
RTECS #:DA0

700000
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/125STEL;9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 13%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 11%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:750PPM/1000STEL;9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOLATILE ORGANIC CONTENT = 92%
RTECS #:9999999VO
Fraction by Wt: 92%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-IRRI

TATION TO EYES, SKIN &

RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS & POSSIBLY DEATH.

CHRONIC- PROLONGED &/OR REPEATED OVEREXPOSURE MAY CAUSE PERIPHERAL NEUROPATHY, ADVERSE EFFECTS TO LIVER, URINARY, BLOOD FORMING, CVS, CNS OR REPRODUCTIVE SYSTEM

Explanation of Carcinogenicity:NO INGREDIENT IN THESE PRODUCTS IS AN NTP, IARC OR OSHA LISTED CARCINOGEN. SOME MAY BE LISTED BY CALIFORNIA.

Effects of Overexposure:

HEADACHE, DIZZINESS, NAUSEA & LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MIST.

Medical Condition Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:IF IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL ATTENTION.

EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRY BEFORE REUSE. INHALED:REMOVE FROM EXPOSURE. AID OR RESTORE BREATHING AS NEEDED. KEEP WARM & QUIET.

SWALLOWED: GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:1

Spec Gravity:NOT GIVEN

Evaporation Rate & Reference:>1 (ETHER)

Solubility in Water:NOT GIVEN

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:

NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE & CARBON MONOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE FROM THESE PRODUCTS MAY BE HAZARDOUS UNDER RCRA (40CFR261) & MUST BE TESTED TO DETERMINE RCRA WASTE NUMBERS. DO NOT INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF I/A/W FEDERAL, STATE & LOCAL REGULATIONS REGARDING

DING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.