

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3201 CLASS B BLACK (PART A) --
8030-01-262-9041

===== Product Identification =====

Product ID:CS 3201 CLASS B BLACK (PART A)
MSDS Date:06/13/1997
FSC:8030
NIIN:01-262-9041
Status Code:A
MSDS Number: CJZRQ
=== Responsible Party ===
Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV
Address:11120 SHERMAN WAY
City:SUN VALLEY
State:CA
ZIP:91352-4949
Country:US
In
fo Phone Num:818-982-1650
Emergency Phone Num:(800)424-9300
Chemtec Ind/Phone:(800)424-9300
CAGE:14439

=== Contractor Identification ===
Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV
Address:11120 SHERMAN WAY
Box:City:SUN VALLEY
State:CA
ZIP:91352-4949
Country:US
Phone:818-982-1650
CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:LIQUID POLYSULFIDE POLYMER
CAS:68611-50-7
= Wt:65.

===== Hazards Identification =====

Health Hazards Acute and Chronic:POSSIBLE SKIN IRRITATION AFTER PROLONGED CONTACT, WITH RESULTING DERMATITIS. NOT CONSIDERED TO BE A PRIMARY SKIN IRRITANT.

Effects of Overexposure:SKIN OR IRRITATION.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH WITH LARGE AMOUNTS OF WATER, CONSULT PHYSICIAN.
SKIN-WASH WITH SOAP AND WATER. INGESTION- INDUCE VOMITING,
CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:~93.3C, 200.F
200F

Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AND TRANSFER TO CONTAINER FOR REACTION WITH CURING AGENT. CLEANUP RESIDUE WITH AEROMATIC NAPHTHA/SAND/SWEEPING COMPOUND. WASH AREA WITH SOAP AND WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY AREA AWAY FROM STRONG ACIDS.

Other Precautions:WASH HANDS BEFORE EATING, SMOKING OR DRINKING AFTER HANDLING THIS PRODUCT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:LOCAL EXHAUST: AIR. MECHANICAL: FAN.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.

Work Hygienic Practices:TRAIN EMPLOYEES IN SAFE HANDLING OF THIS PRODUCT.

Supplemental Safet

===== Physical/Chemical Properties =====

Vapor Density:NIL
Spec Gravity:1.50
Evaporation Rate & Reference:1
Solubility in Water:NEGLEGABLE
Appearance and Odor:BLACK PASTE, POLYSULFIDE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS AND STRONG ACIDS
Stability Condition to Avoid:OPEN FLAME
Hazardous Decomposition Products:H2S, CO, CO2, SO2, SMOKE.

=====

===== Disposal Considerations =====

Waste Disposal Methods:REACT WITH CURING AGENT AND DISPOSE AS HAZARDOUS WASTE, NON-MIX , NON-HAZARDOUS.

===== MSDS Transport Information =====

Transport Information:UNIT CONTAINER: 6 OZ IN 1/2-PINT METAL
CAN.SHIPPING NAME: ADHESIVE N.O.S. HAZARD CLASS: NON-HAZARDOUS
UNIT CAONTAINER: 12 OZ IN 16 OZ METAL CAN. US POSTAL
REGULATIONS: PARA 124.142 HARMFUL M ATTER. DISPOSAL INFO:

INCINERATION OR LAND DISPOSAL, MIXED WITH PART B, HAZARDOUS WASTE,
NON-MIX, NON-HAZARDOUS. EPA CODE: CADO62064746. WASTE
CHARACTERISTICS: SLUDGE. DISPOSAL METHODS: INCINER ATION OR LAND
DISPOSAL, DISPOSE WASTE ACCORDING TO FEDERAL, STATE AND LOCAL
REGULATIONS. APPLICABLE REGULATIONS: 49 CFR, IMO, IATA.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States
of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.