

GRIGGS PAINT -- TT-S-711C DK WALNUT OIL STAIN, 700N150 -- 8010-00-281-2076

=====  
Product Identification  
=====

Product ID:TT-S-711C DK WALNUT OIL STAIN, 700N150

MSDS Date:01/01/1994

FSC:8010

NIIN:00-281-2076

Status Code:A

MSDS Number: CKCXN

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency

Phone Num:800-424-9300 CHEMTREC

Preparer's Name:ROBERT COMMISSO

Chemtrek Ind/Phone:(800)424-9300

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC HYDROCARBONS (STODDA

RD TYPE) (SARA III) (VAPOR  
PRESSURE 2.0 MM HG @ 68F)  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 45%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:CONTACT TO EYES MAY CAUSE IRRIT.  
PROLONGED/ REPEATED CONTACT MAY CAUSE SKIN IRRIT. INHALATION OF  
HIGH CONCENTRATION MAY LEAD TO LUNG  
CHANGES,NAUSEA,VOMIT  
ING,COUGH,PULMONARY IRRIT & CENTRAL NERVOUS SYS  
TEM DEPRESSION. INGESTION MAY CAUSE GI DISTURBANCES. ASPIRATION  
INTO LUNG MAY CAUSE PNEUMONITIS,PULMONARY EDEMA,HEMORRHAGE.  
Effects of Overexposure:INHAL: BREATHING HIGH VAPOR CONCENTRATIONS MAY  
CAUSE DROWSINESS,DIZZINESS,FATIGUE,FOLLOWED BY COMA. EYE: MAY CAUSE  
IRRITATION. SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE  
IRRITATION/DERMATITIS. MAY BE A BSORBED THROUGH SKIN WHICH IS  
INDICATED BY IRRITATION, DERMATITIS, & DEFATTING.

INGESTION:ASPIRATION INTO LUNGS MAY CAUSE PNEUMONITIS,PULMONARY  
EDEMA & HEMORRAGE. MAY CAUSE GI DISTURBANCE.  
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING  
DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN, CENTRAL NERVOUS  
SYSTEM, LIVER AND KIDNEY.

=====  
===== First Aid Measures =====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER  
FOR 15 MINUTES. SEEK MEDICAL AID. SKIN: WASH THOROUGHLY WITH SOAP  
A  
ND WATER. SEEK MEDICAL AID IF IRRITATION PERSISTS. INGESTION:  
IMMEDIATELY SEEK MEDICAL AID. DO NOT INDUCE VOMITING. DO NOT  
ATTEMPT TO GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:=43.3C, 110.F  
Lower Limits:1.0  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG  
Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING  
PERSONEL. WATER MAY BE INEFFECTIVE. WATER

MAY BE USED TO COOL

CONTAINERS. IF WATER IS USED, FOG NOZZLES PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE .

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UPRIGHT TO PREVENT LEAKAGE. AVOID FLAMES, WELDING, OPEN LIGHTS, ETC. AVOID BREATHING OF VAPOR AND SPRAY MISTS. AVOID SKIN/EYE CONTACT. MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT, WITHOUT ADEQUATE VENTILATION.

Other Precautions:DO NOT STORE NEAR OR NEXT TO OXIDIZING MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENT DOESN'T MAINTAIN INHALATION EXPOSURES