

PILKINGTON AEROSPACE INC (FORMERLY- SWEDLOW INC) -- SS-6832 PT B -- 1560-01-308-8459
===== Product Identification =====

Product ID:SS-6832 PT B
MSDS Date:02/04/1998
FSC:1560
NIIN:01-308-8459
Status Code:A
MSDS Number: CKDLC
=== Responsible Party ===
Company Name:PILKINGTON AEROSPACE INC (FORMERLY- SWEDLOW INC)
Address:12122 WESTERN AVE
City:GARDEN GROVE
State:CA
ZIP:92641
Country:US
Info Phone
Num:714-893-7531
Emergency Phone Num:800-424-9300
CAGE:86175
=== Contractor Identification ===
Company Name:PILKINGTON AEROSPACE INC (FORMERLY- SWEDLOW INC)
Address:12122 WESTERN AVE
Box:City:GARDEN GROVE
State:CA
ZIP:92641
Country:US
Phone:714-893-7531
Contract Num:SP0460-97-M-DD28
CAGE:86175

===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYLMETHYLHYDROGEN POLYSILOXANES
CAS:68037-59-2
= Wt:2.

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Health Hazards Acute and Chronic:EYE CONTACT: DIRECT CONTACT MAY CAUSE TEMPORARY DISCOMFORT WITH MILD REDNESS AND DRYNESS SIMILAR TO WIND BURN. SKIN: A SINGLE RELATIVELY SHORT EXPOSURE CAUSES NO KNOWN ADVERSE EFFECT. SEVERAL REPEATED PROLONGED EXPOSURES (24 TO 48 HOURS) CAUSES NO KNOWN ADVERSE EFFECT. INHALATION: NO IRRITATION TO EYES AND RESPIRATORY PASSAGES. NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOSURE OF LESS THAN 8 HOURS. INGESTION: SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.
Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY: MANUFACTURERS MSDS IDENTIFIES THIS PRODUCT AS NOT A CARCINOGEN.
Effects of Overexposure:EYES: TEMPORARY DISCOMFORT WITH MILD REDNESS AND DRYNESS SIMILAR TO WINDBURN. SKIN: NO KNOWN ADVERSE EFFECTS. INHALATION: NO IRRITATION OR INJURY LIKE
LY. INGESTION: DIGESTIVE DISCOMFORT. CHRONIC HEALTH EFFECTS: NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED.
Medical Cond Aggravated by Exposure:THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. MANUFACTURER DOES NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:E
YES: FLUSH WITH WATER. SKIN: WIPE OFF AND FLUSH WITH WATER. INHALATION: NO FIRST AID SHOULD BE NEEDED. INGESTION: NO FIRST AID SHOULD BE NEEDED.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:=100.C, 212.F
Autoignition Temp:Autoignition Temp Text:N/D
Lower Limits:N/D
Upper Limits:N/D
Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING

SHOULD BE WORN IN FIGHTING FIRES INVOLVING
CHEMICALS.

Unusual Fire/Explosion Hazard:NONE KNOWN TO PILKINGTON AEROSPACE.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN
FOR SALVAGE OR DISPOSAL. PRODUCT IS AN OIL IN THE CONTEXT OF THE
U.S. CLEAN WATER ACT. SPILLS TO U.S. SURFACE WATER, OR TO
WATERCOURSE OR SEWERS LEADING TO U.S. SURFACE WATER THAT CAUSE A
VISIBLE SHEEN MUST BE REPORTED
TO THE NATIONAL RESPONSE CENTER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 100F/38C. USE REASONABLE
CARE AND CAUTION. MAY GENERATE FLAMMABLE HYDROGEN GAS. AVOID
CONTACT WITH WATER, ACIDIC, BASIC OR OXIDIZING MATERIALS. STORE IN
ORIGINAL CONTAINER IN COOL, WELL- VENTILATED AREA.

Other Precautions:TRACES OF FORMALDEHYDE AND OTHER THERMAL
DECOMPOSITION PRODU

CTS MAY FORM AT TEMPERATURES ABOVE 150C IN THE
PRESENCE OF AIR. PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE
WITHIN INHALATION GUIDELINES WHEN HANDLING AT ELEVATED
TEMPERATURES. REPORT SPILLS THAT MAY ENTER SURFACE WATERS TO
NATIONAL RESPONSE CENTER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO RESPIRATORY PROTECTION SHOULD BE NEEDED WHEN
HANDLING AT ROOM TEMPERATURE. WHEN HANDLING AT ELEVATED
TEMPERATURES, OR AEROSOL/S
PRAY APPLICATIONS, ADDED PRECAUTIONS MAY
BE REQUIRED.

Ventilation:LOCAL EXHAUST: NONE SHOULD BE NEEDED. MECHANICAL(GENERAL):
RECOMMENDED FOR ROOM TEMP HANDLING. MAY REQUIRE ADDED PRECAUTION
AT ELEVATED TEMP OR WHEN SPRAYING

Protective Gloves:NOT APPLICABLE.

Eye Protection:USE PROPER PROTECTION-SAFETY GLASSES, AS A MINIMUM.

Work Hygienic Practices:WASHING AT MEALTIME AND END OF SHIFT IS
ADEQUATE. GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL
BE REMOVED FROM SKIN

AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING
OR SMOKING.

Supplemental Safety and Health

KEY1:V5. THIS ENTRY, MFN 2, DESCRIBES PART TWO OF A THREE PART KIT. SEE
THIS SAME NSN, CAGE 86175, MFN 1 AND MF 3, FOR PART 1 AND PART 3
DATA.

===== Physical/Chemical Properties =====

HCC:F2

Vapor Pres: