View NSN Online: https://aerobasegroup.com/nsn/8040-01-181-2355

LORD CORP -- ACCELERATOR 4 (RD2132-17) -- 8040-01-181-2355

Product ID:ACCELERATOR 4 (RD2132-17)

MSDS Date:01/06/1997

FSC:8040

NIIN:01-181-2355

Status Code:A

MSDS Number: CKHXH
=== Responsible Party ===
Company Name:LORD CORP

Address:2000 WEST GRANDVIEW BLVD

City:ERIE State:PA ZIP:16514 Country:US

Info Phone Num:814-868-3611

Emergency Phone Num:814-763-2345

CAGE: 30676

=== Contractor Identification ===

Company Name: LORD CORPORATION, CHEMICAL PRODUCTS DIVISION

Address:2000 WEST GRANDVIEW BLVD

Box:City:ERIE State:PA

ZIP:16514-0038 Country:US

Phone:814-868-3611

CAGE:30676

======= Composition/Information on Ingredients ========

Ingred Name:BENZOYL PEROXIDE

CAS:94-36-0

Fraction by Wt: 10% OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3

Ingred Name: METHYL ISOBUTYL KETONE

CAS:108-10-1

Fraction by Wt: 10% OSHA PEL:100 PPM ACGIH TLV:50 PPM ACGIH STEL:75 PPM

ΕP

A Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL METHACRYLATE

CAS:80-62-6

RTECS #:OZ5075000 Fraction by Wt: 2%

OSHA PEL:410 MG/M3;100 PPM ACGIH TLV:410 MG/M3;100 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: METHYLENE CHLORIDE

CAS:75-09-2

Fraction by Wt: 70% OSHA PEL:1000 PPM ACGIH TLV:50 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TRICHLOROETHYLENE

CAS:79-01-6

RTECS #:KX4550000 Fraction by Wt: 15% OSHA PEL:100 PPM OSHA STEL:200 PPM ACGIH TLV:50 PPM

ACGIH S

TEL:100 PPM

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

========= Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:MAY CAUSE SKIN AND EYE IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION. MAY CAUSE RESPIRATORY TRACT IRRITATION.

Effects of Overexposure:EYE CONTACT: MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN SENSITIZATION. MAY CAUSE DERMATITIS. EFFECTS OF OVEREXPOSURE INHALATION: MAY

CAUSE RESPIRATORY TRACT IRRITATION.

EFFECTS OF OVEREXPOSURE IN GESTION: HARMFUL IF SWALLOWED.

INGESTION IS NOT AN EXPOOTED ROUTE OF ENTRY IN INDUSTRIAL OR

COMMERCIAL USES. CHRONIC SKIN CONTACT MAY CAUSE DERMATITIS.

First Aid:EYE CONTACT: FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN WHILE FLUSHING. GET PROMPT MEDICAL ATTENTION. SKIN CONTACT: FLUSH CONTAMINATED

SKIN WIT H LARGE AMOUNTS OF WATER WHILE REMOVING CONTAMINATED CLOTHING. WASH AFFECTED SKIN AREAS WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INHALATION: MOVE PERSON TO FRESH AIR. RESTOR E AND SUPPORT CONTINUED BREATHING. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. \*

========== Fire Fighting Measures ===========================

Flash Point Method:SCC Flash Point:>93.3C, 200.F

93C

Lower Limits: 1.4

Upp

er Limits:44.8

Extinguishing Media: CO2 DRY CHEMICAL FOAM WATER FOG


Fire Fighting Procedures:WEAR FULL FIREFIGHTING PROTECTIVE CLOTHING, INCLUDING SELF-COMTAINED BREATHING APPARATUS (SCBA). IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. DURING A FIRE, IRRITATING AND/OR TOXIC GASES AND PARTIC ULATE MAY BE GENERATED BY THORMAL DECOMPOSITION OR COMBUSTION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS LIGHTLY CLOSED. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. USE WATER

SPRAY TO KEEP FIRE EXPOSED CONTAINERS COOL.

======== Accidental Release Measures ===========

Spill Release Procedures: AVOID BREATHING VAPORS. NOTIFY APPROPRIATE AUTHORITIES IF NECESSARY. AVOID CONTACT. USE APPROPRIATE RESPIRATORY PROTECTION FOR LARGE SPILLS OR SPILLS IN CONFINED AREA. KEEP NON-ESSENTIAL PERSONNEL AWAY FROM SPILL AREA. SCOOP SPILLED MATERIAL INTO AN APPROPRIATE CONTAINER FOR PROPER DISPOSAL. (IF NECESSARY, USE INERT A



========= Physical/Chemical Properties ===========

Boiling Pt:>40.C, 104.F B.P. Text:104-241F Vapor Density:HEAVIER TH Spec Gravity:1.25 VOC Pounds/Gallon:781 Evaporation Rate & Deference:SLOWER THAN Solubility in Water:INSOLUBLE Appearance and Odor:MILKY LIQUID/SOLVENT ODOR. Percent Volatiles by Volume:88.9
=========== Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES ALUMINUM, ZINC, CAUSTICS, HALOGENS. STRON OXIDIZERS ACIDS, BASES. Stability Condition to Avoid:ALUMINUM OR GALVANIZED PARTS IN A CLOSED SYSTEM. DRIED MATERIAL IS FLAMMABLE, SENSITIVE TO SHOCK AND HEAT. DIRECT SUNLIGHT, SHOCK, AND TEMPERATURES IN EXCESS OF 90'F Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES.
========= Toxicological Information ===========
Toxicological Information:NO PRODUCT TOXICOLOGICAL INFORMATION IS AVAILABLE.
======= Disposal Considerations ==========
Waste Disposal Methods:DISPOSAL SHOULD BE DONE IN ACC ORDANCE WITH
FEDERAL (40CFR PART 261), STATE AND LOCAL ENVIROMENTAL CONTROL REGULATIONS. IF WASTE IS DETERMINED TO BE HAZARDOUS, USE LICENSED HAZARDOUS WASTE TRANSPORTOR AND DISPOSAL FACILITY.
======== MSDS Transport Information ==========
Transport Information:DOT PROPER SHIPPING NAME: NOT REGULATED DOT HAZARD CLASS: NONE DOT UN/NA NUMBER: NONE EMERGENCY RESPONSE RESPONSE GUIDE NUMBER: NONE PACKING GROUP: NONE
======================================

SARA Title III Information:OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.12) THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF T HE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372: 1) METHYLENE CHLORIDE 2) TRICHLOROETHYLENE 3) METHYL ISOBUTYL KETONE 4) BENZOYL PEROXIDE 5) METHYL METHACRYLATE INV ENTORY STATUS:

THE

CHEMICAL SUBSTANCES IN THIS PRODUCT ARE ON THE TSCA SECTION8 INVENTORY.

State Regulatory Information:U.S. FEDERAL REGULATIONS: AS FOLLOWS - OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) INTERNATIONAL REGULATIONS: AS FOLLOWS - CANADIAN WHMIS: THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR USE OF THE 16 HEADINGS. CANADIAN WHMIS CLASS: NO INFORMATION AVAILABLE.

\_\_\_\_\_

== Other Information ===========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.