View NSN Online: https://aerobasegroup.com/nsn/8010-00-615-2027

Product ID:KRYLON HIGH HEAT RESISTANT PAINTS, 1402 HI-HEAT ALUMINUM MSDS Date:08/17/1998 FSC:8010 NIIN:00-615-2027 Status Code:A **MSDS Number: CKJRR** === Responsible Party === Company Name: SHERWIN-WILLIAMS CO, KRYLON/SPRAYON INDUS **TRIAL PRODUCTS** Address:31500 SOLON ROAD City:SOLON State:OH ZIP:44139 Country:US Info Phone Num:800-777-2956 Emergency Phone Num:216-566-2956 Resp. Party Other MSDS Num.:HHR/KRI CAGE:09800 === Contractor Identification === **Company Name: BORDEN CHEMICAL CO** Address:180 E BROAD ST Box:City:COLUMBUS State:OH ZIP:43215-3705 Country:US Phone:614-225-6124 CAGE:86142 **Company Name: BORDEN INC** Address:180 E BROAD ST Box:208 City:COLUMBUS State:OH ZIP:43215-3705 Country:US Phone:614-225-6124 CAGE:07982 Compa

ny Name: KRYLON PRODUCTS Address:31500 SOLON ROAD Box:City:SOLON State:OH ZIP:44139 Country:US Phone:800-832-2541/216-566-2917 CAGE:87187 Company Name: KRYLON PRODUCTS Address:180 EAST BROAD ST Box:City:COLUMBUS State:OH ZIP:43215 Country:US Phone:614-431-6600:800-848-9400 **CAGE: IO479** Company Name: SHERWIN-WILLIAMS CO THE Address:101 PROSPECT AVE NW Box:City:CLEVELAND State:OH ZIP:44115-1042 Country:US Phone:800-251-2486/216-566-2242 CAGE:54636 Company Name: SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC. Address:26300 FARGO AVENUE Box:City:BEDFORD HEIGHTS State:OH ZIP:44146 Country:US Phone:216-292-7400 OR 216-595-8634 CAGE:09800 Ingred Name: PROPANE. (VAPOR PRESSURE 760.0 MM HG) CAS:74-98-6 RTECS #:TX2275000 = Wt:18. OSHA PEL:1000 PPM Ingred Name: MINERAL SPIRITS. (VAPOR PRESSURE 2.0 MM HG) CAS:64742-88-7 = Wt:1. **OSHA PEL:100 PPM** ACGIH TLV:100 PPM Ingred Name: ETHYLBENZENE. (VAPOR PRESSURE 7.1 MM HG) CAS:100-41-4 RTECS #: DA07

00000 = Wt:2. OSHA PEL:100 PPM **OSHA STEL:125 PPM** ACGIH TLV:100 PPM ACGIH STEL:125 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:XYLENE. (VAPOR PRESSURE 5.9 MM HG) CAS:1330-20-7 RTECS #:ZE2100000 = Wt:12. OSHA PEL:100 PPM **OSHA STEL:150 PPM** ACGIH TLV:100 PPM ACGIH STEL:150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: ACETONE. (VAPOR PRESSURE 180.0 MM HG) CAS:67-64-1 RTECS #:AL3150000 = Wt:57. **OSHA PEL:750 PPM OSHA STEL:1000 PPM** ACGIH TLV:750 PPM ACGIH STEL:1000 PPM EPA R pt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TO MINIMIZE EXPOSURE, FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT. ACUTE: EFFECTS OF OVEREXPOSURE: IRRITATION OF EYES, SKIN AND RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREM

- E OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH. SIGNS AND SYMPTOMS OF OVEREXPOSURE: HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF COORDINATION ARE INDICATI ONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE. (EFFECTS OF OVEREXPOSURE)
- Effects of Overexposure:HEALTH HAZARDS: CHRONIC: PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINA
- RY, BLOOD-FORMING, CARDIOVASCULAR, AND REPRODUCTIVE SYSTEMS. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

First Aid:INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMI

NATED CLOTHING AND LAUNDER

BEFORE REUSE. E YES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: SEEK MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point: