

VARFLEX CORPORATION -- VARGLAS ACRYLIC A-397 & 343 SLEEVING -- 5970-01-315-7864
===== Product Identification =====

Product ID:VARGLAS ACRYLIC A-397 & 343 SLEEVING
MSDS Date:07/01/1997
FSC:5970
NIIN:01-315-7864
Status Code:A
MSDS Number: CKLMN
=== Responsible Party ===
Company Name:VARFLEX CORPORATION
Address:512 WEST COURT STREET
City:ROME
State:NY
ZIP:13440
Country:US
Info Phone Num:315-336-4400

Emergency Phone Num:315-336-4400
CAGE:79074
=== Contractor Identification ===
Company Name:VARFLEX CORPORATION
Address:512 WEST COURT STREET
Box:City:ROME
State:NY
ZIP:13440
Country:US
Phone:315-336-4400
CAGE:79074

===== Composition/Information on Ingredients =====

Ingred Name:FIBOROUS GLASS

Ingred Name:CH2 CH00C2H5 - POLYACRYLATE

===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE: SKIN: TRANSIENT MECHANICAL
I

IRRITATION. EYE: DIRECT CONTACT WILL CAUSE MECHANICAL IRRITATION.

INGESTION: UNLIKELY TO OCCUR. CHRONIC: NONE.

Effects of Overexposure:OBSERVE INDIVIDUAL, IF SYMPTOMS DEVELOP,
CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp Text:NONE P

Extinguishing Media:WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Neutralizing Agent:NONE PROVIDED BY MFR.

=====
===== Handling and Storage =====

Handling and Storage Precautions:IF IN CONTACT WITH SENSITIVE SKIN, USE
GLOVES. FOR PROLONGED PERIODS, STORE IN ABSENCE OF DIRECT SUNLIGHT.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED

Ventilation:LOCAL EXHAUST, MECHANICAL (GENERAL)

Protective Gloves:USE WITH SENSITIVE SKIN

Eye P

Protection:NOT REQUIRED

Other Protective Equipment:NOT REQUIRED

Work Hygienic Practices:NOT REQUIRED BY DOT - WASH AND SHOWER NORMALLY
AT END OF WORK DAY.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

Vapor Density:NOT APPLIC

Spec Gravity:2.54 (H2O=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CYLINDRICAL FIBERGLASS BRAID, ACRYLIC COATED WITH
FAINT ODOR

=====
===== Stability and Reactivity Data =====

==

Stability Indicator/Materials to Avoid: YES
NONE

Hazardous Decomposition Products: SIZINGS OR BINDERS MAY DECOMPOSE IN A
FIRE TO CO, CO2 AND OTHER HYDROCARBONS.

Conditions to Avoid Polymerization: WILL NOT OCCUR

===== Toxicological Information =====

Toxicological Information: OSHA HAS NOT ESTABLISHED A SPECIFIC PEL FOR
FIBROUS GLASS. IT IS CONSIDERED TO BE A PARTICULATE NOT OTHERWISE
REGULATED (PNOR) AND IS COVERED UNDER THE OSHA NUISANCE DUST PELS

OF 5 MG/M3 FOR THE RESPIRABLE DUST FRACTION AND 15 MG/M3 FOR THE
TOTAL DUST FRACTION FOR AN 8 HR. TWA.

===== Disposal Considerations =====

Waste Disposal Methods: THE PRIMARY METHOD OF DISPOSAL IS IN A MUNICIPAL
OR INDUSTRIAL LANDFILL. CHECK LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of
America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.