

CLIFTON ADHESIVE INC -- FA 1053 MMM-A-1617, TYPE 1 -- 8040-00-262-9028

=====
Product Identification
=====

Product ID:FA 1053 MMM-A-1617, TYPE 1

MSDS Date:02/06/1995

FSC:8040

NIIN:00-262-9028

Status Code:A

MSDS Number: CKLXS

=== Responsible Party ===

Company Name:CLIFTON ADHESIVE INC

Address:BURGESS PL

City:WAYNE

State:NJ

ZIP:07470

Country:US

Info Phone Num:201-694-0845

Emergency Phone Num:201-694-0845

Chemtrec Ind/Phone:(800)424-9300

CAGE:79833

=== Contractor Identification ===

Company Name:CLIFTON ADHESIVE INC

Address:BURGESS PL

Box:City:WAYNE

State:NJ

ZIP:07470

Country:US

Phone:201-694-0845; 973-694-0845

CAGE:79833

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 60%

OSHA PEL:50

ACGIH TLV:50

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:STYRENE BUTADIENE RUBBER (NO OTHER INFO GIVEN)

CAS:9003-55-8

RTECS #:WL6478000

Ingred Name:NATURAL RUBBER (NO OTHER INFO GIVEN)

CAS:9006-04-6

OSHA PEL:(NO

Ingred Name:TERPINE PHENOL RESIN (TSR#: 1397250002-5053P) (NO OTHER
INFO GIVEN)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE: NAUSEA AND/OR NARCOSIS. TARGET
ORGANS: HEXANE MAY CAUSE CNS EFFECTS OR DAMGE PERIPHERAL NERVE
TISSUE.

Explanation of Carcinogenicity:CARCINOGEN
ICITY: NO

Effects of Overexposure:IRRITATION TO EYES AND MUCOUS MEMBRANES. CAN
ALSO CAUSE SKIN DRYNESS. LIQUID INGESTION MAY RESULT IN VOMITING.
NUMBNESS, TINGLING AND WEAKNESS OF ARMS AND LEGS.

Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS.

===== First Aid Measures =====

First Aid:IN EMERGENCY SITUATIONS NOTIFY PHYSICIAN IMMEDIATELY. SKIN:
WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION. EYES: FLUSH EYES
ABUNDANTLY WITH CLEAN

WATER AND REFER TO PHYSICIAN. INGESTION: DO

NOT IND UCE VOMITING. REFER TO PHYSICIAN. EXCESSIVE INHALATION:

REMOVE PATIENT TO FRESH AIR OR GIVE OXYGEN. USE CPR IF PATIENT IS
NOT BREATHING. REFER TO PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-31.7C, -25.F

Autoignition Temp:=-265.6C, 510.F

Lower Limits:1.0

Upper Limits:7.5

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NIOSH/MSHA - APPROVED

SELF-CONTAINED BREATHING

APPARATUS SHOULD BE WORN. USE WATER SPRAY TO COOL FIRE EXPOSED STRUCTURES AND DISPERSE VAPOR CLOUD IF FIRE IS NOT PRESENT.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL IN SAND, EARTH, VERMICULITE, OIL-DRI, OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER AND COVER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN APPROVED SOLVENT STORAGE AREA. KEEP TIGHTLY CLOSED. KEEP AWAY FROM HEAT, OPEN FLAMES, SPARKS, HOT SURFACES AND OXIDIZING AGENTS.

Other Precautions:NA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH-APPROVED ATMOSPHERE SUPPLYING OR AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS AS REQUIRED TO MAINTAIN

EXPOSURE LEVELS BELOW RECOMMENDED LIMITS.

Ventilation:AS SPECIFIED, LOCAL EXHAUST: REMOVE VAPORS DURING PROCESSING. MECHANICAL EXHAUST: EXPLOSION-PROOF EQUIPMENT. SPECIAL: REDUCE VAPOR CONCENTRATIONS BELOW LIMITS.

Protective Gloves:PVA GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices:KEEP AREA CLEAN. CLEAN UP SPILLS IMMEDIATELY. PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=65.C, 149.F

Vapor Pres:125 MMHG @ 20C OR 68F

Vapor Density:3.0

Spec Gravity:0.816

VOC Grams/Liter:3.9

Appearance and Odor:AMBER. MILD HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NA

Stability Condition to Avoid:AVOID HEAT, OPEN FLAMES, SPARKS, HOT SURFACES, AND OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES

OF CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,
AND LOCAL CHEMICAL AND SOLVENT WASTE DISPOSAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:ADHESIVES, UN1133

===== Regulatory Information =====

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.