View NSN Online: https://aerobasegroup.com/nsn/8010-01-350-4741

MOBILE PAINT MANUFACTURING CO INC -- MILP24441/SB TOPCOAT-HAZE GRAY

8010-01-350-4741

Product ID:MILP24441/SB TOPCOAT-HAZE GRAY

MSDS Date:02/04/1992

FSC:8010

NIIN:01-350-4741 Status Code:A

MSDS Number: CKMCJ === Responsible Party ===

Company Name: MOBILE PAINT MANUFACTURING CO INC

Box:717

City:THEODORE

State:AL ZIP:36582 Country:US

Info Phone Num:334-443-6110

Ε

mergency Phone Num:18002553924 Preparer's Name:JULIE HOAGLAND

CAGE:88633

=== Contractor Identification ===

Company Name: MOBILE PAINT MANUFACTURING CO INC

Box:717

City:THEODORE

State:AL ZIP:36582 Country:US

Phone:334-443-6110

CAGE:88633

======= Composition/Information on Ingredients ========

Ingred Name: N-BUTYL ALCOHOL

CAS:71-36-3

RTECS #:EO1400000

= Wt:34.

ACGIH TLV:50PPM; 150 MG/M3

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR22 75000 = Wt:5.

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:BUFF TITANIUM

CAS:1317-80-2

RTECS #:VM2940000

> Wt:5.

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: HYDROUS MAGNESIUM SILICATE

CAS:14807-96-6

RTECS #:WW2710000

= Wt:35.

OSHA PEL:20 MPPCF ACGIH TLV:2 MG/M3

========== Hazards Identification ===========================

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION:ANESTHETIC, INHALATION CAN CAUSE IRRIT. OF THE RESPI

RATORY TRACT, ACUTE NERVOUS SYSTEM

DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSIOUSNESS, COMA AND ASPHYX IATION. SKIN: MODERATE IRRIT., DEFATTING, DERMATITIS. MAY BE SENSITIZER IN SOME. EYES: SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION. MAY BE A SENSITIZER IN SOME. LIQUID CAN BE ABSORBED THROUGH THE SKIN RESULTING IN SYMPTOMS SIMILAR TO THE INHALATION EFFECTS. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING ANS DIARRHEA. ASPIRATI

ON INTO THE LUNGS

DURING INGESTION-VOMITING MAY CAUSE MILD-SEVERE P ULMONARY INJURY AND POSSIABILY DEATH.

Medical Cond Aggravated by Exposure: EXPOSURE TO PETROLEUM SOLVENTS MAY AGGREVATE PREEXISTING DERMITITUS.

First Aid:INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF BREATHING IS DIFFICULT. RESTORE BREATHING IF NECESSARY. TREAT SYMPTOMATICALLY. CONSULT A PHYSICIAN. SKIN: WASH EFFECTED AREAS WITH

SOAP AND WATER. REMOVE AND LAUNDER CONTAMINATED CLOTHING. CONSULT A PHYSICIAN IF NEEDED. EYES: FLUSH IMMEDIATELY WITH LARGE AMMOUNTS OF WATER FOR AT LEAST 15 MINITUES. TAKE TO A PHYCIAN FOR MEDICAL TREATMENT. INGEST ION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. GET MEDICAL HELP IMMEDIATELY.

========== Fire Fighting Measures ================

Flash Point:=37.2C, 99.F

99-103 F

Lower Limits: 1.4

Extinguishing Media: FOAM, ALCOHOL FOAM, CO2,

DRY CHEMICAL

Fire Fighting Procedures: DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION. KEEP CONTAINERS TIGHTLY CLOSED. ISOLAT E FROM HEAT, SPARKS AND OPEN FLAME. WATER MAY BE USED TO COOL CLOSED CONTAINERS RO PREVENT PRESSURE BUILD-UP.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRE

SPECIAL PRECAUTIONS. FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE US ED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED FOG NOZZLES ARE PREFERABLE.

=======================================	Accidental	Release	Measures	============
---	------------	---------	----------	--------------

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT SURFACES, ASN ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING CAPORS. VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=======================================	Hand	lling and	Storage	
	ilaila	iiii ig ai ia	Ciorago	

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANITIES ONLY IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106.KEEP CLOSURES TIGHT AND CONT. UPRIGHT-PREVENT LEAKAGE. DO NOT STORE/USE NEAR HEAT, SPARKS,FLAME.NEV ER USE PRESSURE TO EMPTY.DRUMS MUST NOT BE WASHED OUT OR USED FOR OTHER PURPOSES.GROUND DRUMS.

Other Precautions: DO NOT TRANSFER THIS PRODUCT TO UNLABLED CONTAINERS.

DRUM MUST BE WASHED OUT OR USED FOR OTHER PURPOSE. DO NOT HANDLE UNTIL THE MANUFACTURES SAFTEY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. KEEP OUT OF REACH OF CHILDREN. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: IN OUTDOOR OR OPEN AREAS USLE NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIR BORNE PARTICLES. IN RESTRICTED VENTILATION AREAS USE NIOSH/MSHA APPROVED MECHANICAL/CHEMICAL FILTERS DESIGNED TO REM OVE A COMBUSTION OF PARTICULATE AND GAS VAPOR. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIR LINE KTYPE RESPIORATORS OR HOODS. Ventilation: ACCORANCE WITH REGULATIONS Protective Gloves:RECOMMENDED Eye Protection: SAFTEY EYE WEAR INCLUDING SPLASH GUARDS OR SIDE SHIELDS RECOMMENDED Other Protective Equipment: USE PROTECTIVE OUTER-WEAR AND PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING Work Hygienic Practices: WASH SKIN THROUGHLY BEFORE BREAKS AND MEALS AND AT END OF WORK **PERIOD** Supplemental Safety and Health ========= Physical/Chemical Properties =========== Spec Gravity:(H2O=1) 1.3

Boiling Pt:=115.6C, 240.F B.P. Text:240F DEG F Vapor Density:+ AIR

VOC Pounds/Gallon:441 VOC Grams/Liter:3.68

Evaporation Rate & Evaporation R

Solubility in Water: NEGLIFIBLE

Appearance and Odor:TYPICAL PAINT SOLVENT ODOR

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES **OXIDIZING MAT**

EIALS. Stability Condition to Avoid:HIGH TEMPATURES. Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION AS IN WELDING.
======= Disposal Considerations ==========
Waste Disposal Methods:DISPOSE OF IN ACCORDANCE KWITH LOCAL, STATE AND FEDERQAL REGULATIONS. INCINERATE IN APPROVE FACILITY. DO NOT

=========== Other Information =====================

Disclaimer (provided with t

his information by the compiling agencies):

INCINERATE CLOSED CONTAINERS.

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.