

CAAP CO INC -- CAAPCOAT FP-050 COLOR MATCHED LUSTERLESSPOLYURITHANE TOPCOAT --  
8010-01-235-0828

=====  
Product Identification  
=====

Product ID:CAAPCOAT FP-050 COLOR MATCHED LUSTERLESSPOLYURITHANE TOPCOAT

MSDS Date:12/01/1996

FSC:8010

NIIN:01-235-0828

Status Code:A

MSDS Number: CKNMX

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

City:MILFORD

State:CT

ZIP:06460

Countr

y:US

Info Phone Num:203-877-0375

Emergency Phone Num:7035273887

Chemtrec Ind/Phone:(800)424-9300

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ISO-BUTYL KETONE MIBK

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 17%

Other REC Limits:75PPPM-STEL

OSHA PEL:50PPM TWA

ACGIH TLV:50PPM TW

A  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 51%  
Other REC Limits:150PPM-STEL  
OSHA PEL:100PPM  
ACGIH TLV:100PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:RESUEUAL METHYLENEBIS(4-CYCLOHEXYL ISOCYANATE)  
CAS:5124-30-1  
RTECS #:HQ9250000  
Fraction by Wt: 116.1C, 241.F  
B.P. Text:241-281F \*\*  
Melt/Freeze Pt:M.P/F.P Text:NA  
Vapor Pres:8MMHG  
Vapor Density:3.5AIR=1  
Spec Gravity:1.996 H2O=1(COATING)H2O=1  
VOC Pounds/Gallon:652  
VOC  
Grams/Liter:5.43  
Evaporation Rate & Reference:0.85 BUTYL ACETATE =1  
Solubility in Water:INSOLLUABLE (COATING)  
Appearance and Odor:LIGHT TO DARK GRAY OR GREEN LIQUID, AROMATIC  
SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
THE PRODUCT IS INCOMPATIVLE WITH STRON OXIDIZING AGENTS.  
Stability Condition to Avoid:SHOULD BE KEPT AWAY FROM ALL IGNITION  
SOURCES, HOT SURFACES, AND TEMPERATURES ABOVE 100 DEG. F.  
Haza  
rdous Decomposition Products:CARBON MONOXIDE CARBON DIOXIDE OXIDES  
OF NITROGEN AS WELL AS TRACES OF HCN MAY BE RELEASED DURING  
COMBUSTION.

===== Toxicological Information =====

Toxicological Information:\* OVERSHOES IS REQUIRED. WEAR SOLVENT  
RESISTANT APRON AND BOOTS FOR SPILLS. AN EYE WASH AND SAFETY SHOWR  
SHOULD BE NEARBY AND READY FOR USE.

===== Disposal Considerations =====

Waste Disposal Methods:INCNRATION IN A

PROPERLY DESIGNED AND LICENCED

INCINRATR IS PREFERRED; THIS IS RCRA HAZARDOUS IGNITABLE WASTE. REGULATIONS MAY VARY FROM STATE TO STATE; DISPOSE OF ACCOR. TO STATE AND FEDERAL RGLATIONS. WHEN THE POLYURITHANE AND CURING AGENT AND ARE MIXED AND THE SOLVENT IS ALLOWED TO EVAPORATE, THE SO LID END POODUCT IS A NON=HAZARDOUS LANDFILL ITEM.

===== MSDS Transport Information =====

Transport Information:SHIPPING NAME PAINT RELATED MATERIAL. DOT CLASSIFICATION 3 (FLAMMABLE LIQUID)

===== Regulatory Information =====

SARA Title III Information:MIBK XYLENE CHROMIUM III OXIDE GREEN, COPPER PHTHALOCYANINE BLUE.

Federal Regulatory Information:ALL INFREDIENTS ARE TSCA LISTED.

State Regulatory Information:THE FOLLOWING CHEMICALS ARE LISTED BY INDIVIDUAL STATES. FOR MORE COMPLETE INFORMATION, CONTACT THE APPROPRIATE AGENCY IN YOUR STATE. OTHER PRODUCT SPECIFIC HEALTH AND SAFETY DATA IN OTHER SECTIO

NS IN THE MSDS MAY ALSO BE ALPPLICALLE

FOR STATE REQUIREMENTS. FOR DETAILS ON YOUR REGULATORY REQUIREMENTS, YOU SHOULD CONTACT THE APPROPRIATE AGENCY IN YOUR STATE. MIBK: =MA, PA RIGHT-TO-KNOW XYLENE=MA, PA, RIGHT-TO-KNOW. METHALENE BIS(4CYCLOHEXYLISOCYANATE)=MA, NJ, PA, RIGHT-TO-KNOW.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.