

MET-L-CHEK COMPANY -- PENETRANT & LUBE -- 6850-00-826-0981

===== Product Identification =====

Product ID: PENETRANT & LUBE

MSDS Date: 01/01/1997

FSC: 6850

NIIN: 00-826-0981

Status Code: A

MSDS Number: CKPBZ

=== Responsible Party ===

Company Name: MET-L-CHEK COMPANY

Address: 1639 EUCLID ST

City: SANTA MONICA

State: CA

ZIP: 90404-3770

Country: US

Info Phone Num: 310-450-1111

Emergency Phone Num: (800)424-9300

C

hemtrec Ind/Phone: (800)424-9300

CAGE: 98733

=== Contractor Identification ===

Company Name: MET-L-CHEK COMPANY

Address: 1639 EUCLID ST

Box: 00000

City: SANTA MONICA

State: CA

ZIP: 90404

Country: US

Phone: 310-450-1111/FAX 310452-4046

CAGE: 98733

===== Composition/Information on Ingredients =====

Ingred Name: PETROLEUM HYDROCARBON

CAS: 64742-46-7

RTECS #: JN9379645

Minumum % Wt: 1.

Maxumum % Wt: 100.

OSHA PEL: 5 MG/M3

ACGIH TLV: 5 MG/M3

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYE CONTACT-PRESUMED NON-IRRITATING.
SKIN CONTACT-SLIGHTY IRRITATING. INAHALATION-VAPORS OR OIL MIST
MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT.
INGESTION-MAY RESULT IN VOMITING. ASPIRATIO N MUST BE AVOIDED.
Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:EYE CONTACT-FLUSH WITH WATER. SKIN CONTACT-FL
USH WATER, WASH
SOAP AND WATER. INHALATION-REMOVE TO FRESH AIR, PROVIDE OXYGEN IF
BREATHING IS DIFFICULT. INGESTION-DO NOT INDUCE VOMITING. GET
MEDICAL A TTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:=93.3C, 200.F
200F
Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT
USE DIRECTSTREAM WATER.
Fire Fighting Procedures:MATERIAL WILL NOT BURN UNLESS PREHEATED. DO
NOT ENTER CONFINED FIRE-S
PACE WITHOUT FULL BUNKER GEAR, INCLUDING A
POSITVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH AN ABSORBENT SUCH AS CLAY, SAND,
OR OTHER SUITABLE MATERIAL. DISPOSE OF IN ACCORDANCE WITH FEDERAL
AND STATE REGULATIONS FOR OIL RESIDUE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, OPEN F
LAMES AND
OXIDIZING MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE EXCEEDS TLV, USE NIOSH APPROVED
RESPIRATOR TO TO PREVENT OVEREXPOSURE.
Ventilation:LOCAL EXHAUST: TO MAINTAIN TLV. MECHANICAL: TO MAINTAIN
TLV.
Protective Gloves:CHEMICAL RESISTANT TO MINIMIZE SKIN CONTACT.
Eye Protection:NO SPECIAL PROTECTION REQUIRED.
Other Protective Equipment:AS REQUIRED TO MINIMIZE SKIN CONTACT.
Work Hygienic Practices:MINIMI

ZE SKIN CONTACT. WASH WITH SOAP AND
WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:>204.4C, 400.F
B.P. Text:400F
Melt/Freeze Pt:=23.9C, 75.F
M.P/F.P Text:75F
Spec Gravity:ABOUT 0.88
Solubility in Water:INSOLUBLE
Appearance and Odor:DEEP RED LIQUID, HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avo
id:YES
OXIDIZING MATERIALS.
Stability Condition to Avoid:HEAT, OPEN FLAMES, AND OXIDIZING
MATERIALS.
Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND OTHER
UNIDENTIFIED ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN APPROPRIATE DISPOSAL FACILTY IN
COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by
elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.