

CAAP CO INC -- CAAPCOAT AS-P108 BLACK ANTISTATIC POLYURTHANE RAIN EROSION C --
8010-00-459-1756

=====
Product Identification
=====

Product ID:CAAPCOAT AS-P108 BLACK ANTISTATIC POLYURTHANE RAIN EROSION C

MSDS Date:11/01/1997

FSC:8010

NIIN:00-459-1756

Status Code:A

MSDS Number: CKPFF

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

City:MILFORD

State:CT

ZIP:06460

Countr

y:US

Info Phone Num:203-877-0375

Emergency Phone Num:703-527-3887

Chemtre Ind/Phone:(800)424-9300

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 44.15%

Other REC Limits:150 PPM-STEL

OSHA PEL:100PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:10

00 LBS

Ingred Name:METHYL ISOBUTYL KETONE

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 16%

Other REC Limits:75 PPM-STEL

OSHA PEL:50 PPM TWA

ACGIH TLV:50 PPM TWA

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:RESIDUAL METHYLENE BIS (4-CYCLOHEXYLISOCYANATE)

CAS:5124-30-1

RTECS #:HQ9250000

Fraction by Wt: 116.1C, 241.F

B.P. Text:241-281F (116-138C)

Vapor Pres:(MM HG) : 8

Vapor Density:AIR=1 3.6

Spec Gravity:0.96 (COATING)

VOC Pounds/Gallon:519

VOC Grams/Liter:4.33

Evaporation

Rate & Reference:.85

Solubility in Water:INSOLUABLE COAT

Appearance and Odor:BLACK AROMATIC LIQUID (COATING SOLUTION)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

THE PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:THE PRODUCT IS STABLE BUT SHOULD BE KEPT

AWAY FROM ALL IGNITION SOURCES, HOT SURFACES, AND TEMPERATURE ABOVE
100 F (38 C)

Hazardous Decomposition Products:CARBON MONOXI

DE, CARBON DIOXIDE,

OXIDES OF NITROGEN, AS WELL AS TRACES OF HCN MAY BE RELEASED DURING
COMBUSTION.

===== Toxicological Information =====

Toxicological Information:VENTILATION SHOULD BE IN ACCORDACNE WITH

ACGIH GUIDELINES AS CONTAINED IN ITS INDUSTRIAL VENTILATION
PUBICATION.

===== Ecological Information =====

Ecological:*SWEEP AND WET MOP THE AFFECTED AREA WITH SOAP AND WATER.

VENTILATED THE AREA AS WELL A

S POSSIBLE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION IN AN APPROPRIATELY DESIGNED AND LICENSED INCUNERATOR IS PROFERRED THIS IS A RCRA HAZARDOUS IGNITABLE WASTE. REGULATIONS MAY VARY FROM STATE TO STATE. DISPOSE OF ACCORDING TO STATE, LOC AL, AND FEDERAL REGULATIONS WHEN THE FP-200, CURING AGENT AND ACCELERATOR ARE MIXED TOGETHER AND THE SOLVENT IS ALLOWED TO EVAPORATE,**

===== MSDS Transport Information =====

Transport Information:THE USER MUST BE FULLY PROTECTED FROM EXPOSURE TO THE MATERIAL CURING MIXING AND SPRAY APPLICATION. IF EXPOSURE MIGHT OCCUR A FULL PERMEATION RESISTANT PROTECTIVE SUIT INCLUDING HEAD COVERING, FACE S HIELD, GLOVES, AND OVERSHORES IS REQUIRED.

===== Regulatory Information =====

State Regulatory Information:MIBK, MEK, XYLENE: MA, PA RIGHT-TO-KNOW. METHYLENE BIS (4-CYCLOHEXYLISOCYANTE) : MA, NJ, PA RIGHT-TO-KNOW.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.