

SAFETY-KLEEN CORP -- AMERICA'S CHOICE DIESEL MOTOR OIL INCLUDES GRADES 10W-30;15W
-- 9150-01-438-6070

===== Product Identification =====

Product ID:AMERICA'S CHOICE DIESEL MOTOR OIL INCLUDES GRADES 10W-30;15W

MSDS Date:05/13/1998

FSC:9150

NIIN:01-438-6070

Status Code:A

MSDS Number: CKQFC

=== Responsible Party ===

Company Name:SAFETY-KLEEN CORP

Address:ONE BRINCKMAN WAY

City:ELGIN

State:IL

ZIP:60123-7857

Country:US

Info Phone Num:800-669-5740

Emergency Phone Nu

m:800-752-7869

Preparer's Name:PRODUCT MSDS COORDINATOR

CAGE:0CWB2

=== Contractor Identification ===

Company Name:SAFETY-KLEEN CORP

Address:ONE BRINCKMAN WAY

Box:City:ELGIN

State:IL

ZIP:60123-7857

Country:US

Phone:800-669-5740

CAGE:0CWB2

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OILS, PETROLEUM, HYDROTREATED SPENT

CAS:64742-58-1

Minimum % Wt:30.

Maximum % Wt:95.

OSHA PEL:5C

OSHA STEL:N.AV.

ACGIH TLV:5

ACGIH STEL:10 CD

Ingred Name:RESIDUAL OIL

S (PETROLEUM), SOLVENT-DEWAXED

CAS:64742-62-7

Minumum % Wt:0.

Maxumum % Wt:50.

OSHA PEL:5C

OSHA STEL:N.AV.

ACGIH TLV:5C

ACGIH STEL:10 CD

Ingred Name:RESIDUAL OILS (PETROLEUM), HYDROTREATED

CAS:64742-57-0

Minumum % Wt:0.

Maxumum % Wt:50.

OSHA PEL:5C

OSHA STEL:N.AV.

ACGIH TLV:5C

ACGIH STEL:10CD

Ingred Name:LUBRICATING OILS (PETROLEUM), C>25, HYDROTREATED BRIGHT
STOCK-BASED

CAS:72623-83-7

Minumum % Wt:0.

Maxumum % Wt:50.

OSHA PEL:5C

OSHA STEL:N.AV.

ACGIH TLV:5C

ACGIH STEL:10CD

Ingred Name:MI

NERAL OIL

Minumum % Wt:0.

Maxumum % Wt:50.

OSHA PEL:5C

OSHA STEL:N.AV.

ACGIH TLV:10CD

ACGIH STEL:N.AV.

Ingred Name:ALKARYL AMINE

Minumum % Wt:0.

Maxumum % Wt:2.

OSHA PEL:N.AV.

OSHA STEL:N.AV.

ACGIH TLV:N.AV.

ACGIH STEL:N.AV.

Ingred Name:BENZENAMINE, N-PHENYL-, REACTION PRODUCTS WITH
2,4,4-TRIMETHYLPENTENE

CAS:68411-46-1

Minumum % Wt:0.

Maxumum % Wt:1.5

OSHA PEL:N.AV.

OSHA STEL:N.AV.

ACGIH TLV:N.AV.

ACGIH STEL:N.AV.

Ingred Name:PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC
SA

LTS
CAS:68649-42-3
Minumum % Wt:0.
Maxumum % Wt:1.5
OSHA PEL:N.AV.
OSHA STEL:N.AV.
ACGIH TLV:N.AV.
ACGIH STEL:N.AV.

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CAUSES RESPIRATORY TRACT (NOSE,
THROAT, AND LUNGS), EYE, AND SKIN IRRITATION. PROLONGED OR
REPEATED SKIN CONTACT MAY CAUSE DRYING, CRACKING, REDNESS, ITCHING,

AND/OR SWELLING. PROLONGED OR REPEATED INHALATION OF OIL MIST MAY
CAUSE OIL PNEUMONIA, LUNG TISSUE INFLAMMATION, AND/OR FIBROUS
TISSUE FORMATION.

Explanation of Carcinogenicity:NO KNOWN CARCINOGENICITY. IARC
CLASSIFIES CHEMICALS BY THEIR CARCINOGENIC RISK, INCLUDING AGENTS
THAT ARE KNOWN, PROBABLE, OR POSSIBLE CARCINOGENS. NTP CLASSIFIES
CHEMICALS AS EITHER KNOWN CARCINOGENS, OR FOR WHICH THERE IS
LIMITED EVIDENCE OF CARCINOGENICITY IN EXPERIMENTAL ANIMALS. ACGIH

RECOGNIZES SEVERAL CATEGORIES OF CARCINOGENS.

Effects of Overexposure:INHALATION: HIGH CONCENTRATIONS OF VAPOR OR
MIST MAY IRRITATE THE RESPIRATORY TRACT (NOSE, THROAT, AND LUNGS).
EYES: DIRECT CONTACT WITH PRODUCT MAY CAUSE IRRITATION. SKIN:
DIRECT CONTACT WITH PRODUCT MAY CAUSE IRRITATION. A SINGLE,
PROLONGED EXPOSURE IS NOT LIKELY TO CAUSE THE PRODUCT TO BE
ABSORBED THROUGH THE SKIN IN HARMFUL AMOUNTS. INGESTION: MAY CAUSE
THROAT IRRITATION, NAUSEA, VOMITING, A

ND DIARRHEA. BREATHING
PRODUCT INTO THE LUNGS DURING INGESTION OR VOMITING MAY CAUSE LUNG
INJURY AND POSSIBLE DEATH.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING
RESPIRATORY TRACT (NOSE, THROAT, AND LUNGS) AND/OR SKIN DISORDERS
MAY HAVE INCREASED SUSCEPTIBILITY TO THE EFFECTS OF EXPOSURE.

=====
===== First Aid Measures =====
=====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE
ARTIFICIAL RESPIRATION. IF BRE

ATHING IS DIFFICULT, GIVE OXYGEN.

SOMEONE SHOULD STAY WITH VICTIM. EYES:FOR DIRECT CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, HOLDING EYELIDS APART, FOR 15 MINUTES. IF IRRITATION OR REDNESS FROM EXPOSURE TO VAPOR DEVELOPS, MOVE AWAY FROM EXPOSURE INTO FRESH AIR.

SKIN:REMOVE CONTAMINATED CLOTHING AND SHOES. WASH SKIN THOROUGHLY WITH SOAP AND WATER. INGESTION:DO NOT INDUCE VOMITING. IF SPONTANEOUS VOMITING OCCURS, KEEP HEAD BELOW HIPS TO AVOID B

REATHING THE PRODUCT INTO THE LUNGS. IN ALL CA SES, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:=200.C, 392.F

MINIMUM

Autoignition Temp:=398.9C, 750.F

Autoignition Temp Text:APPROX

Lower Limits:1%

Upper Limits:10%

Extinguishing Media:CARBON DIOXIDE, REGULAR FOAM, DRY CHEMICAL, WATER SPRAY, OR WATER FOG.

Fire Fighting Procedures:KEEP STORAGE CONTAINERS COOL WITH WATER SPRAY. POSITIVE-PRESSURE, SELF-CONTAINED BREATHING APPARATUS (SCBA) AND STRUCTURAL FIREFIGHTERS' PROTECTIVE CLOTHING MAY PROVIDE LIMITED PROTECTION.

Unusual Fire/Explosion Hazard:HEATED CONTAINERS MAY RUPTURE. "EMPTY" CONTAINERS MAY RETAIN RESIDUE AND CAN BE DANGEROUS. NOT SENSITIVE TO MECHANICAL IMPACT OR STATIC DISCHARGE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. DO NOT TOUCH OR WALK THROUGH SPILLED PRODUCT. STOP LEAK I F YOU CAN DO IT WITHOUT RISK. WEAR PROTECTIVE EQUIPMENT SPECIFIED. VENTILATE AREA AND AVOID BREATHING VAPOR OR MIST. CONTAIN AWAY FROM SURFACE WATERS AND SEWERS. CONTAIN AS A LIQUID FOR POSSIBLE RECOVERY OR ABSORB WITH COMPATIBLE SORBENT MATERIAL AND SHOVEL WITH A CLEAN TOOL INTO A SEALABLE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OR FLAME. USE CLEAN TOOLS. DO NOT

BREATHE VAPOR OR MIST. USE IN A WELLVENTILATED AREA. AVOID CONTACT WITH EYES, SKIN, CLOTHING, AND SHOES. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE AND DURING TRANSPORT. STORE CONTAINER IN A COOL, DRY PLACE. DO NOT PRESSURIZE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA-APPROVED RESPIRATORY PROTECTIVE EQUIPMENT WHEN CONCENTRATION OF VAPOR OR MIST EXCEEDS APPLICABLE EXPOSURE LIMITS. A SELF-CONTAINED B

REATHING APPARATUS (SCBA) AND

FULL PROTECTIVE EQUIPMENT ARE REQUIRED FOR FIRE EMERGENCIES.

SELECTION AND USE OF RESPIRATORY PROTECTIVE EQUIPMENT SHOULD BE IN ACCORDANCE IN THE USA WITH OSHA.

Protective Gloves:NEOPRENE,NITRILE,OR EQUIVALENT PROTECTIVE GLOVES;RUBBER GLOVES NOT RECOMMENDED

Eye Protection:SAFETY GLASSES;CONTACT LENS USE NOT RECOMMENDED

Other Protective Equipment:WHERE SPILLS AND SPLASHES ARE LIKELY, WEAR APPROPRIATE CHEMICAL-RESISTANT APRON OR OTHER PROTECTIVE CLOTHING.

CLEAN WATER SHOULD BE AVAILABLE IN WORK AREAS FOR FLUSHING THE EYES AND SKIN.

Work Hygienic Practices:USE GOOD HYGIENE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, OR USING TOBACCO PRODUCTS. CLEAN CONTAMINATED CLOTHING, SHOES, AND PROTECTIVE EQUIPMENT BEFORE REUSE.

Supplemental Safety and Health

LDB:LUBRICATING OILS:>15000;RESIDUAL OILS:>10000;RESIDUAL OILS(PETROLEUM):N.AV.;LUBRICATING OILS:>5000;MINERAL OIL:N.AV.;ALKARY

L AMINE:N.AV.;BENZENAMINE:7580;PHOSPHORODITHLOIC

ACID:N.AV. SEE 29 CFR 1910.1000(D)(2) AND ACGIH THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS BIOLOGICAL EXPOSURES BOOKLET

===== Physical/Chemical Properties =====

Boiling Pt.=215.6C, 420.F

Melt/Freeze Pt.:M.P/F.P Text:NOT AVAILABLE

Vapor Pres:10

Spec Gravity:0.88

VOC Pounds/Gallon:880

VOC Grams/Liter:7.3

Evaporation Rate & Reference:0.001(ETHYL ETHER=1)

Solubility in Water:INSOLUB

LE
Appearance and Odor:LIQUID, AMBER, PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID OXIDIZING AGENTS.
Stability Condition to Avoid:STABLE UNDER NORMAL TEMPERATURES AND PRESSURES. AVOID HEAT, SPARKS, OR FLAME.
Hazardous Decomposition Products:NONE UNDER NORMAL TEMPERATURES AND PRESSURES.

===== Toxicological Information =====

Toxicological Information:BASED ON BEST CURRENT INFORMATION, THERE IS NO KNOWN TERATOGENICITY ASSOCIATED WITH THIS PRODUCT. BASED ON BEST CURRENT INFORMATION, THERE IS NO KNOWN REPRODUCTIVE TOXICITY ASSOCIATED WITH THIS PRODUCT. EXPERIMENTAL EVIDENCE SUGGESTS THAT THIS PRODUCT DOES NOT CAUSE MUTAGENESIS. BASED ON BEST CURRENT INFORMATION, THERE ARE NO KNOWN TOXICOLOGICALLY SYNERGISTIC PRODUCTS ASSOCIATED WITH THIS PRODUCT.

===== Ecological Information =====

Ecological:ECOTOXICITY: NOT AVAILABLE
OCTANOL/WATER: NOT AVAILABLE
PHOTOCHEMICALLY REACTIVE AS PER 40 CFR PART 51.100(S).

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. REGULATIONS MAY ALSO APPLY TO EMPTY CONTAINERS. THE RESPONSIBILITY FOR PROPER WASTE DISPOSAL LIES WITH THE OWNER OF THE WASTE. CONTACT SAFETY-KLEEN REGARDING RECYCLING OR PROPER DISPOSAL.

=====
===== MSDS Transport Information =====

Transport Information:DOT: NOT REGULATED TDG: NOT REGULATED

===== Regulatory Information =====

SARA Title III Information:SARA SECTIONS 311 AND 312: THIS PRODUCT POSE THE FOLLOWING HEALTH HAZARDS AS DEFINED IN 40 CFR PART 370 AND IS SUBJECT TO THE REQUIREMENTS OF SECTIONS 311 AND 312 OF THE TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986.
SARA SECTION 313: CAS#

68649-42-3

Federal Regulatory Information:TSCA: ALL THE COMPONENTS OF THIS PRODUCT ARE LISTED ON, OR ARE EXEMPTED FROM THE REQUIREMENT TO BE LISTED ON, THE TSCA INVENTORY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.