CONTACT INDUSTRIES -- CONTACT SILICONE-QUICK SLIP -- 9150-01-443-9003

Product ID:CONTACT SILICONE-QUICK SLIP MSDS Date:07/10/1996 FSC:9150 NIIN:01-443-9003 Status Code:A MSDS Number: CKRZG === Responsible Party === Company Name: CONTACT INDUSTRIES Address:641DOWD AVE City:ELIZABETH State:NJ ZIP:07201-2116 Country:US Info Phone Num:908-351-5900 **Emergency Phone Num** :908-351-5900 Resp. Party Other MSDS Num.:535 Preparer's Name:LEO M. CAGE:2P016 === Contractor Identification === Company Name: CONTACT INDUSTRIES Address:641DOWD AVE Box:City:ELIZABETH State:NJ ZIP:07201-2116 Country:US Phone:908-351-5900 CAGE:2P016

Ingred Name:ISOPARAFFINIC HYDROCARBON CAS:64742-48-9 Other REC Limits:400 PPM

Ingred Name:ISOBUTANE CAS:75-28-5 RTECS #:TI4300000 Other REC Limits:800 PPM

Ingred Name:PROPANE CA S:74-98-6 RTECS #:TX2275000 Other REC Limits:1000 PPM OSHA PEL:1800 MG/M3;1000 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE IRRITANT. MAY CAUSE SKIN

IRRITATION. PROLONGED INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM
DEPRESSION.

Effects of Overexposure:EYE STINGING, TEARING, REDNESS AND SWELLING.

MAY CAUSE SKIN

REDNESS, BURNING, DRYING AND SKIN BURNS.

OVEREXPOSURE MAY CAUSE DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS AND EVEN DEATH.

Medical Cond Aggravated by Exposure:NONE KNOWN

First Aid:FLUSH EYES WITH WATER. WASH DKIN WITH SOAP AND WATER. REMOVE PATIENT TO FRESH AIR. CALL A PHYSICIAN IF NECESSARY.

Flash Point Method :TCC Flash Point:=-7.6C, 18.F Lower Limits:NA Upper Limits:NA Extinguishing Media:WATER, WATER FOG, DRY CHEMICAL, CARBON DIOXIDE. Fire Fighting Procedures:SELF-CONTAINED RESPIRAATORY PROTECTION SHOULD BE PROVIDED FOR FIREMAN FIGHTING IN BUILDINGS OR CONFINED AREAS. Unusual Fire/Explosion Hazard:AEROSOLS ARE UNDER PRESSURE. EXPOSURE IN EXCESS OF 120F MAY CAUSE BURSTING OF CAN.

Spill Release Procedures: AVOID INHALATION O

F CONCENTRATED VAPORS. ABSORB SPILLED MATERIAL WITH APPROPRIATE ABSORBENT.

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN
 FLAME OR DIRCT SUNSIHINE. DO NOT PUNCTURE OR INCINERATE CONTAINER.
 Other Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND
 INHALING VAPOR CONTENTS CAN BE HARMFUL OR FATAL.

Respiratory Protect ion:NOT NECESSARY UNDER NORMAL USE. Ventilation:LOCAL EXHAUST. Protective Gloves:RUBBER GLOVES. Eye Protection:SAFETY GLASSES OR GOGGLES OR FACE SHIELD. Work Hygienic Practices:WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING. Supplemental Safety and Health

HCC:V1 Boiling Pt:=96.1C, 205.F Melt/Freeze Pt:M.P/F.P Text:NA Vapor Pres:40 PSIG @70F Vapor Density:>1 Spec Gravity:0.64 Evaporation Rate & amp; Reference:>1(BUTYL A CETATE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR COLORLESS LIQUID WITH MILD PERTOLEUM ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS AND ALKALINES. Stability Condition to Avoid:NA Hazardous Decomposition Products:BURNS TO FORM CO2, CO AND POSSIBLY INCOMPLETELY DECOMPOSED MATERIALS. Conditions to Avoid Polymerization:HIGH TEMPERATURES.

======== Disposal Consideration

Waste Disposal Methods:DISPOSE OF ALL WASTE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Transport Information: PROPER SHIPPING NAME: CONSUMER COMMODITY, PRESSURIZED AEROSOL CANS. HAZARD CLASS: ORM-D.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Americ a in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.