

ECOLINK INC -- AERO KLEEN AVIATION SOLVENT

=====
MSDS Safety Information
=====

FSC: 6850
NIIN: 01-442-0530
MSDS Date: 07/20/1999
MSDS Num: CKSDB
Product ID: AERO KLEEN AVIATION SOLVENT
MFN: 01
Responsible Party
Cage: 0WU71
Name: ECOLINK INC
Address: 1481 ROCK MOUNTAIN BLVD
City: STONE MOUNTAIN GA
30083-1505
Info Phone Number: 800-886-8240
Emergency Phone Number: 800-535-5053
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 0WU71
Name: ECOLINK INC
Address: 1481 ROCK MOUNTAIN BLVD
City: STONE MOUNTAIN GA 30083-1505
Phone: 800-886-8240/770-621-8240
Contract Number: SP0450-00-M-SE02

=====
Item Description Information
=====

Item Manager: S9G
Item Name: CLEANING COMPOUND,SOLVENT
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: QT
UI Container Qty: 0
Type of Container: UNKNOWN

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

=====
Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Effects of Exposure: INGESTION: SWALLOWING LARGE AMOUNTS MAY BE HARMFUL, BY CAUSING GASTROINTESTINAL IRRITATION. INHALATION: BREATHING LARGE AMOUNTS MAY BE HARMFUL, BY CAUSING BLURRED VISION, NOSE, THROAT, RESPIRATORY TRACT IRRITATION. EYES: IRRITANT. LIQUID CONTACT WILL IRRITATE EYES AND MAY CAUSE STINGING, TEARING AND REDNESS. WEAR CHEMICAL GOGGLES AND HAVE EYE FLUSHING

EQUIPMENT AVAILABLE. SKIN CONTACT: MAY CAUSE IRRITATION OR REDNESS AND BURNING, SKIN DEFATTING.

Signs And Symptoms Of Overexposure: INGESTION: GASTROINTESTINAL IRRITATION. INHALATION: BLURRED VISION, NOSE, THROAT, RESPIRATORY TRACT IRRITATION. EYES: STINGING, TEARING AND REDNESS. SKIN CONTACT: IRRITATION OR REDNESS AND BURNING.

First Aid: INGESTION-DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE 1 OR 2 GLASSES OF WATER. SEEK MEDICAL AID IMMEDIATELY. PLACE INDIVIDUAL ON LEFT SIDE WITH HEAD

DOWN. CONTACT MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING. CAUTION: ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONIA. INHALATION-REMOVE TO FRESH AIR, IF BREATHING IS DIFFICULT GIVE OXYGEN, GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. KEEP PERSON WARM & QUIET. SEEK MEDICAL AID. EYES-IRRIGATE IMMEDIATELY WITH WATER FOR 15 MINS. GET MEDICAL AID IF IRRITATION PERSISTS. SKIN-WASH WITH SOAP & WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL AID.

=====
Handling and Disposal
=====

Spill Release Procedures: SMALL SPILL: ABSORB LIQUID ON VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD.

Waste Disposal Methods: AEROKLEEN LIQUID IS TO BE DISPOSED OF BY INCINERATION OR RECYCLE IN ACCORDANCE TO LOCAL, STATE, AND FEDERAL REGULATIONS. PLEASE CALL US IF YOU NEED ADDITIONAL DISPOSAL INFORMATION. UNDER RCRA, (40 CFR 261) IN ITS PURCHASED FORM, THIS MATERIAL IS NOT CONSIDERED A HAZARDOUS WASTE.

Handling And Storage Precautions: SINCE EMPTY CONTAINERS RETAIN PRODUCT RESIDUES, ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED. ALL METAL PAILS OR DRUMS SHOULD BE GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSFERRED.

Other Precautions: ANY USE OF THIS PRODUCT IN ELEVATED TEMPERATURE PROCESSES SHOULD BE THOROUGHLY EVALUATED TO ESTABLISH & MAINTAIN SAFE OPERATING CONDITIONS.

SUDDEN RELEASE OF HOT ORGANIC CHEMICAL VAPORS OR MISTS FROM
PROCESS EQUIPMENT OPERATING AT ELAVTED TEMPERATURES MAY RESULT IN IGNITION.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point: =102.2C, 216.F

Lower Limits: ND

Upper Limits: ND

Extinguishing Media: ALCOHOL FOAM, WATER (FLOOD WITH WATER), CARBON DIOXIDE.

Fire Fighting Procedures: KEEP FIRE EXPOSED CO

NTAINERS COOL WITH WATER. FIRE

FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPOECE
OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WITH APPROPRIATE GEAR AND
CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard: NONE KNOWN.

=====
Control Measures
=====

Respiratory Protection: NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF VAPOR
MIST IS P

RESENT USE NIOSH CERTIFIED ORGANIC VAPOR MASK. RESPIRATORY PROGRAMS
MUST COMPLY WITH 29 CFR 1910.134.

Ventilation: LOCAL EXHAUST/HOOD OR FAN SUGGESTED.

Protective Gloves: NITRILE GLOVES.

Eye Protection: SAFETY GLASSES REQUIRED. SPLASH PROTECTION SUGGESTED.

Other Protective Equipment: NONE REQUIRED UNDER NORMAL USE.

Work Hygienic Practices: STORE RAGS USED WITH THIS MAATERIAL IN AN AIR TIGHT,
MEATAL CONTAINER. TREAT THIS CHEMICAL WITH RESPECT AND FOLLOW ALL MSDS
INSTRUCTIONS.

Supplemental S

afety and Health: **NOTE TO PHYSICIAN: ACTIVATED CHARCOAL MIXTURE

MAY BE BENEFICIAL, SUSPEND 50 G IN 400 ML WATER & GIVE 5 ML/KG BODY

WEIGHT OR 350 ML FOR AN AVERAGE ADULT. ****OTHER PREACUTIONS-KEEP THIS &

ALL CHEMICALS OUT OF THE REACH OF CHILDREN.

=====
Physical/Chemical Properties
=====

HCC: V5

B.P. Text: 196-228

M.P/F.P Text: NA

Vapor Pres: 0.06 MM HG @ 20C

Vapor Density: >

Spec Gravity: 1.085 @ 20C

Solubility in Water: 5.5% (WT)@ 20C

Appearance and Odor: COLORLESS, SWEET LIQUID.

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: ELEVATED TEMPERATURE, DECOMPOSES WITH HEAT. SOURCES OF IGNITION SUCH AS SPARKS, HOT SPOTS, WELDING, FLAMES.

IGNITION/FLASH MAY RESULT IF CONCENTRATION OF PRODUCT IN AIR IS EXTREMELY

Materials To Avoid:

STRONG OXIDANTS, ACIDS AND ALKALIS.

Hazardous Decomposition Products: NO UNIQUE HAZARDOUS DECOMPSITION PRODUCTS EXPECTED.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR.

Toxicological Information

Toxicological Information: DIMETHYL GLUTARATE, DIMETHYL SUCCINATE, DIMETHYL ADIPATE***ECOLINK SUGGESTS AN EXPOSURE LIMIT OF 10 MG/M3 (1.5 PPM) PER 8 HOUR

TWA BASED UPON THE ACGIH RECOMMENDATION FOR COMPONENTS OF THE SAME CHEMICAL FAMILY. DUE TO THE LACK OF VOLATILITY OF THIS PRODUCT, IT IS NOT EXPECTED THAT THIS EXPOSURE LIMIT CAN BE REACHED IN THE COURSE OF NORMAL USE.

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Other Information: LARGE SPILL: ELIMINATE ALL IGNITION SOURCES. (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PEOPLE NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN UP

HA S BEEN

COMPLETED. STOP SPILL AT SOURCE. PREVENT FROM ENTERING DRAINS, SEWERS, STREAMS, ETC. IF RUNOFF OCCURS, NOTIFY AUTHORITIES AS REQUIRED. PUMP OR VACUUM TRANSFER SPILLED PRODUCT TO CLEAN CONTAINERS FOR RECOVERY. TRANSFER CONTAMINATED ABSORBENT, SOIL & OTHER MATERIALS TO CONTAINERS FOR DISPOSAL.

=====
Transportation Information
=====

Responsible Party Code: 0WU71

Trans ID NO:

154394

Product ID: AERO KLEEN AVIATION SOLVENT

MSDS Prepared Date: 07/20/1999

Review Date: 08/10/2000

MFN: 1

Net Unit Weight: 9 LBS

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: QT

Container QTY: 0

Type Of Container: UNKNOWN

Additional Data: CALL MANUFACTURER ON 8/10/00, ITEM IS NOT A FLAMMABLE AEROSOL, IT IS SHIPPED IN PUMP SPRAY BOTTLES OR CANS.

=====
Detail DOT Information
=====

DOT P

SN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REG

ULATED BY THIS MODE OF TRANSPORTATION

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
HAZCOM Label
=====

Product ID: AERO KLEEN AVIATION SOLVENT

Cage: 0WU71

Company Name: ECOLINK INC

Street: 1481 ROCK MOUNTAIN BLVD

C

City: STONE MOUNTAIN GA

Zipcode: 30083-1505

Health Emergency Phone: 800-535-5053

Label Required IND: Y

Date Of Label Review: 08/10/2000

Status Code: A

Year Procured: 2000

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: NO

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: INGESTION: SWALLOWING LARGE AMOUNTS MAY BE HARMFUL, BY CAUSING GASTROINTESTINAL IRRITATION. INH

ALATION: BREATHING LARGE AMOUNTS MAY

BE HARMFUL, BY CAUSING BLURRED VISION, NOSE, THROAT, RESPIRATORY TRACT IRRITATION. EYES: IRRITANT. LIQUID CONTACT WILL IRRITATE EYES AND MAY CAUSE STINGING, TEARING AND REDNESS. WEAR CHEMICAL GOGGLES AND HAVE EYE FLUSHING EQUIPMENT AVAILABLE. SKIN CONTACT: MAY CAUSE IRRITATION OR REDNESS AND BURNING, SKIN DEFATTING.

=====
Disclaimer (provided with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is no

t a military or civilian employee of the

United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.