View NSN Online: https://aerobasegroup.com/nsn/6750-01-443-3337

EASTMAN KODAK COMPANY -- 882 4690,KODAK FLEXICOLOR SM TANK BLEACH/C-41SM - 6750-01-443-3337

Product ID:882 4690, KODAK FLEXICOLOR SM TANK BLEACH/C-41SM MSDS Date:09/13/2000 FSC:6750 NIIN:01-443-3337 MSDS Number: CKSQN === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num: 716-722-5151/(800) 242-2424 Emergency Phone Num:716 722-5151 Preparer's Name:NOT PROVIDED CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 Contract Num:SP0500-96-D-9413-M364 CAGE:19139

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Minumum % Wt:55. Maxumum % Wt: 60. Other REC Limits:NOT PROVIDED Code:F Code:F

Ingred Name: FERRIC AMMONIUM PROPYLENEDIAMINETETRAACETIC ACID CAS:111687-36-6 Minumum % Wt:10. Maxumum % Wt:15. Other REC Limits:NOT PROVIDED OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED Ingred Name: AMMONIUM NITRATE CAS:6484-52-2 RTECS #: BR9050000 = Wt:12. Other REC Limits:NOT PROVIDED **OSHA PEL:NOT PROVIDED** ACGIH TLV:NOT PROVIDED Ingred Name: AMMONIUM BROMIDE CAS:12124-97-9 RTECS #:BO9155000 = Wt:9. Other REC Limits:NOT PROVIDED **OSHA PEL:NOT PROVI** DED ACGIH TLV:NOT PROVIDED Ingred Name: ACETIC ACID CAS:64-19-7 RTECS #:AF1225000 Minumum % Wt:1. Maxumum % Wt:5. Other REC Limits:NOT PROVIDED OSHA PEL:25 MG/M3;10 PPM ACGIH TLV:25 MG/M3;10 PPM ACGIH STEL:37 MG/M3;15 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name:1,3-DIAMINO-2-PROPANOLTETRAACETIC ACID CAS:3148-72-9 Minumum % Wt:1. Maxumum % Wt:5. Other REC Limits:NOT PROVIDED

OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

LD50 LC50 Mixture:NOT PROVIDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EFFECTS OF EXPOSURE: INHALATION: EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. EYES: CAUSES IRRITATION. HOWEVER, IMMEDIATE FLUSHING OF THE EYES WITH WATER WILL MINIMIZE ANY IRRITATIVE EFFECT. SKIN: CAUSES IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN. INGESTION: HARMFUL IF SWALLOWED. Explanation of Carcinogenicity:CARCINOGENICITY CLASSIFICATION

(COMPONENTS PRESENT AT 0.1% OR MORE): - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC): NONE - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): NON E - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE

Effects of Overexposure: EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATION.

Medical Cond Aggravated by Exposure:NOT PROVIDED

First Aid:I

NHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTEN TION IF SYMPTOMS OCCUR. SKIN: IMMEDIATELY REMOVE CONTAMINATED CLOTHING AND SHOES AND WASH WITH SOAP AND PLENTY OF WATER. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. WASH CONTAMI NATED CLOTHING BEFORE REUSE. INGESTION: ONLY INDUCE VOMITING AT THE INS

TRUCTION OF MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN OR POISON CONTROL CENTER I MMEDIATELY.

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL, ALCOHOL FOAM

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. Unusual Fire/Explosion Hazard:SOLUTION CONTAINS A STRONG OXIDIZER. DRIED PRODUCT RESIDUE CAN ACT AS AN OXIDIZER. ELEVATED TEMPERATURE CAN CAUSE DECOMPOSITION.

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUG

HLY TO REMOVE RESIDUAL CONTAMINATION. COLLECT IN A NONCOMBUSTIBLE CONTAINER FOR PROMPT DISPOSAL. FLUSH SPILL AREA WITH WATER SPRAY.

Neutralizing Agent:NOT PROVIDED

Handling and Storage Precautions:DO NOT STORE/SHIP TOGETHER WITH COMBUSTIBLE MATERIAL. STORE IN ORIGINAL CONTAINER. KEEP CONTAINER TIGHTLY CLOSED TO PREVENT LOSS OF WATER. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES. KEEP AWAY FROM COMBUS TIBLE MATER IAL. KEEP

AWAY FROM HEAT. EXERCISE CAUTION IN HEATING, ESPECIALLY IN A CLOSED CONTAINER.

Other Precautions: AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. REMOVE AND WASH CONTAMINATED CLOTHING PROMPTLY.

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW EXPOSURE LIMITS, A

N APPROVED RESPIRATOR MUST

BE WORN. RESPIRATOR TYPE: FULL-FACE ORGANIC VAPOR CARTRIDGE: IF HAZARDOUS DECOMPOSITI ON PRODUCTS ARE LIKELY TO BE/HAVE BEEN RELEASED. A FULL-FACE POSITIVE-PRESSURE AIR-SUPPLIED NEEDED. ASSURE COMPLIANCE WITH OSHA STANDARD 29 CFR 1910.134.

Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves:WEAR IMPERVIOUS GLOVES AND PROTECTIVE CLOTHING

APPROPRIATE FOR RISK OF EXPOSURE Eye Protection: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES). Other Protective Equipment: EYE BATH, WASHING FACILITIES, SAFETY SHOWER Work Hygienic Practices:NOT PROVIDED Supplemental Safety and Health SUPPLEMENTARY LOCAL EXHAUST VENTILATION, CLOSED SYSTEMS, OR RESPIRATORY PROTECTION MAY BE NEEDED IN SPECIAL CIRCUMSTANCES SUCH AS POORLY VENTILATED SPACES, EVAPORATION FROM LARGE SURFACES, SPRAYING, H EATING, ETC, N/A = NOT APPLICABLE, N/P = NOT PRO VIDED. N/R = NOT RELEVANT. N/D = NOT DETERMINED. N/E = NOT ESTABLISHED. HCC:C3 NRC/State Lic Num:NOT RELEVANT Boiling Pt:>100.C, 212.F Melt/Freeze Pt:M.P/F.P Text:NOT PROVIDED Decomp Temp:>215.C, 419.F Vapor Pres:(68F): 23 MBAR (18 MM HG) Vapor Density:0.6 Spec Gravity:1.17 pH:4.5 Viscosity:NOT PROVIDED Evaporation Rate & amp; Reference: NOT PROVIDED Solubility in Water:COMPLETE Appearance and Odor: GREEN - BROWN LIQUID. ODO R: SLIGHT ACETIC ACID Percent Volatiles by Volume:55-60 WT Corrosion Rate:NOT PROVIDED Stability Indicator/Materials to Avoid:YES MATERIAL CAN REACT VIOLENTLY WITH COMBUSTIBLE MATERIAL, STRONG REDUCING AGENTS. BASES, SODIUM HYPOCHLORITE (BLEACH). Stability Condition to Avoid:STABLE. SAFE HANDLING TEMPERATURES ARE DEPENDENT ON SPECIFIC CONDITIONS OF USE AND ARE TYPICALLY SUBSTANTIALLY BELOW THE ONSET TEMPERATURE. CO NSULT YOUR TECHNICAL SAFETY EXPERTS. Hazardous Decomposition Products: AMMONIA, CHLORAMINE, HYDROGEN BROMIDE, CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN Toxicological Information: CONTAINS: FERRIC AMMONIUM PROPYLENEDIAMINETETRAACETIC ACID (111687-36-6). EXPOSURE TO HIGH CONCENTRATIONS MAY CAUSE INCREASED URINARY EXCRETION OF ZINC AND CALCIUM. THIS COMPOUND CAN CHELATE METALS AND MAY ALTER.

С

ALCIUM AND OTHER CATION BALANCES. CONTAINS: 1,3-DIAMINO-2-PROPANOLTETRAACETIC ACID (003148-72-9). BASED ON ANIMAL DATA THIS MATERIAL CAN PRODUCE METHEMOGLOBIN WHICH, IN SUF FICIENT CONCENTRATION, CAUSES CYANOSIS, A BLUE-GRAY DISCOLORATION OF THE SKIN AND LIPS CAUSED BY A REDUCED ABILITY OF THE BLOOD TO CARRY OXYGEN. SEE NOTE TO PHYSICIANS IN THE FIRST AID SECTION.

Ecological:THE FOLLOWING PR OPERTIES ARE ESTIMATED FROM THE COMPONENTS OF THE PREPARATIONS. POTENTIAL TOXICITY: FISH LC50 MG/L: >100. DAPHNID EC50 MG/L: >100. ALGAL IC50 MG/L: 10-100. ORGANICS READILY DEGRAD ABLE (>70%): YES (14 DAYS). POTENTIAL BIOACCUMULATION: LOG POW 100.

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER . SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE,

FOLLOW LABEL WARNINGS E VEN AFTER CONTAINER IS EMPTIED.

Transport Information:FOR TRANSPORTATION INFORMATION REGARDING THIS PRODUCT CALL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE: (716) 722-2400 BETWEEN 8 A.M. AND 5 P.M. (EASTERN STANDARD TIME), MONDAY THROUGH FRIDAY.

SARA Title

III Information:CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372: NITRATE COMPOUNDS (WATER DIS SOCIABLE), (AMMONIUM NITRATE); AMMONIUM BROMIDE, AMMONIUM NITRATE AS SOURCES OF AQUEOUS AMMONIA.

Federal Regulatory Information:NOT PROVIDED

State Regulatory Information:MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: NONE - MATERIAL(S) KNOWN Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this documen

t should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.