View NSN Online: https://aerobasegroup.com/nsn/9150-00-257-5360

\_\_\_\_\_

# NORDSTROM VALVES INC -- NORDSTROM 950 SEALANT (BULK GRADE)

MSDS Safety Information

\_\_\_\_\_ FSC: 9150 NIIN: 00-257-5360 MSDS Date: 08/14/1998 MSDS Num: CKTNS Product ID: NORDSTROM 950 SEALANT (BULK GRADE) MFN: 01 **Responsible Party** Cage: 06JW1 Name: NORDSTROM VALVES INC Address: 1511 JEFFERSON STREET E Citv: S **ULPHUR SPRINGS TX 75482** Info Phone Number: 903-885-4692 Emergency Phone Number: 903-885-3159 Resp. Party Other MSDS No.: 950B REV.1 Proprietary Ind: Y Review Ind: Y Published: Y \_\_\_\_\_ Contractor Summary \_\_\_\_\_\_ Cage: 06JW1 Name: NORDSTROM VALVES INC DBA NORDSTROM AUDCO, INC. Address: 1511 JEFFERSON ST. City: SULPHUR SPRINGS TX 75482 Phone: 903-885-4692/903-885-3151 Cage: 0PGK2 Name: SDB CONSULTANT S LTD Address: 401 WHITNEY AVE SUITE 120 City: GRETNA LA 70056 Phone: 504-366-9105 Contract Number: SP0450-00-W-2016 \_\_\_\_\_ Item Description Information \_\_\_\_\_ Item Manager: S9G Item Name: GREASE, PLUG VALVE Specification Number: MIL-G-6032 Type/Grade/Class: TY 1 Unit of Issue: CN Quantitative Expression: 2000000175LB **UI** Container Qty: L Type of Container: CAN \_\_\_\_\_

\_\_\_\_\_

#### Ingredients

\_\_\_\_\_\_

Name: \*\*\* PROPRIETARY \*\*\*

-----

# Health Hazards Data

\_\_\_\_\_

Carcinogenicity Inds - NTP: NO

IARC: YES

OSHA: NO

Effects of Exposure: INHALATION: NONE EXPECTED. INGESTION: MAY BE MILDLY

IRRITATING TO THE GASTROINTESTINAL TRACT. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATI

ON. EYES: MATERIAL CONTACTING EYES MAY CAUSE IRRITAT ION.

Explanation Of Carcinogenicity: ORGANOPHILIC CLAY (CONTAINING 0-4% TOTAL CRYSTALLINE SILICA). THE IARC HAS CONCLUDED THAT THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA TO EXPERIMENTAL ANIMALS AND LIMITED EVIDENCE FOR THE CARCINOGENICITY TO HUMANS. THE ORGANOPHILIC CLAY USED IN THIS FORMULATION IS ENCAPSULATED & amp; CANNOT BECOME AIRBORNE Signs And Symptions Of Overexposure: INHALATION: NONE EXPECTED. INGESTION: MAY

BE MILDLY IRRITATING TO THE GASTROINTESTINAL TRACT. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION. EYES: MATERIAL CONTACTING EYES MAY CAUSE IRRITAT ION.

First Aid: EYES: FLUSH EYES FOR 15 MINUTES WITH CLEAR WATER. CONTACT PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. CONTACT PHYSICIAN IF SIGNS OF IRRITATION APPEAR. INHALATION: VAPOR PRESSURE IS VERY LOW. VAPOR INHALATION IS NOT CONSIDERED A PROBLEM UNDER NORMAL USAGE CONDITIONS. INGESTION: CONSULT

### PHYSICIAN.

\_\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_

Spill Release Procedures: RECOVER FREE MATERIAL. ADD SUITABLE ABSORBENT TO SPILL AREA. CLEAN SPILL AREA WITH DETERGENT SOLUTION.

Waste Disposal Methods: INCINERATE IN A FURNACE OR OTHERWISE DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REQUIREMENTS AND REGULATIONS.

Handling And Storage Precautions: STORE IN SEALED CONTAINE

RS TO AVOID CONTAMINATION WITH FOREIGN PARTICLES.. STORE AWAY FROM STRONG OXIDIZERS.

\_\_\_\_\_

Fire and Explosion Hazard Information Flash Point Method: COC Flash Point: >204.4C, 400.F Lower Limits: NA Upper Limits: NA Extinguishing Media: DRY CHEMICAL POWDER, CARBON DIOXIDE, CHEMICAL FOAM. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRE IN CONFINED A REAS. TREAT AS BURNING OIL. Unusual Fire/Explosion Hazard: NONE KNOWN. \_\_\_\_\_ Control Measures \_\_\_\_\_ Respiratory Protection: RESPIRATORY PROTECTION NOT NEEDED UNDER NORMAL USAGE CONDITIONS. Ventilation: ADEQUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE IS SUFFICIENT. Protective Gloves: USE RESISTANT GLOVES AS NEEDED TO MINIMIZE SKIN CONTACT. Eve Protection: SAFETY GLASSES ADVIS ED AS STANDARD SAFETY PRECAUTION. Other Protective Equipment: NONE NORMALLY NEEDED. \_\_\_\_\_ **Physical/Chemical Properties** HCC: V5 Vapor Pres: NIL Spec Gravity: 1.10 @ 75F Evaporation Rate & amp; Reference: NIL (ETHER=1) Solubility in Water: NEGLIGIBLE Appearance and Odor: TAN GREASE-LIKE MATERIAL. SLIGHT FATTY ODOR. Percent Volatiles by Volume: NIL \_\_\_\_\_\_ \_\_\_\_\_ Reactivity Data \_\_\_\_\_ \_\_\_\_\_\_ Stability Indicator: YES Materials To Avoid: AVOID CONTACT WITH STRONG OXIDIZERS. Hazardous Decomposition Products: INCOMPLETE COMBUSTION MAY PRODUCE CARBON MONOXIDE, CARBON DIOXIDE AND ASPHYXIANTS. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NONE. \_\_\_\_\_

Toxicological Information

\_\_\_\_\_

===

\_\_\_\_\_\_

**Ecological Information** 

\_\_\_\_\_

Transport Information: APPLICABLE DOT CLASSIFICATION: NOT REGULATED. DOT PROPER SHIPPING NAME: N/A. DOT IDENTIFICATION NUMBER: N/A. DOT HAZARD CLASS: N/A.

#### Regulat

ory Information

\_\_\_\_\_

Sara Title III Information: MATERIALS REGULATED UNDER SARA SECTION 313 (40 CFR 372): NONE.

Federal Regulatory Information: MATERIALS REGULATED UNDER CERCLA (40 CFR 302): NONE. MATERIALS REGULATED UNDER RCRA (40 CFR 261): NONE. OSHA HAZARD COMMUNICATION STANDARD: THIS PRODUCT HAS BEEN EVALUATED AND DOES NOT REQUIRE ANY WAR NING LABEL UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200 (D)).

\_\_\_\_\_

\_\_\_\_\_

# Other Information

\_\_\_\_\_\_

Other Information: WHIMIS: NOT REGULATED. NFPA RATING: HEALTH-1, FLAMMABILITY-1, REACTIVITY-0.

\_\_\_\_\_\_

Transportation Information

\_\_\_\_\_

Responsible Party Cage: 06JW1 Trans ID NO: 154830 Product ID: NORDSTROM 950 SEALANT (BULK GRADE) MSDS Prepared Date: 08/14/1998 Review Date: 10/02 /2000 MFN: 1 Net Unit Weight: 1.75 LBS Multiple KIT Number: 0 Unit Of Issue: CN Container QTY: L Type Of Container: CAN

**Detail DOT Information** 

\_\_\_\_\_

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO Information

\_\_\_\_\_\_

\_\_\_\_\_\_

IMO PSN Code: ZZZ

Т

MO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION \_\_\_\_\_ **Detail IATA Information** \_\_\_\_\_ IATA PSN Code: ZZZ IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION \_\_\_\_\_ **Detail AFI Information** AFI PSN Code: ZZZ AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION \_\_\_\_\_ HAZCOM Label \_\_\_\_\_ Product ID: NORDSTROM 950 SEALANT (BULK GRADE) Cage: 06JW1 Company Name: NORDSTROM VALVES INC DBA NORDSTROM AUDCO, INC. Street: 1511 JEFFERSON ST. City: SULPHUR SPRINGS TX Zipcode: 75482 Health Emergency Phone: 903-885-3159 Label Required IND: Y Date Of Label Review: 10/02/2000 Status Code: A Year Procured: 2000 Origination Code: F Chronic Hazard I ND: Y Eye Protection IND: YES Skin Protection IND: YES Signal Word: CAUTION **Respiratory Protection IND: NO** Health Hazard: Slight Contact Hazard: Slight Fire Hazard: Slight Reactivity Hazard: None Hazard And Precautions: INGESTION: MAY BE MILDLY IRRITATING TO THE GASTROINTESTINAL TRACT. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION. EYES: MATERIAL CONTACTING EYES MAY CAUSE IRRITATION. TARGET ORGANS: NO DATA PROVIDED BYRESPONSIBLE PARTY. FIRST AID: EYES: FLUSH EYES FOR 15 MINUT

# ES WITH CLEAR WATER. CONTACT PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. CONTACT PHYSICIAN IF SIGNS OF IRRITATION APPEA R. INGESTION: CONSULT PHYSICIAN.

\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information

to have any application, use or

viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their p

articular situation regardless of similarity to a corresponding Department of Defense or other government situation.