View NSN Online: https://aerobasegroup.com/nsn/8040-01-107-3981 CLICK BOND, INC -- KA1E1 CP125-000-005 A1A1 CB300 PART A -- 8040-01-107-3981 Product ID:KA1E1 CP125-000-005 A1A1 CB300 PART A MSDS Date:01/12/1998 FSC:8040 NIIN:01-107-3981 Status Code:A Kit Part:Y MSDS Number: CKTYC === Responsible Party === Company Name: CLICK BOND, INC Address:2151 LOCKHEED WAY City: CARSON CITY State:NV ZIP:89706

Country:US

Info Phone Num:702-885-8000/702-883-0191

Emergency Phone Num:800-255-3924 (CHEM-TEL)

CAGE:MO939

=== Contractor Identification === Company Name: CLICK BOND, INC Address:2151 LOCKHEED WAY

City: CARSON CITY

State:NV ZIP:89706 Country:US

Phone:702-885-8000/702-883-0191

CAGE:MO939

======= Composition/Information on Ingredients ========

Ingred Name: EPOXY RESIN

Ingred Name:TRADE SECRET

Ingred Name:TRADE SECRET

Routes of Entry: Inhalatio

n:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF OVEREXPOSURE.

Effects of Overexposure:INHALATION: INHALATION OF VAPOR COULD CAUSE HEADACHES, NAUSEA, DIZZINESS AND RESPIRATORY TRACT IRRITATION. EYE CONTACT: CAUTION! CAN CAUSE MODERATE IRRITATION. MAY CAUSE SEVERE EYE INJURY. DAMAGE REVE RSIBLE. INGESTION: EXPECTED TO BE SLIGHTLY TOXIC BY THIS ROUTE. SKIN CONTACT: CAUTION! MODERATELY I RRITATING

TO THE SKIN. NOT LIKELY TO BE ABSORBED THROUGH SKIN IN TOXIC AMOUNTS. PROLONGED OR REPEATE D EXPOSURE MAY RESULT IN SENSITIZATION AND RASH.

First Aid:INHALATION: REMOVE PERSON TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT. GET IMMED MED ATTN. INGEST: DO NOT INDUCE VOMITING. GIVE LARGE AMOUNTS OF WATER/MILK IF AVAIL & TRANSPORT TO A MEDICAL FACIL ITY. EYE: FLUSH THOROUGHLY W/WATER FOR AT L EAST 15

MINS WHILE LIFTING UPPER & LOWER LIDS. GET IMMED MED ATTN. SKIN: IMMED REMOVE CONTAMINATED CLOTHES/SHOES. WIPE EXCESS FROM SKIN & FLUSH W/PLENTY OF W ATER FOR AT LEAST 15 MINS. USE SOAP IF AVAIL OR FOLLOW BY WASHING W/SOAP & WATER. DO NOT REUSE CLOTHING UNTIL THOROUGHLY CLEANED. GET MED ATTEN CONTAM LEATHER ARTICLES, INCL SHOES, CANNOT BE DECONTAM & SHOULD BE DESTROYED TO PREVENT REUSE.

========= Fire Fighting Measures ==============

Flash

Point Method: PMCC

Flash Point:=190.6C, 375.F


Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM AND CARBON DIOXIDE. Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACESHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARAT US. COOL FIRE-EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:FIRE EXPOSED CONTAINERS MAY BUILD PRESSURE AND BURST.

======

======= Accidental Release Measures =========
Spill Release Procedures:IN CASE OF SPILLS, SHUT OFF ALL IGNITIONS SOURCES AND DIKE SPILL TO CONTAIN AND PREVENT ENTRY INTO SEWERS OR WATER SOURCES. ABSORB SPILLED MATERIAL AND PLACE IN CLOSED CONTAINER FOR DISPOSAL.
========== Handling and Storage ===========
Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.
====== Exposure Controls/Personal Protection =========
Respiratory Protection:IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL OR VENTILATION, WEAR A RESPIRATOR APPROVED BY NIOSH WHENEVER EXPOSED TO FUMES OR VAPORS. COMPLY WITH OSHA 1910.134 (CFR). Ventilation:LOCAL EXHAUST RECOMMENDED.  Protective Gloves:USE PROTECTIVE GLOVES MADE OF NITRILE RUBBER OR OTHER IMPERVIOUS MATTER.  Eye Protection:ANSI APPROVED SAFETY GLASSES WITH SIDE SHIELDS/CHEMICAL WORKER GOGGLES.  Other Protective Equipment:EY  EWASH STATION & SAFETY SHOWER MEETING ANSI DESIGN CRITERIA SHOULD BE AVAILABLE FOR EMERGENCY USE. CHEMICAL RESISTANT PROTECTIVE CLOTHING TO MINIMIZE EXPOSURE; CHEMICAL SPLASH APRON & FULL FACE SHIELD.  Supplemental Safety and Health  PHYSICAL/CHEMICAL DATA: WGT %: 0.7. VAPOR DENSITY: HEAVIER THAN AIR. LIQUID DENSITY: HEAVIER THAN WATER. WGT PER GALLON: 10.00 POUNDS. FLAMMABILITY CLASS: N/A.
========= Physical/Chemical Properties ==========
Vapor Density:SU P DATA Evaporation Rate & Description Rate & Descript
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES SEE CONDITIONS TO AVOID. Stability Condition to Avoid:OXIDIZING AGENTS, STRONG LEWIS ACIDS, STRONG MINERAL ACIDS, CURING AGENTS (CONSIDERABLE HEAT CAN BE

RELEASED), HEAT STRONG ACIDS, AMINES, MERCAPTANS AND BASES.
Hazardous Decomposition Products: ALDEHYDES, ACIDS, CA



etent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.