View NSN Online: https://aerobasegroup.com/nsn/9150-00-657-4959

CHEVRON PRODUCTS COMPANY GLOBAL LUBRICANTS -- CPS226502, DEXRON III SUPREME

AUTOMATIC TRANSMISSION FLUID -- 9150-00-657-4959

============= Product Identification ========================

Product ID:CPS226502, DEXRON III SUPREME AUTOMATIC TRANSMISSION FLUID

MSDS Date:09/22/1999

FSC:9150

NIIN:00-657-4959

MSDS Number: CKVMC === Responsible Party ===

Company Name: CHEVRON PRODUCTS COMPANY GLOBAL LUBRICANTS

Address:555 MARKET ST

. ROOM 803

City:SAN FRANCISCO

State:CA

ZIP:94105-2870

Country:US

Info Phone Num:800-414-6737/415-894-0434

Emergency Phone Num:800-231-0623

Resp. Party Other MSDS Num.:000021 REVISION #26

Chemtrec Ind/Phone:(800)424-9300

CAGE:2H740

=== Contractor Identification ===

Company Name: CASCADE DISTRIBUTING

Address:136 E. MAIN STREET SUITE 6

Box:City:KENT

State:OH ZIP:44240

Country:US

Phone:330-677-1118/FAX 330-677-1014

Contract Num: SP0450-01-C-0605

CAGE:082N2

Company Name: CASCADE DISTRIBUTING

Address:136

E. MAIN STREET SUITE 6

Box:City:KENT

State:OH ZIP:44240 Country:US

Phone:330-677-1118/FAX 330-677-1014

Contract Num: SP0450-01-C-0623

CAGE:082N2

Company Name: CHEVRON PRODUCTS CO GLOBAL LUBRICANTS

Address:555 MARKET STREET ROOM 803

Box:City:SAN FRANCISCO

State:CA

ZIP:94105-2870

Country:US

Phone:800-228-3500/415-894-0703

CAGE:2H740

======= Composition/Information on Ingredients =========

> Wt:80.

Ingred Name: DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

Code:F

PY8035500 OSHA PEL:5 MG/M3 (MIST) ACGIH TLV:5 MG/M3 (MIST)

ACGIH STEL:10 MG/M3 (MIST)

Ingred Name: DISTILLATES (PETROLEUM), SOLVENT DEWAXED HEAVY PARAFFINIC

CAS:64742-65-0

Code:F

RTECS #:PY8038500

OSHA PEL:5 MG/M3 (MIST) ACGIH TLV:5 MG/M3 (MIST) ACGIH STEL:10 MG/M3 (MIST)

Ingred Name: DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC

CAS:64742-56-9 RTECS #:PY8039500

OSHA PEL:5 MG/M3 (MIST) ACGIH TLV:5 MG/M3 (MIST)

Ingred Name: DISTILLATES, SOLVENT-REFINED LIGHT NAPHTHENIC

CAS:64741-97-5 RTECS #:PY8041000

OSHA PEL:5 MG/M3 (MIST) ACGIH TLV:5 MG/M3 (MIST)

========== Hazards Identification ================

LD50 LC50 Mixture:NOT DATA PROVIDED BY MANUFACTURER Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: NOT EXPECTED TO CAUSE PROLONGED OR SIGNIFICANT IRRITATION. SKIN: CONTACT WITH SKIN IS NOT EXPECTED TO CAUSE PROLONGED OR SIGNIFICANT IRRITATION. NOR EXPECTED TO BE HARMFUL TO INTERNAL ORGANS IF A BSORBED THR

OUGH THE SKIN.

ACCIDENTAL HIGH-VELOCITY INJECTION UNDER THE SKIN OF MATERIALS OF THIS TYPE MAY RESULT IN SERIOUS INJURY. THE INITIAL WOUND AT THE INJECTION SITE MAY NOT APPEAR TO BE SERIOUS AT FIRST, BUT, IF LEFT UNATTENDED, COULD RESULT IN DISFIGUREMENT OR AMPUTATION OF THE AFFECTED PART. INGESTION: NOT EXPECTED TO BE HARMFUL IF SWALLOWED. INHALATION: MAY CAUSE RESPIRATORY IRRITATION O R OTHER PULMONARY EFFECTS.

Explanation of Carcinogenicity: NONE OF THESE OILS REQU

IRE A CANCER

WARNING UNDER OSHA 29 CFR 1910.1200. THESE OILS HAVE NOT BEEN LISTED BY THE NTP OR IARC.

Effects of Overexposure:ACCIDENTAL HIGH-VELOCITY INJECTION UNDER THE SKIN OF MATERIALS OF THIS TYPE MAY RESULT IN SERIOUS INJURY. THE INITIAL WOUND AT THE INJECTION SITE MAY NOT APPEAR TO BE SERIOUS AT FIRST, BUT, IF LEFT UN ATTENDED, COULD RESULT IN DISFIGUREMENT OR AMPUTATION OF THE AFFECTED PART. INHALATION: MAY CAUSE RESPIRATORY IRRITATION OR OTHER PULMONARY EFFEC

TS.

Medical Cond Aggravated by Exposure: NO DATA PROVIDED BY MANUFACTURER

First Aid:EYE: NO SPECIFIC FIRST AID MEASURES ARE REQUIRED. AS A PRECAUTION REMOVE CONTACT LENSES, IF WORN, & FLUSH EYES WITH WATER. SKIN: NO SPECIFIC FIRST AID MEASURES ARE REQUIRED BECAUSE THIS MATERIAL IS NO T EXPECTED TO BE HARMFUL IF IT CONTACTS THE SKIN. AS A PRECAUTION, REMOVE CLOTHING & SHOES IF CONTAMINATED. USE A WATERLESS H

AND CLEANER, MINERAL OIL, OR PETROLEUM JELLY TO REMOVE
THE MATERIAL, THEN W ASH WITH SOAP & WATER. WASH OR CLEAN
CONTAMINATED CLOTHING & SHOES BEFORE REUSE. INGESTION: NO SPECIFIC
FIRST AID MEASURES ARE REQUIRED.

========== Fire Fighting Measures ===============

Flash Point Method:COC Flash Point:=178.C, 352.4F

Autoignition Temp: Autoignition Temp Text: NDA

Lower Limits:NA Upper Limits:NA

Extinguishing Media: CO2, DRY CHEMICAL, FOAM, WATER FOG.

Fire Fighting Procedu

res:THIS MATERIAL WILL BURN ALTHOUGH IT IS NOT EASILY IGNITED.

Unusual Fire/Explosion Hazard:LEAK/RUPTURES IN HIGH PRESSURE SYSTEM USING MATERIALS OF THIS TYPE CAN CREATE A FIRE HAZARD WHEN IN THE VICINITY OF IGNITION SOURCES (EG OPEN FLAMES, PILOT LIGHTS, SPARKS, OR ELECTRIC ARCS)..

======== Accidental Release Measures ===========

Spill Release Procedures:STOP THE SOURCE OF LEAK OR RELEASE. CLEAN UP RELEASES AS SOON AS POSSIBLE, OBSERVING PRECAUTIONS IN

## **EXPOSURE**

CONTROLS/PERSONAL PROTECTION. CONTAIN LIQUID TO PREVENT FURTHER CONTAMINATION OF SOIL, SURF ACE WATER OR GROUNDWATER. CLEAN UP SMALL SPILLS USING APPROPRIATE TECHNIQUES SUCH AS SORBENT MATRIALS OR PUMPING. WHERE FEASIBLE & APPROPRIATE, REMOVE CONTAMINATED SOIL. FOLLOW PRESCRIBED PROCEDURES.

Neutralizing Agent: NO DATA PROVIDED BY MANUFACTURER

========== Handling and Storage ===============

Handling and Storage Precautions:DO NOT USE IN HIGH PRESS URE SYSTEMS IN

THE VACINITY OF FLAMES, SPARKS & HOT SURFACES. USE ONLY IN WELL VENTILATED AREAS. KEEP CONTAINER CLOSED. CONTAINER IS NOT DESIGNED TO CONTAIN PRESSURE. DO NOT US E PRESSURE TO EMPTY CONTAINER OR IT MAY RUPTURE WITH EXPLOSIVE FORCE.

Other Precautions:EMPTY CONTAINERS RETAIN PRODUCT RESIDUE & CAN BE DQNGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY OR OTHER SOUR CE OF

IGNITION. THEY MAY EXPLODE & CAUSE INJURY OR DEATH.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:NO RESPIRATORY PROTECTION IS NORMALLY REQUIRED. IF USER OPERATIONS GENERATE AN OIL MIST, DETERMINE IF AIRBORNE CONCENTRATIONS ARE BELOW THE RECOMMENDED MINERAL OIL EXPOSURE LIMITS. IF NOT WEAR A NIOSH APPROVED RESPIRATOR THAT PROVIDES ADEQUATE PROTECTION FROM MEASURES CONCENTRATIONS OF THIS MATERIAL.USE THE FOLLOWING ELEMENTS FO

R ALL AIR-PURIFYING RESPIRATOR

Ventilation:USE IN A WELL VENTILATED AREA. IF USER GENERATES AN OIL MIST, USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL

Protective Gloves:, ,


Eye Protection: WHERE SPLASHING IS POSSIBLE, WEAR SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:WHERE SPLASHING IS POSSIBLE, SELECT PROTECTIVE CLOTHING DEPENDING ON OPERATIONS CONDUCTED, PHYSICAL REQUIREMENTS AND OTHER SUBSTANCES.

Work Hygien

Supplemental Safety and Health RESPIRATORY: PARTICULATE. VENTILATION: AIRBORNE LEVELS BELOW THE RECOMMENDED MINERAL OIL MIST EXPOSURE LIMITS.
======== Physical/Chemical Properties =========
HCC:V6 Boiling Pt:B.P. Text:NDA Melt/Freeze Pt:M.P/F.P Text:NDA Decomp Temp:Decomp Text:NP Spec Gravity:0.69 pH:NDA Solubility in Water:INSOLUBLE Appearance and Odor:RED LIQUID
======== Stability and Reactivity Data ==================================
Stability Indicator/Materials to Avoid:YES MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS CHLORATES, NITRATES, PEROVICES, ETC. Stability Condition to Avoid:NO DATA AVAILABLE. Hazardous Decomposition Products:NO DATA AVAILABLE.
Toxicological Information: ACUTE SKIN/EYES/INHALATION/ORAL EFEFCTS: HAZARDS BASED ON DATA FOR SIMILAR MATERIAL. ADDITIONAL TOXICOLOGY INFORMATION: THIS PRODUCT CONTAINS PETROLEUM BAS E OILS WHICH MAY BE REFINED BY VARIOUS PROCES SES INCLUDING SEVERE SOLVENT EXTRACTION, SEVERE HYDROCRACKING, OR SEVERE HYDROTREATING. NONE OF THESE OILS REQUIRE A CANCER WARNING UNDER OSHA 29 CFR 1910.1200. THESE OILS HAVE NOT BEEN LISTED BY THE NTP OR IARC AS: CARCINOGENIC TO HUMANS (GROUP I); PROBABLY CARCINOGENIC TO HUMANS (GROUP 2A); OR POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B)
======================================
Ecological:ECOTOXI

ic Practices:NO DATA PROVIDED BY MANUFACTURER



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.