

FISKE BROTHERS REFINING CO -- FISKE'S THREAD-EZY CLEAR CUTTING OIL -- 9150-01-013-5281

=====
Product Identification
=====

Product ID:FISKE'S THREAD-EZY CLEAR CUTTING OIL

MSDS Date:01/01/1999

FSC:9150

NIIN:01-013-5281

Status Code:A

MSDS Number: CKVRD

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

In

fo Phone Num:419-691-2491

Emergency Phone Num:800-255-3924

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:OIL MIST IN AIR (NOT ENCOURAGED IN NORMAL AIR)

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

=====
Hazards Identification
=====

Reports of Carcinog

enicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD RO SEVERE PULMONARY INJU RY.

=====

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH CLEAR WATER FOR 15 MINS OR UNTIL SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN. SKIN-REMOVE ANY CONTAMINATED CLOTHING & WASH WITH SOAP & WARM WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF THE APPERANCE/SIZE, CONTACT PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION-VAPOR PRESSURE IS VERY LOW & INHALATION AT ROOM TEMPERATURE IS NO T A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE & CALL A PHYSICIAN. IF OVER-EXPOSED TO OIL MIST, REMOVE FROM EXPOSURE. INGESTION-CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:=176.7C, 350.F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).

Fire Fighting Procedures:COOL E

XPOSED CONTAINERS WITH WATER. USE

AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER LIQUID, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWER AND WA

TER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED
OR MAY ENTER SEWERS AND WATER COURSES.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.
DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG
OXIDANTS.

Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL-SOAKED CLOTHING
AND LAUNDRY BEFORE RESUE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====
Exposure Controls/Personal
Protection
=====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:LOCAL EXHAUST: USED TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.

Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.

Other Protective Equipment:USE OIL-SOAKED APRON IF NEEDED.

Supplemental Safety and Health

GENERIC/CHEMICAL NAME: PETROLEUM LUBRICATING OIL. FORMULA: MINERAL
OIL, FATTY OIL AND SULFUR.

=====
Physical/Chemical Properties
=====

=

HCC:V6

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:LIQUID

Vapor Pres:5

Spec Gravity:0.92

Evaporation Rate & Reference: