

ACUMULADORES DEL NOROESTE,S.A. DE C.V. -- BATTERY ELECTRIC STORAGE, DRY CHARGED, LEAD-ACID -- 6140-00-984-0068

=====
Product Identification
=====

Product ID:BATTERY ELECTRIC STORAGE, DRY CHARGED, LEAD-ACID

MSDS Date:11/14/2000

FSC:6140

NIIN:00-984-0068

Status Code:A

MSDS Number: CKWVB

=== Responsible Party ===

Company Name:ACUMULADORES DEL NOROESTE,S.A. DE C.V.

Address:CALLE CRUZ DEL SUR NO. 10 F

RACC.LA JOYA

City:TIJUANA B.C. MEXICO

Info Phone Num:1-800-443-1672 FROM USA

Emergency Phone Num:800-535-5053

CAGE:TO293

=== Contractor Identification ===

Company Name:ACUMULADORES DEL NOROESTE,S.A. DE C.V.

Address:CALLE CRUZ DEL SUR NO. 10 FRACC.LA JOYA

Box:City:TIJUANA B.C. MEXICO

Phone:1-800-443-1672 FROM USA

CAGE:TO293

Company Name:BATTERY EMPORIUM AND TECHNOLOGY

Address:1462 CALLE MARBELLA

Box:City:OCEANSIDE

State:CA

ZIP:92056

Country:US

Phone:760-630-1848

Contract Num:SP0430-01-M-G135

CAGE

:05BF1

Company Name:COMMERCIAL BATTERY

Address:6930 CAMINO MAQUILADORA STEK & L

Box:City:SAN DIEGO

State:CA

ZIP:92154

Country:US

Phone:619-424-5945

CAGE:0XGM7

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD, PB

CAS:7439-92-1

RTECS #:OF7525000

OSHA PEL:0.06MG/M3

ACGIH TLV:0.15 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES OSHA:NO

Health Haza

Effects Acute and Chronic: PRODUCT IS DRY CHARGED BATTERY. NO HAZARD IS ANTICIPATED . HAZARDOUS EXPOSURE CAN OCCUR WHEN PRODUCT IS IN FIRE AND/OR BROKEN . EYE AND SKIN IRRITATION BY RESIDUAL ACID. LEAD OVER EXPOSURE CAN BRING ON ABDOMINAL COLIC, CONSTIPATION, NAUSEA, ANEMIA AND MUSCLE FATIGUE.

Explanation of Carcinogenicity: LEAD, CAS# 7439-92-1 AND LEAD COMPOUNDS, INORGANIC (VOL 23, SUPPL. 7; 1987) IS IARC CLASS 2B, " THE AGENT IS POSSIBLY CARCINOGENIC TO HUMANS" AND CLASS I, "INADEQUATE EVIDENCE"

Effects of Overexposure: STINGING AND BURNING SENSATION TO SKIN AND EYES.

=====
Fire Fighting Measures
=====

Extinguishing Media: N/P. [USE MEDIA APPROPRIATE FOR SURROUNDING FIRE].

=====
Handling and Storage
=====

Handling and Storage Precautions: STORE WITH VENT SIDE UP. NEUTRALIZE ELECTROLYTE SPILLS. [THIS IS A DRY CHARGED BATTERY. ONLY RESIDUAL AMOUNTS, IF ANY, ELECTROLYTE INVOLVED.].

=
=====
Exposure Controls/Personal Protection
=====

Protective Gloves: RUBBER GLOVES. [NONE NORMALLY REQUIRED, ONLY IF RESIDUAL ACID INVOLVED].

Eye Protection: SAFETY GOGGLES OR FACE SHIELD. [NONE REQUIRED, ONLY FOR RESIDUAL ACID].

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC: N1

Appearance and Odor: DRY CHARGED LEAD-ACID BATTERY .

=====
Stability and Reactivity Data
=====

Stability Indi

cator/Materials to Avoid: YES

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: DO NOT DISPOSE. MATERIAL SHOULD BE RECYCLED BY A LICENSED BATTERY RECYCLER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.