View NSN Online: https://aerobasegroup.com/nsn/9150-00-935-5851

MOBIL OIL CORP. NORTH AMERICA MARKETING AND REFINING -- 530626-00 MOBILGREASE 28 -- 9150-00-935-5851

Product ID:530626-00 MOBILGREASE 28 MSDS Date:08/29/2000 FSC:9150 NIIN:00-935-5851 Status Code:A MSDS Number: CKXVX === Responsible Party === Company Name: MOBIL OIL CORP. NORTH AMERICA MARKETING AND REFINING Address:3225 GALLOWS RD City:FAIRFAX State:VA ZIP:22037 Country:US Info Phone Num:800-662-4525, 703-849-3451 Emergency Phone Num:609-737-4411 Chemtrec Ind/Phone:(800)424-9300 CAGE:6G112 === Contractor Identification === Company Name: MOBIL OIL CORP Address:3225 GALLOWS RD Box:City:FAIRFAX State:VA ZIP:22037 Country:US Phone:800-662-4525, 856-224-4644 CAGE:6G112 Company Name: RADIAN INTL LLC Address:8501 N MOPAC BLVD Box:201088 City:AUSTIN State:TX ZIP:78720-1088 Country:US Phone:512-419-5224 Contract Num:SP0450-00-D-4021 CAGE:29913

====== Com

position/Information on Ingredients =========

Ingred Name:PENTAERYTHRITOL CAS:115-77-5 RTECS #:RZ2490000 Minumum % Wt:1. Maxumum % Wt:5. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

LD50 LC50 Mixture:ORAL, RAT LD50: >2000 MG/KG.

Health Hazards Acute and Chronic:PRODUCT ASSESSED IN ACCORDANCE WITH OSHA 29 CFR 1910.1200 AND DETERMINED NOT TO BE HAZARDOUS. EFFECTS OF OVER EXPOSURE:NO SIGNIFICANT EFFECTS EXPECTED. Effects o

f Overexposure:NO SIGNIFICANT EFFECTS EXPECTED.

First Aid:EYE CONTACT: FLUSH THOROUGHLY WITH WATER. IF IRRITATION OCCURS, CALL A PHYSICIAN. SKIN CONTACT: WASH CONTACT AREAS WITH SOAP AND WATER. HIGH PRESSURE ACCIDENTAL INJECTION THROUGH THE SKIN REQUIRES IMM EDIATE MEDICAL ATTENTION FOR POSSIBLE INCISION, IRRIGATION AND /OR DEBRIDEMENT. INHALATION: NOT EXPECTED TO BE A PROBLEM. INGESTION: NOT EXPECTED TO B

E A PROBLEM. HOWEVER, IF GREATER THAN 1/2 LITER (P INT) INGESTED, IMMEDIATELY GIVE 1 TO 2 GLASSES OF WATER AND CALL A PHYSICIAN, HOSPITAL EMERGENCY ROOM OR POISON CONTROL CENTER FOR ASSISTANCE. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UN CONSCIOUS PERSON.

Flash Point:=232.2C, 450.F EST. (OIL COC) Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, AND WATER FOG. Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING, USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL, WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE. PREVENT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERIN G STREAMS, SEWERS, OR DRINKING WATER SUPPLY. FOR FIRES IN ENCLOSED AREAS, USE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: SHOVEL UP AND DISPOSE AT APPROPRIATE WAS

ΤE

DISPOSAL FACILITY I/A/W CURRENT APPLICABLE LAWS AND REGULATIONS, AND PRODUCT CHARACTERISTICS AT TIME OF DISPOSAL. PREVENT SPILLS FROM ENTERING STORM SEWERS O R DRAINS AND CONTACT WITH SOIL. REPORT SPILL AS REQUIRED TO APPROPRIATE AUTHOIRITES. US COAST GUARD REGULATIONS REQUIRE IMMEDIATE REPORTING OF SPILLS THAT COULD REACH (CONTD. SEE ECOLOGICAL) Neutralizing Agent:N/P.

Handling and Storage Precautio

ns:HANDLING: HIGH PRESSURE INJECTION

UNDER THE SKIN MAY OCCUR DUE TO THE RUPTURE OF PRESSURIZED LINES. ALWAYS SEEK MEDICAL ATTENTION. STORAGE: DO NOT STORE IN OPEN OR UNLABELLED CONTAINERS. STORE AWAY FR OM STRONG OXIDIZING AGENTS OR COMBUSTIBLE MATERIAL.

Other Precautions:(CONTD FROM" WASTE DISPOSAL") DISPOSAL FACILITY. USE OF THESE METHODS IS SUBJECT TO USER COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS AND CONSIDERATION OF PRODUCT CHARACTERISTICS AT TIME OF DISPO

SA L.(CONTD SEE "ECOLOGICAL")

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE. PROVIDE ADEQUATE VENTILATION.

Protective Gloves:WEAR OIL IMPERVIOUS GLOVES IF REPEATED OR PROLONGED SKIN CONTACT IS LIKELY.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL TYPE GOGGLES IF EYE

CONTACT LIKELY

Work Hygienic Practices: GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.

Supplemental Safety and Health

HCC:V5 Boiling Pt:>315.6C, 600.F Vapor Pres: