

ELDORADO CHEMICAL COMPANY, INC. -- ELDORADO PR3404, PAINT REMOVER, ID PR-3404 --
8010-00-943-7128

===== Product Identification =====

Product ID:ELDORADO PR3404, PAINT REMOVER, ID PR-3404

MSDS Date:12/21/1999

FSC:8010

NIIN:00-943-7128

Status Code:A

MSDS Number: CKYSN

=== Responsible Party ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Info Phone Num:210-653-2060/FX2106530825

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtec Ind/Phone:(800)424-9300

CAGE:55208

=== Contractor Identification ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Phone:800-531-1088/ 210-653-2060

CAGE:55208

===== Composition/Information on Ingredients =====

Ingred Name:DICHLOROMETHANE

CAS:75-09-2

RT

ECS #:PA8050000
= Wt:75.
OSHA PEL:SEE TABLE Z-2
ACGIH TLV:174 MG/M3;50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHANOL
CAS:64-17-5
RTECS #:KQ6300000
= Wt:8.
OSHA PEL:1900 MG/M3;1000 PPM
ACGIH TLV:1880 MG/M3;1000 PPM

Ingred Name:AMMONIUM HYDROXIDE
CAS:1336-21-6
RTECS #:BQ9625000
= Wt:5.
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHANOL
CAS:67-56-1
RTECS #:PC1400000
= Wt:2.
OSHA PEL:260 MG/M3;200 PPM
ACGIH TLV:262 MG/M3;200 PPM
ACGIH STEL:328 MG/M3;250 PPM
EPA Rpt
Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM CHROMATE
CAS:7775-11-3
RTECS #:GB2955000
= Wt:.7
OSHA PEL:SEE TABLE Z-2
ACGIH TLV:0.05 MG/M3
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Health Hazards Acute and Chronic:INHALATION ACUTE: HIGH ABSORBED INTO LUNGS INDUCES NARCOSIS, DIZZINESS, NAUSEA INHALATION CHRONIC: LOW NO CUMULATIVE EFFECT. SUSPECTED CARCINOGEN BY ANIMAL STUDIES. SKIN CONTACT ACUTE: HIGH CO

R ROSIVE TO SKIN. WILL CAUSE SCARRING THAT SHOULD DISAPPEAR IN 1-2 YEARS SKIN CONTACT CHRONIC: NONE NO EVIDENCE OF SKIN ABSORPTION HAZARD EYE CONTACT ACUTE: HIGH CORROSIVE TO EYES ON CONTACT. SHORT EX POSURE WILL CAUSE HAZY VISION WHICH SHOULD RETURN TO NORMAL. EYE CONTACT CHRONIC: SLIGHT PAIN SHOULD PRECLUDE CHRONIC EXPOSURE. NO CHRONIC EFFECTS EXPECTED. Medical Cond Aggravated by Exposure:

=====
===== First Aid Measures =====

First Aid:EYE
S: FLUSH WITH WATER FOR AT LEAST 15 MINUTES SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING, CONSULT PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Autoignition Temp:>426.7C, 800.F
Extinguishing Media:WATER
Fire Fighting Procedures:SCBA IS REQUIRED.
Unusual Fire/Explosion Hazard:CONTACT WITH FLAME MAY PRODUCE TOXIC CHLORINE FUMES AND/OR PHOSGENE GAS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN AND CLEANUP SPILLS WITH ABSORBENT. USEPA HAZARDOUS WASTE NO?S: AS IS: THIS PRODUCT HAS A D007 EPA HAZARDOUS WASTE CODE. CONSULT FEDERAL, STATE AND LOCAL REGULATORY AGENCIES FOR PROPER DISPOSAL.

=====
===== Handling and Storage =====

Other Precautions:

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:OSHA/NIOSH APPROVED RESPIRATORY PROTECTION.
Ventilation:100FT/MIM.
Protective Gloves:CHEMICAL RESISTANT.
Eye Protection:GOGGLES AND FACE SHIELD.
Other Protective Equipment:FULL WASH RACK GEAR AND RUBBER BOOTS AND RAIN SUITS
Work Hygienic Practices:AVOID SKIN CONTACT, WASH WITH SOAP AND WATER AFTER USE. DO NOT USE IN A CONFINED SPACE.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt.=46.1C, 115.F
Vapor Pres:300 MMHG@20C
Vapor Density:2
Spec Gravity:1.2
pH:12
Evapo

ration Rate & Reference:1
Solubility in Water:INSOLUBLE
Appearance and Odor:VISCOUS LIQUID, PUNGENT ODOR
Percent Volatiles by Volume:90

===== Stability and Reactivity Data =====

STRONG OXIDIZERS, ACIDS, ALKALIS, AND REACTIVE METALS.
Hazardous Decomposition Products:CHLORINE FUMES AND/OR PHOSGENE GAS
MAYBE PRODUCED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.