

BOW ELECTRONIC SOLDERS -- SOLU-CORE SOLDER TIN/LEAD/SILVER ALLOYS --
3439-00-912-8698

=====
===== Product Identification =====

Product ID:SOLU-CORE SOLDER TIN/LEAD/SILVER ALLOYS

MSDS Date:05/01/2000

FSC:3439

NIIN:00-912-8698

Status Code:A

MSDS Number: CKYVG

=== Responsible Party ===

Company Name:BOW ELECTRONIC SOLDERS

Address:1 CROSSMAN RD

City:SAYREVILLE

State:NJ

ZIP:08872

Country:US

Info Phone Num:73

2-316-2100

Emergency Phone Num:800-535-5053 (INFOTRAC)

CAGE:3A822

=== Contractor Identification ===

Company Name:BOW ELECTRONIC SOLDERS (REPLACED BY CAGE 52329)

Address:1 CROSSMAN RD

Box:City:NEWARK

State:NJ

ZIP:07100

Country:US

Contract Num:SP0490-98-M-M844

CAGE:3A822

=====
===== Composition/Information on Ingredients =====

Ingred Name:TIN

CAS:7440-31-5

RTECS #:XP7320000

Minimum % Wt:0.

Maximum % Wt:100.

OSHA PEL:2.0 MG/M3

ACGIH TLV:2 MG/M3

Ingred Name:LEAD

CAS:7439-92-1

RTECS #

:OF7525000
Minumum % Wt:0.
Maxumum % Wt:100.
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.15 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY
CAS:7440-36-0
RTECS #:CC4025000
< Wt:2.
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SILVER
CAS:7440-22-4
RTECS #:VW3500000
< Wt:5.
OSHA PEL:0.01 MG/M3
ACGIH TLV:0.1 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MIXED AMINE SALTS
Minumum % Wt:1.
Maxumum % Wt:3.

=====
ntification =====

Health Hazards Acute and Chronic:ACUTE: LEAD MAY LEAD TO CENTRAL NERVOUS SYSTEM DISORDERS, CHARACTERIZED BY DROWSINESS, SEIZURES, COMA AND DEATH. EXPOSURES OF THIS MAGNITUDE IN AN INDUSTRIAL ENVIRONMENT ARE EXTREMELY UNLIKELY. CHRONI C: LEAD CAN RESULT IN SYSTEMIC POISONING WITH SYMPTOMS OF METALLIC TASTE, ANEMIA, INSOMNIA, WEAKNESS, CONSTIPATION, ABDOMINAL PAIN, GASTROINTESTINAL DISORDERS, JOINT AND MUSCLE PAIN AND MUSCULAR WEAKN ESS A

ND MAY

CAUSE DAMAGE TO BLOOD-FORMING, NERVOUS, KIDNEYS, AND REPRODUCTIVE SYSTEMS. DAMAGE MAY INCLUDE REDUCED FERTILITY IN BOTH MEN AND WOMEN, DAMAGE TO FETUS OF EXPOSED PREGNANT WOMEN, ANEMIA, MUSCULAR WEAKNESS AND KIDNEY DYSFUNCTION.

Explanation of Carcinogenicity: SPECIAL PRECAUTIONS, PROCEDURES, LABEL INSTRUCTION: SPECIAL ATTENTION IS DRAWN TO THE REQUIREMENTS OF THE OSHA LEAD STANDARD (1910.1025) AND RESPIRATOR STANDARD (1910.134) SHOULD AIRBORN EXPOSURES EXCEED THE OSHA ACTION LEVEL AND PEL.

Effects of Overexposure: DROWSINESS, SEIZURES, COMA, AND DEATH, SYSTEMIC POISONING, METALLIC TASTE, ANEMIA, INSOMNIA, WEAKNESS, CONSTIPATION, ABDOMINAL PAIN, GASTROINTESTINAL DISORDERS, JOINT AND MUSCLE PAIN AND MUSCULAR WEAKNESS, DAMAGE TO BLOOD-FORMING, NERVOUS, KIDNEYS, AND REPRODUCTIVE SYSTEMS, REDUCED FERTILITY IN BOTH MEN AND WOMEN, DAMAGE TO FETUS OF EXPOSED PREGNANT WOMEN, ANEMIA, MUSCULAR WEAKNESS, AND KIDNEY DYSFUNCTION.

Medical C

and Aggravated by Exposure: DISEASES OF THE BLOOD AND BLOOD FORMING ORGANS, KIDNEYS, NERVOUS AND POSSIBLY REPRODUCTIVE SYSTEMS.

===== First Aid Measures =====

First Aid: INHALATION: REMOVE FROM EXPOSURE AND CALL A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND WATER. IF BURNS SHOULD OCCUR FROM MOLTEN METAL TREAT FOR BURN AND GET IMMEDIATE MEDICAL ASSISTANCE. EYE CONTACT: FLUSH EYES WITH WATER FOR 15 MINUTES, CALL A PHYSICIAN.

INGESTION: INGEST LARGE QUANTITIES OF WATER, CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point: =204.4C, 400.F

METAL CORE

Extinguishing Media: USE CO2 OR DRY CHEMICAL ON SURROUNDING FIRE.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS AND FULL BODY PROTECTIVE CLOTHING. DO NOT USE WATER ON FIRE WHERE MOLTEN METAL IS PRESENT.

Unusual Fire/Explosion Hazard: MOLTEN METALS PRODUCE FUME OR VAPOR THAT

MAY BE TOXIC AND/OR RESPIRATORY IRRITANTS. REACTS VIOLENTLY WITH OXYDIZING AGENTS.

===== Accidental Release Measures =====

Spill Release Procedures: ANY METHOD THAT KEEPS DUST TO A MINIMUM IS ACCEPTABLE. VACUUMING IS PREFERRED. USE OF APPROVED RESPIRATORY PROTECTION WHERE THE POSSIBILITY OF DUST/FUME EXPOSURE EXISTS. DO NOT USE COMPRESSED AIR FOR CLEANING.

===== Handling and Storage =====

Handling and Storage Preca

utions: NORMAL HANDLING: USE OF APPROVED

RESPIRATOR IS REQUIRED FOR APPLICATIONS WHERE ADEQUATE VENTILATION CANNOT BE PROVIDED. ACTIVITIES WHICH GENERATE DST OR FUME SHOULD BE AVOIDED. WHEN MELTED, THE TEMPER ATURE SHOULD BE KEPT AS LOW AS POSSIBLE. STORAGE: GENERAL STORAGE PROCEDURES ARE ACCEPTABLE.

Other Precautions: OVERHEATING OF ALLOY CAN PRODUCE METAL FUMES AND OXIDES. MACHINING OPERATIONS SUCH AS GRINDING, SAWING, OR BUFFING CAN GENERATE AIRBORN PARTICULATES IN THE W

ORK AREA. EXPOSURE LEVELS

INDICATED FOR ING REDIENTS ARE RELAVENT TO THESE AND OTHER OPERATIONS. SPECIAL ATTENTION IS DRAWN TO THE (CONTD. SEE " TOXICOLOGICAL")

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WHERE AIRBORNE EXPOSURES MAY EXCEED OSHA/ ACGIH PERMISSIBLE AIR CONCENTRATIONS, THE MINIMUM RESPIRATORY PROTECTION RECOMMENDED IS A NEGATIVE PRESSURE AIR PURIFYING RESPIRATOR WITH CARTRIDGES THAT ARE NIOSH/ MSHA APPROVED

AGAINST DUST, FUMES, AND

MISTS HAVING A TWA NOT LESS THAN 0.05 MG/ M3.

Ventilation: LOCAL EXHAUST VENTILATION IS RECOMMENDED FOR DUST AND/OR FUME GENERATION OPERATIONS WHERE AIRBORN EXPOSURES MAY EXCEED PERMISSIBLE AIR CONCENTRATIONS.

Protective Gloves: GLOVES RECOMMENDED IF SKIN CONTACT IS APPRECIABLE.

Eye Protection: SAFETY GLASSES RECOMMENDED WHEN DUST PARTICLES AND HANDLING MOLTEN METAL EXISTS

Other Protective Equipment: PROTECTIVE CLOTHING RECOMMENDED IF SKIN CONTACT IS APPR

ECIABLE. A SHOWER IS RECOMMENDED IF SIGNIFICANT DUST EXPOSURE OCCURS.

Work Hygienic Practices:AVOID INHALATION OR INGESTION. PRACTICE GOOD HOUSEKEEPING AND PERSONAL HYGIENE PROCEDURES. SHOWER IS RECOMMENDED IF SIGNIFICANT DUST EXPOSURE OCCURS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:>1300.C, 2372.F

Melt/Freeze Pt:=179.C, 354.2F

M.P/F.P Text:179C TO 312C (METAL)

Decomp Temp:Decomp Text:FLUX DECOMPOSES W/ H EAT

Spec Gravity:7.3 TO 11.3 (METAL)

Solubility in Water:FLUX SOLUBLE.

Appearance and Odor:SOLID, SILVER-WHITE METAL, CORE HAS PLEASANT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, SULFUR, CHLRINE, BROMINE, IODINE, AND HALOGEN ACIDS. STRONG OXIDIZERS MAY CAUSE VIOLENT REACTION.

Stability Condition to Avoid:OPEN FLAMES

Hazardous Decomposition Products:AT TEMPERATURES ABOVE THE MELTING POINT, TOXIC FUMES OR VAPORS MAY BE EMITTED.

===== Toxicological Information =====

Toxicological Information:(CONTD. FROM "OTHER PRECAUTIONS")

REQUIREMENTS OF THE OSHA LEAD STANDARD (1910.1025) AND RESPIRATOR STANDARD (1910.134) SHOULD AIRBORNE EXPOSURES EXCEED THE OSHA ACTION LEVEL AND PEL.

===== Ecological Information =====

Ecological:(CONTD. FROM " WASTE DISPOSAL") RCRA STATUS OF UNUSED MATERIAL: IF DISCARDED IN UNALTERED FORM,

MATERIAL SHOULD BE TESTED

TO DETERMINE IF IT MUST BE CLASSIFIED AS A HAZARDOUS WASTE FOR DISPOSAL PURPOSES. UNDER SPECIFIC CIRCUMSTANCES, APPLICATION CAN BE MADE TO THE EPA ADMINISTRATOR TO HAVE A PARTICULAR WASTE DESIGNATED NON-HAZARDOUS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSER MUST COMPLY WITH FEDERAL, STATE, AND LOCAL DISPOSAL OR DISCHARGE LAWS. IF HAZARDOUS UNDER 40 CFR 261, SUBPARTS B AND C, MATERIAL MUST BE TREATED OR DISPOSED IN A FACILITY MEETING REQUIREMENTS OF 40 CFR 254 OR 265. IF NON-HAZARDOUS, MATERIAL SHOULD BE DISPOSED IN A FACILITY MEETING THE REQUIREMENTS OF 40 CFR 257. (CONTD. SEE "ECOLOGICAL")

===== MSDS Transport Information =====

Transport Information:NOT REGULATED BY D.O.T.

===== Regulatory Information =====

SARA Title III Information:LISTED BY SARA III SECTION 313 CHEM.:

LEAD, CAS#, 7439-92

-1; ANTIMONY, CAS# 7440-36-0; SILVER, CAS#7440-22-4.

State Regulatory Information:PROPOSITION 65: WARNING: THIS PRODUCT CONTAINS LEAD, WHICH IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.