

AMERICAN GAS AND CHEMICAL COMPANY,LTD -- LEAK-TEC OX-65C -- 6850-00-621-1819

=====
Product Identification
=====

Product ID:LEAK-TEC OX-65C
MSDS Date:07/26/1999
FSC:6850
NIIN:00-621-1819
Status Code:A
MSDS Number: CKZCP
=== Responsible Party ===
Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD
Address:220 PEGASUS AVENUE,
City:NORTHVALE
State:NJ
ZIP:07647-1904
Country:US
Info Phone Num:201-767-73
00
Emergency Phone Num:201-767-7300
Preparer's Name:ELENA FROST
CAGE:03530
=== Contractor Identification ===
Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD
Address:220 PEGASUS AVENUE,
City:NORTHVALE
State:NJ
ZIP:07647-1904
Country:US
Phone:201-767-7300
CAGE:03530

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL
CAS:107-21-1
RTECS #:KW2975000
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
Hazards Id
=====

entification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LOW HAZARD FOR INDUSTRIAL OR
COMMERCIAL HANDLING TRAINED PERSONNEL.
Explanation of Carcinogenicity:NONE REPORTED.
Effects of Overexposure:NONE REPORTED.
Medical Cond Aggravated by Exposure:NONE.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM AREA. SKIN CONTACT: WASH WITH SOAP
AND WATER. EYE CONTACT: -FLUSH WI
TH WATER. SEEK MEDICAL ATTENTION
IF IRRITATION PERSISTS. INGESTION: INDUCE VOMITING IMMEDIATELY.
CALL PHYSI CIAN AND/OR TRANSPORT TO EMERGENCY FACILITY.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE ANY SUITABLE FOR SURROUNDING MATERIAL.
Fire Fighting Procedures:USE WATER TO COOL FIRE-EXPOSED CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER. SOAK UP
WITH ABSORBENT
MATERIAL. DIKE TO CONTAIN TO PREVENT WATER POLLUTION.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE: STORE IN COOL, DRY PLACE AT
TEMPERATURES BELOW 120F. DONOT PUNCTURE OR INCINERATE AEROSOL CANS.
SHELFLIFE = 2 YRS. AEROSOL: STORE IN A COOL DRY PLACE AT
TEMPERATURES BELOW 120F. DO NOT PUNCTU RE OR INCINERATE AEROSOL
CANS.
Other Precautions:GENERAL: AVOID REPEATED OR PROLONGED CONTACT ITH
SKIN
. DO NOT GET IN EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.
Ventilation:NONE SPECIFIED BY MANUFACTURER.
Protective Gloves:NON-ABSOEBENT GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING, DRINKING OR SMOKING.
Supplemental Safety and Health
AVOID REPEATED OR PROLONGED CONTACT WITH SKIN. DO

NOT GET ON SKIN OR IN
EYES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:=111.1C, 232.F

Vapor Pres:17.5 MM HG @20C

Vapor Density:>1

pH:6-7.5

Evaporation Rate & Reference: