View NSN Online: https://aerobasegroup.com/nsn/6810-00-664-0387

MALTER INTERNATIONAL BULK CHEMICAL DIVISION -- TRICHLOROETHANE, TECHNICAL 6810-00-664-0387

============ Product Identification =========================

Product ID:TRICHLOROETHANE,TECHNICAL

MSDS Date:02/01/1989

FSC:6810

NIIN:00-664-0387 Status Code:A

MSDS Number: CKZHQ === Responsible Party ===

Company Name: MALTER INTERNATIONAL BULK CHEMICAL DIVISION

Address:80 FIRST STREET

City:GRETNA

State:LA ZIP:70053 Country:US

Info

Phone Num:504-362-3232, OR 800-535-4095

Emergency Phone Num:999-999-9999 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:27978

=== Contractor Identification ===

Company Name: MALTER INTERNATIONAL BULK CHEMICAL DIVISION

Address:80 FIRST STREET

Box:City:GRETNA

State:LA ZIP:70053 Country:US

Phone:504-362-3232, OR 800-535-4095

CAGE:27978

======= Composition/Information on Ingredients ========

Ingred Name:1,1,1 TRICHLOROMETHANE (STABILIZED)

= Wt:100.

OSHA PEL:350 PPM

=========== Hazards Identification =============
Effects of Overexposure:INHALATION: MAJOR ROUTE OF EXPOSURE-LOW
SYSTEMIC TOXICITY; ACUTE EXPOSURE IN THE 1000PPM RANGE CAUSE NARCOSIS. OVEREXPOSURE CAN CAUSE
DIZZINESS,DRUNKENNESS AND DROSINESS, UNCONSCIOUSNESS AND EVEN DEAT H AT EXTREME DOSES. SKIN CONTACT/ABSORPTION: PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE DERMATITIS
THROUGH DEFATTING OF SKIN. INGESTION: UNLIKELY ROUTE OF EXPOSURE, INGESTION OF SMALL
Q UANTITIES IS NOT LIKELY BE TOXIC.
======================================
First Aid:EYES AND SKIN: REMOVE CONTAMINATED CLOTHING AND FLUSH EXPOSED AREAS WITH WATER
FOR 5 TO 15 MINUTES. INHALATION: REMOVE TO FRESH AIR . IF BREATHING HAS STOPPED,
ADMINISTER RESPIRATION OR OXYGEN IF AVAI LABLE. INGESTION: DO NOT INDUCE VOMITING.
CALL PHYSICIAN AND OBTAIN MEDICAL ATTENTION.
======================================
Flash Point Me thod:TCC Lower Limits:7.5% Upper Limits:15.0% Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE
USED WHERE 1,1,1 TRICHLOROMETHANE IS STORED. Unusual Fire/Explosion Hazard:CONCENTRATED VAPORS CAN BE IGNITED BY
HIGH INTENSITY HEAT SOURCE. DECOMPOSITION PRODUCES HYDROGEN CHLORIDE.
========= Accidental Release Measures ==========
Spill Release Procedures:CLEN UP AREA (WEAR PROTECTIVE CLOTHING)

BY MOPPING OR WITH ABSORBENT MATERIAL TRANSFER TO CLOSED CONTAINER. ============= Handling and Storage ========================== Handling and Storage Precautions: AVOID CONTACT WITH SKIN AND AVOID BREATHING VAPORS. PIPE VENTS OUTDOOR. STORE IN COOL, DRY, VENTILATED AREA, VAPORS ARE HEAVIER THAN AIR AND WILL **COLLECT IN LOW** AREA. Other Precautions: PREVENT MOIST AIR FROM ENTERING STORGE. NO SMOKING IN PRESENCE OF VAPORS. CONTACT WITH ALUMINUM PARTS IN A PRESSURIZABLE FLUID SYSTEM MAY CAUSE VIOLENT REACTIONS. CONSULT EQUIPMENT SUPPLIER FOR FURTHE R INFORMATION. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE REQUIRED WHEN USED WITH ADEQUATE VENTILATION. Ventilation:LOCAL EXHAUST: SUFFICIENT TO MAINTAIN BELOW PEL. Protective Gloves: NEOPRENE, VITRON, POLYVINYL ALCOHOL COATED GLOVES OR EQUIVALENT. Eye Protection: CHEMICAL SAFETY GOGGLES. CONTACT LENSES SHOULD NOT BE WORN. Other Protective Equipment: HEADG EAR & APRON WHEN SPLASHING IS A PROBLEM. Supplemental Safety and Health ========= Physical/Chemical Properties =========== Boiling Pt:=87.8C, 190.F Vapor Pres:(MM HG) @20%C 100 Vapor Density:(AIR=1)4.6

Spec Gravity:(H20=1):1.3

Evaporation Rate & Evaporation R

Solubility in Water: 0.07G/100G @ 25%C

Appearance and Odor: COLORLESS CLEANLIQUID; MILDLY SWEET ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials t

o Avoid:YES

STRONG ALKALIES, OXIDIZING MATERIALS.

Stability Condition to Avoid:CONTACT WITH OPEN FLAMES, HOT SURFACES OR ELECTRIC ARCS.

Hazardous Decomposition Products:HYDROGEN CHLORIDE, PHOSGENE (SMALL AMOUNTS)

======= Disposal Considerations ===========

Waste Disposal Methods:RECOVERED LIQUIDS MAY BE SENT TO A LICENSED RECLAIMED OR INCINERATED. CONTAMINATED

ABSORBENT MATERIAL MUST BE DISPOSED OF IN A PERMITTED WASTE MANAGEMENT FACILITY.

CONSULT FEDERA

L, STATE AND LOCAL DIS POSAL AUTHORITIES FOR APPROVED PROCEDURES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibili

ty for the suitability of this information to their particular situation.