View NSN Online: https://aerobasegroup.com/nsn/8040-00-916-8534

Product ID:SCOTCH-WELD 1838-B EPOXY ADHESIVE (GREEN) MSDS Date:11/25/1997 FSC:8040 NIIN:00-916-8534 Status Code:A Kit Part:Y MSDS Number: CKZJK === Responsible Party === **Company Name:3M GENERAL OFFICES** Address:3M CENTER BLDG 224-5S-04 City:ST PAUL State:MN ZIP:55144-1000 Country: US Info Phone Num:1-800-364-3577; 651-737-6501 Emergency Phone Num:999-999-9999 Preparer's Name: HENRY SIMMONS CAGE:76381 === Contractor Identification === Company Name: MINNESOTA MINING AND MFG CO, DBA 3M Address:3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381

Ingred Name:EPOXY RESIN CAS:25068-38-6 Code:F RTECS #:CE6880000 Minumum % Wt:70. Maxumum % Wt:80.

Ingred Name:KAOLIN CAS:1332-58-7 RTECS #:GF1670500 Minumum % Wt:20. Maxumum % Wt:30. OSHA PEL:15 MG/M3 ACGIH TLV:2 MG/M3

Ingred Name:NATURAL CALCIUM CARBONATE CAS:1317-65-3 RTECS #:EV9580000 Minumum % Wt:1. Maxumum % Wt:5. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Minumum % Wt:.1 Maxumum % Wt:1. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:BENTONITE, BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM COMPLEX CAS:68953-58-2 RTECS #:UZ2996400 Minumum % Wt:1. Maxumum % Wt:5.

Effects of Overexposure:EYE CONTACT: MODERATE EYE IRRITATION: SIGNS/SYMPTOMS CAN INCLUDE REDNESS, SWELLING, PAIN, TEARING, AND HAZY VISION. VAPORS FROM HEATED MATERIAL MAY CAUSE EYE IRRITATION. SKIN CONTACT: ALLERGIC SKIN R EACTION: SIGN/SYMPTOMS CAN INCLUDE REDNESS, SWELLING, BLISTERING, AND ITCHING. MILD SKIN IRRITATION: SIGNS/SYMPTOMS CAN INCLUDE REDNESS, SW

 ELLING, AND ITCHING. INHALATION: IRRITATION (UPPER RESPIRATOR Y):SIGNS/SYMPTOMS CAN INCLUDE SORENESS OF THE NOSE AND THROAT, COUGHING AND SNEEZING. VAPORS OF HEATED MATERIAL MAY CAUSE RESPIRATORY SYSTEM IRRITATION. IF SWALLOWED:INGESTION MAY CAUSE: IRRITATION OF GASTROINTESTINAL TISSUES.
======================================
First Aid:EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN CONTACT : IMMEDIATELY WASH SKIN WITH SOAP AND LARGE
AMOUNTS OF WATER. REMOVE CONTAMINATED CLOTHING BEFORE REUSE AND DISPOSE OF
CONTAMINATED SHOES. INHALATION: IF SIGN/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR.
IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN. IF SWALLOWED: DO NOT INDUCE VOMITING.
DRI NK TWO GLASSES OF WATER. CALL A PHYSICIAN.
======================================
Extinguishing Media:WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Pr ocedures:WEAR FULL PROTECTIVE CLOTHING INCLUDING HELMET, SELF ?CONTAINED, POSITIVE PRESSURE OR PRESSURE DEMAND BREATHING APPARATUS, BUNKER COAT AND PANTS, BANDS AROUND ARMS, WAIST AND LEGS, FACE MASK, AND PROT ECTIVE COVERING FOR EXPOSED AREAS OF THE HEAD. Unusual Fire/Explosion Hazard:NONE KNOWN.
======================================
Spill Release Procedures:REFER TO OTHER SECTIONS OF THIS MSDS FOR INFORMATION REGARDING PHYSICAL AND HEALTH HAZ
ARDS, RESPIRATORY PROTECTION, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT.
COVER WITH ABSORBENT MATERIAL. COLLE CT SPILLED MATERIAL. PLACE IN A U.S.
DOT-APPROVED CONTAINER.
======================================
Handling and Storage Precautions:STORE AWAY FROM HEAT. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:PREVENTION OF ACCIDENTAL INGESTION: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. WASH EXPOSED AREAS THOROUGHLY WITH SOAP AND WA

TER. DO NOT

DIGEST. FIRE

AND EXPLOSION AVOIDANCE. KEEP CONTAINER T IGHTLY CLOSED.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: AVOID BREATHING OF VAPORS CREATED DURING THE CURE CYCLE. AVOID BREATHING OF DUST CREATED BY CUTTING, SANDING, OR GRINDING. SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONC ENTRATION OF CONTEMINANTS AND IN ACCORDANCE WITH OSHA REGULATIONS; HALF MASK DUST RESPIRATOR. Ventilatio

n:PROVIDE APPROPRIATE LOCAL EXHAUST FOR GRINDING, CUTTING OR SANDING CURED MATERIAL.

Protective Gloves: AVOID SKIN CONTACT. WEAR APPROPRIATE GLOVES WHEN HANDLING THIS MATERIAL.

Eye Protection: AVOID EYE CONTACT. WEAR VENTED GOGGLES. WEAR SAFETY GLASSES WITH SIDE SHIELDS.

Supplemental Safety and Health

Spec Gravity:1.300 GM/ML Viscosity:PASTE Solubility in Water:VERY SLIGHT Appearance and Odor:VISCOUS PASTE, WHITE, L ITTLE ODOR Percent Volatiles by Volume:0%

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, STRONG OXIDIZING AGENTS, HEAT IS GENERATED DURING CURE. DO NOT CURE A MASS LARGER THAN 50 GRAMS IN A CONFINED SPACE TO PREVENT A PREMATURE REACTION (EXOTHERM) WITH A PRODUCTION OF INTENSE HEAT AND SMOKE.
Hazardous Decomposition Products:CARBON MONOXIDE, AND CARBON DIOXIDE, ALDEHYDES, KETONES, HYDROCARBONS, TOXIC
VAPORS, GASES OR PARTICULATES.

Waste Disposal Methods:CURE PRODUCT ACCORDING TO PRODUCT INSTRUCTIONS. INCINERATE UNCURED WASTE IN AN INDUSTRIAL OR COMMERCIAL INCINERATOR. DISPOSE OF COMPLETELY CURED (OR POLYMERIZED) MATERIAL IN A SANITARY LANDFILL.

Federal Regulatory Information: VOLATILE ORGANIC COMPOUNDS: 0 GMS/LITER. VOC LESS H20 & EXEMPT SOLVENTS: 0 GMS/LITER HAZARDOUS AIR

POLLUTANTS: 0 % BY WT (0 LBS. HAPS/LBS. SOLIDS) SINCE REGULATIONS VERY, CONSULT APPLICABLE REGULAT IONS OR AUTHORITIES BEFORE DISPOSAL; U.S. EPA HAZARDOUS WASTE NUMBER = NONE (NOT U.S EPA HAZARDOUS)

State Regulatory Information:

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expr

essly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.