

WACO INC -- MARINE ACCOUSTICAL HULLBOARD -- 5640-00-756-5866

=====  
Product Identification  
=====

Product ID:MARINE ACCOUSTICAL HULLBOARD

MSDS Date:12/04/1986

FSC:5640

NIIN:00-756-5866

Status Code:A

MSDS Number: CLBCG

=== Responsible Party ===

Company Name:WACO INC

Address:5450 LEWIS ROAD

City:SANDSTON

State:VA

ZIP:23150

Country:US

Info Phone Num:804-222-8440

Emergency Phone Num:0000000000

CAGE:1B8

32

=== Contractor Identification ===

Company Name:WACO INC

Address:5450 LEWIS ROAD

Box:City:SANDSTON

State:VA

ZIP:23150

Country:US

Phone:804-222-8440

CAGE:1B832

=====  
Composition/Information on Ingredients  
=====

Ingred Name:FIBROUS GLASS

CAS:65996-61-4

ACGIH TLV:5 MG/M3

Ingred Name:PHENOLIC RESIN (CURED)

CAS:25085-50-1

Ingred Name:ACRYLIC ADHESIVE

CAS:79-10-7

RTECS #:AS4375000

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
Hazards Identification  
=====

=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:DIRECT EYE CONTACT WILL CAUSE  
MECHANICAL IRRITATION. SKIN CONTACT MAY CAUSE TRANSITORY MECHANICAL  
DERMITITIS. SKIN ABSORBTION DOES NOT OCCUR.  
Effects of Overexposure:REDNESS OF SKIN DUE TO MECHANICAL IRRITATION,  
WATERING EYES IN EVENT FIBERS GET IN EYES.  
Medical Cond Aggravated by Exposure:BRONCHIAL CONGESTION, HIGHLY  
ALLERGIC INDIVIDUALS.

===== First Aid Measu  
res =====

First Aid:EYE CONTACT: FLUSH EYE WITH FLOWING WATER FOR AT LEAST 15  
MINITUES. SKIN CONTACT: FREQUENT RINSING OF SKIN SURFACE TO REMOVE  
ACCUMULATED FIBERS WILL MINIMIZE IRRITATION.

===== Fire Fighting Measures =====

Extinguishing Media:WATER, FOAM, CO2 OR CHEMICAL  
Fire Fighting Procedures:USE SCBA. FIBEROUS GLASS NON-FLAMMABLE. BINDER  
WILL PYROLIZE IN MAJOR CONFLAGRATION.  
Unusual Fire/Explosion Hazard:CO2, CO, AROMATIC  
HYDROCARBONS

===== Accidental Release Measures =====

Spill Release Procedures:VACCUM CLEAN DUST. USE A DUST SUPPRESSANT IF  
SWEEPING IS NECESSARY.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP MATERIAL DRY AND MINIMIZE  
GENERATION OF DUST.  
Other Precautions:WASH WORK CLOTHES SEPERATELY FROM OTHER CLOTHING TO  
PREVENT GLASS FIBER MIGRATION. RINSE WASHER THOROUGHLY.

===== Exposure Controls  
/Personal Protection =====

Respiratory Protection:A DISPOSABLE MASK DESIGNED FOR NUISANCE DUST  
SHOULD BE USED.  
Protective Gloves:RECCOMMENDED  
Eye Protection:GOGGLES  
Other Protective Equipment:WEAR LONG SLEEVED, LOOSE FITTING CLOTHING  
AND HEAD COVERING.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Melt/Freeze Pt:=1371.1C, #####F  
M.P/F.P Text:2500F  
Appearance and Odor:FIBEROUS GLASS BOARD COMPOSITE; NO APPRECIABLE ODOR

==

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
HYDROFLURIC ACID WILL DISSOLVE GLASS

===== Disposal Considerations =====

Waste Disposal Methods: GENERALLY CLASSIFIED AS A NON-HAZARDOUS WASTE  
AND DISPOSAL MAY BE IN A LANDFILL FOR NON-CRITICAL MATERIALS. LOCAL  
REGULATIONS SHOULD BE CONSULTED.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.