View NSN Online: https://aerobasegroup.com/nsn/5640-01-074-7875 THERMAL CERAMICS -- KAOWOOL -- 5640-01-074-7875 ============ Product Identification ========================= Product ID:KAOWOOL MSDS Date:03/15/1995 FSC:5640 NIIN:01-074-7875 Status Code:A MSDS Number: CLBLG === Responsible Party === Company Name: THERMAL CERAMICS Address:P.O. BOX 923 MS 300 City: AUGUSTA State:GA ZIP:30903 Country:US Info Phone Num:800-722-5681 Emergency Phone Num:0000000000 CAGE:0UHC8 === Contractor Ident ification === Company Name: THERMAL CERAMICS Address:P.O. BOX 923 MS 300 Box:City:AUGUSTA State:GA ZIP:30903 Country:US Phone:800-722-5681 CAGE:0UHC8 ======= Composition/Information on Ingredients ======== Ingred Name: REFACTORIES, FIBERS, ALUMINOSILICATE CAS:1332-21-4 RTECS #:CI6475000 Minumum % Wt:95. Maxumum % Wt:100. OSHA PEL:15 MG/M3

ACGIH TLV:5 MG/M3 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

=========== Hazards Identification ===============

Reports of Carcinogenic

ity:NTP:UNKNOWN IARC:YES

Health Hazards Acute and Chronic:DUST AND RESPIRABLE FIBERS FROM THIS PRODUCT MAY AGGRAVATE EXISTING CHRONIC LUNG CONDITIONS SUCH AS BRONCHITIS, EMPHYSEMA AND ASTHMA. TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM AND LUNGS. UPPER RES PIRATORY PHYSICAL IRRITATION. IRRITATION AND INFLAMMATION TO THE EYES ON CONTACT AND TO THE SKIN ON PROLONGED CONTACT.

Explanation of Carcinogenicity:RFC ALONG WITH FIBEROUS GLASSWOOL AND MINERAL WOOL AS POSSIABLE H

UMAN CARCINOGENS.

Effects of Overexposure:EYE CONTACT: PHYSICAL IRRITATION AND INFLAMMATION. SKIN CONTACT: PHYSICAL IRRITATION AND RASH. INGESTION: MAY CAUSE TEMPORARY IRRITATION TO THE GASTROINTESTIONAL TRACT. INHALATION: IRRITATION OR SOREN ESS IN THROAT, NOSE AND RESPIRATORY TRACT.

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINITUES. DO NOT RUB EYES. SKIN CONTACT: WASH AFFE CTED AREA

GENTLY WITH SOAP AND WATER. SKIN CREAM OR LOTION AFTER WASHING MAY BE HELPFUL. INGESTION: DO NOT INDUCE VOMITING, DRINK PLENTY OF WATER. INHALATION: REMOVE AFFECTED PERSON TO CLEAN FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES IF SYMPTOMS PERSIST.

============ Fire Fighting Measures =========================

Extinguishing Media:NON COMBUSTIABLE. USE EXTINGUISHING MEDIA APPROPIATE IN THE SURROUNDING FIRE. Fire Fighting Procedures:WEAR FULL BUNKER GEAR IN CLUDING POSITIVE PRESSURE SCBA.

======== Accidental Release Measures ============

Spill Release Procedures: AVOID CREATING AIRBORNE DUST. FOLLOW ROUTINE HOUSEKEEPING PROCEDURES. VACCUM ONLY WITH HEPA FILTERED EQUIPMENT. IF SWEEPING IS NECESSARY USE A DUST SUPPRESSANT AND PLACE MATERIAL IN CONTAINERS. DO NOT USE COMPRESSED AIR. PERSONNEL SHOULD WEAR GLOVES AND APPROVED RESPIRATOE. AVOID CLEAN-UP PROCEDURES THAT COULD RESULT IN WATER POLLUTION.

=======

======= Handling and Storage ==========
Handling and Storage Precautions:THIS PRODUCT IS STABLE UNDER ALL CONDITIONS OF STORAGE. STORE IN ORIGINAL FACTORY CONTAINER IN A DRY AREA. KEEP CONTAINER CLOSED WHEN NOT IN USE. FOLLOW ALL MSDS/LABEL PRECAUTIONS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF NEEDED USE APPROVED RESPIRATOR. SEE HARD COPY MSDS FOR SPECIFIC APPLICATIONS.  Ventilation:YES  Protective Gloves:Y ES
Eye Protection:GOGGLES SAFETY GLASSES WITH SIDESHIELDS Other Protective Equipment:LONG SLEEVED SHIRTS, PANTS AND HAT. Work Hygienic Practices:WASH EXPOSED CLOTHING SEPERATELY FROM OTHER CLOTHING AND RINSE WASHER THROUGHLY. Supplemental Safety and Health
========= Physical/Chemical Properties ==========
Melt/Freeze Pt:>1760.C, #####F M.P/F.P Text:>3200 F (1768C) Spec Gravity:2.50-2.70 Solubility in Water:NOT SOLUABLE Appearance and Odor:WHITE ODORLESS WOOL-LIKE FIBERO US MATERIAL Percent Volatiles by Volume:0
======== Stability and Reactivity Data =========
HYDROFLURIC ACID, PHOSPHORIC ACID, STRONG ALKALIES.
======== Toxicological Information =========
Toxicological Information: A STATISTICAL TREND WAS OBSERVED IN THE

Toxicological Information:A STATISTICAL TREND WAS OBSERVED IN THE EXPOSED POPULATION BETWEEN THE DURATION OF EXPOSURE TO RFC AND A DECREASED IN SOME MEASURES OF PULMONARY FUNCTION.THESE OBSERVATIONS ARE CLINICALLY INSIGNIFICAN T.IN OTHER WORDS IF THESE OB

## **SERVATIONS**

WERE MADE ON AN INDIVIDUAL EMPLOYEE THE RESULTS WOULD BE INTERPUTED AS BEING WITHIN NORMAL RANGE. PLEURAL PLAQUES HAVE BEEN OBSERVED IN A SMALL NUMBER OF EMPLOYE ES WHO HAD A LONG DURATION OF EMPLOYMENT. THER ARE SEVERAL OCCUPATIONAL AND NON-OCCUPATIONAL CAUSES FOR PLEURAL PLAQUE. IT SHOULD BE NOTED THAT PLAQUES ARE NOT PRE-CANCER NOT ARE THEY ASSOCIATED WITH AN Y MEASURABLE EFFECT ON LUNG FUNCTION.

	Disposal Considerations	=========
=======		

Waste Disposal Methods:TO PREVENT WASTE FIBERS BECOMING AIRBORNE A COVERED CONTAINER OR PLASTIC BAGGING IS RECOMMENDED. COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS. LANDFILL. CHEMICAL ADITIONS PROCESSING OR OTHERWISE A LTERING THIS MATERIAL MAY MAKE THE WASTE MANAGEMENT INFO PRESENTED IN THIS MSDS INCOMPLETE, INACCUR ATE OR OTHERWISE INAPPROPIATE.

g ,	
State Regulatory Information:CALIFORNIA PRO P 65: CERMAIC FIBERS.	
======= Other Information =	

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.